Shop Supplies

SECTION	PAGE NO.
TAPES	4-1-1 TO 8
HAND TOOLS	4-2-1 TO 14
MAINTENANCE TOOLS SUPPLIES	4-3-1 TO 22
WELDING	4-4-1 TO 14
SAFETY PRODUCTS	4-5-1 TO 14

TABLE OF CONTENTS

1 TAPES	— VON DREHLE FACIAL TISSUE	
SHIPPING SUPPLIES4-1-8	— VON DREHLE FOLDED TOWELS	4-3-13
TAPE	— VON DREHLE HARDWOUND TOWELS	4-3-14
— ATTACHMENT4-1-6	— VON DREHLE JUMBO ROLL TOILET TISSUE	4-3-15
— AUTOBODY TAPES & SUPPLIES4-1-3	SHOP TOWELS & WIPES	4-3-9
— ELECTRICAL4-1-1	SPILL CONTROL	
— LABELING4-1-5	— ABSORBENTS	4-3-22
— MASKING4-1-3	— SPILL KITS	
— PACKAGING4-1-8		
— SAFETY4-1-4	SYR CLEANING PRODUCTS	4-3-20
— SEALING4-1-7	TOOLS	
— VELCRO4-1-8	— BLOW GUNS	4-3-2
2 HAND TOOLS	— MAGNETS	4-3-5
2 HAND TOOLS	— PNEUMATIC	4-3-1
MTAMPER RESISTANT SCREWS — REMOVAL TOOLS	— RAZOR BLADE & UTILITY KNIVES	
TOOLS	— SCRAPERS	
— ADJUSTABLE WRENCHES	TRASH CAN LINERS	
— CLAMPTITE™ BINDING	WIPERS	
— COMBINATION WRENCHES		420
— FOLDING HEX KEY SETS	— TORK ADVANCED 430	
— HAMMERS	— TORK ADVANCED 450	
— HAND TOOL WARRANTY INFORMATION	— TORK DISPENSERS	
— HEX &TORX KEYS	— TORK PREMIUM 510/530 MULTI-PURPOSE CLOTH	4-3-8
— HEX BIT KITS, INSERTS & ACCESSORIES	— TORK WASHROOM REFILLS	4-3-9
— HEX KEY SETS		
— HEX KEYS	4 WELDING	
— LEVELS. 4-2-14	WELDING	
— PLIERS	— ACCESSORIES	4.4.0
— POWER BITS & NUT SETTERS		
— PUNCHES & CHISELS	— BRAZING ROD	
— SCREWDRIVERS 4-2-2	— CABLE	
— SOCKET SETS 4-2-1	— CHARTS	
— SOCKETS 1/2"4-2-1	— CHEMICALS	4-4-12
— SOCKETS 3/8" 4-2-1	— ELECTRODES	4-4-2
— TAPE MEASURES 4-2-13	— EYE PROTECTION	4-4-14
— T-HANDLE HEX KEYS 4-2-10	— MACHINE	4-4-1
— TOOL HOLDERS 4-2-14	— MIG WIRE	
	— SAFETY	
3 MAINTENANCE TOOLS SUPPLIES	— SOLDER	
AUTO DETAIL — APPLICATORS, SPONGES & TOWELS4-3-21	— STAR ALLOYS WELDING SUPPLIES	
BROOMS — FLOOR4-3-18		
BRUSHES4-3-16	— STUDS	
DRILL — CHUCKS & CHUCK EYES4-3-1	— TIG WIRE	4-4-6
GEORGIA PACIFIC — MULTI-FOLD & C-FOLD TOWELS		
LUBRICATION EQUIPMENT	5 SAFETY PRODUCTS	
— COUPLERS & ADAPTERS	SAFETY	
— GREASE GUNS HOSES	— DISPOSABLE GLOVES	4-5-1
	— EYE PROTECTION	
PAINT SUPPLIES — PUTTY & JOINT KNIVES4-3-18	— FALL PROTECTION.	
— POTTY & JOINT KNIVES	— FIRST AID	
PAPER		
— GEORGIA PACIFIC BATHROOM TISSUE	— GLASSES	
— GEORGIA PACIFIC BATHROOM 11550E	— GLOVES	
— GEORGIA PACIFIC CENTERPOLL TOWELS	— HEAD & FACE PROTECTION	4-5-6
— GEORGIA PACIFIC ENMOTION ROLL TOWELS	— HEARING PROTECTION	4-5-6
— GEORGIA PACIFIC PACIAL 11330E	— MISCELLANEOUS PROTECTION	4-5-9
— VON DREHLE BATHROOM TISSUE	— PERSONAL PROTECTION	4-5-13
— VON DREHLE CENTERPULL TOWELS	— RESPIRATORS	
TOTAL CHATCH OFF TOTAL CONTROL OF THE CONTROL OF TH	RESTRICTIONS	

Copyright © 2023

WEKNOW MRO

TAPE — ELECTRICAL

PLASTI DIP[®] LIQUID ELECTRICAL TAPE

Color	Net Contents	Part No.
Red	4 fl. oz. (118 ML)	F4212
Black	4 fl. oz. (118 ML)	F41070

- An air-dry, synthetic rubber coating with applicator brush in cap Will not unravel like tape or crack, harden or peel

- Exhibits excellent moisture, acid, alkaline, abrasion, and dielectric resistance. Can be used to seal, insulate, protect, and color code connections Remains flexible even under extreme conditions

Size

3/4 x 66

3/4 x 66′ 3/4 x 66′

Applications: Electrical connections and components for boats, trailers, RVs, auto and trucks, timers, outdoor wiring, repair damaged extension cord casings, instruments, computers, circuit boards, switches, accessory light connections and more.



SCOTCH® SUPER 33+™ VINYL ELECTRICAL TAPE



Size	3M Part No.	Part No.
3/4" x 20'	06130	F41225
3/4" x 66'	06132	F4733
3/4" x 52'	06133	F4611
- 0		6 114 1 11

- The first and only 7-mil "one tape for all jobs"
 It wraps and holds in all weather and will continue to perform in sub-zero temperatures or in continuous temperature environment up to 220°F (105°C) Conforms remarkably well
- Resistant to oil, water, wear, chemicals and solvents
- Voltage Range: up to 600v Flame Retardant



SCOTCH® 35 VINYL ELECTRICAL TAPE FOR COLOR CODING 35 3M Part No

10836

10885

00072

10869

10810

10271

10828

Color

Blue

Brown

Gray

Green

Orange

Red

Violet

White

Yellow







- Suited for all-weather conditions
- Excellent electrical insulating
- F24830 colored tape assortment 1 roll of each color

SCOTCH® VINYL PLASTIC ELECTRICAL TAPE SUPER 88





- Suited for cold weather applications
- Remains flexible



3M™ RUBBER SPLICING TAPE 130C			
Size	3M Part No.	Part No.	
3/4" x 30'	41717	F4881	
1"x30'	41753	F4806	
1-1/2" x 30'	41718	F41524	

- Self-bonding ethylene propylene rubber (EPR) Linerless, highly conformable
- Weather resistant
- Temperature rating: 90°C continuous operation 130°C intermittent
- Use for low and high voltage applications (through 69 kV)



ELECTRICAL TAPE

Size	Part No.	
3/4" x 66'	F4721	
1" x 66'	F477	

- 7 Mil Thickness
- Pressure Sensitive
- Resistant to sun, water, oil, acids, alkalies and corrosive chemicals
- Temperature rating: Max 176°F (80°C)
- Uses: General splicing or as a protective outer jacket



3M™ TEMFLEX™ VINYL

ELECTRICAL TAPE 165		
Size	3M Part No.	Part No.
3/4×60′	69254	F44807

- $Flame\ retardant\ and\ weather\ resistant$
- **Voltage Range:** up to 600V **Temperature Range:** up to 194°F



ALL WEATHER INSULATING TAPE

Size	Color	Part No.
3/4 x 66'	Black	F4790

- 7 Mil Thickness
- Highly resistant to sun, water, oil, acid, alkalines, corrosive
- chemicals **UL** Approved
- Temperature rating: Max. 176° F (80° C)



TAPES — ELECTRICAL (continued)

COLD SHRINK TAPE

Color	Size	Part No.
Black	1" x 10'	F4260
Black	1" x 30'	F4153



- Self-amalgamating ethylene propylene rubber (EPR) "welds" itself chemically and mechanically to form a watertight skin
- Resists abrasion, impact, sunlight, ozone and most chemicals
- Requires no heat or flame **Temperature Range:** -40°C to 100°C and 130°C intermittently
- Dielectric Strength: 36 KV/mm

Automotive: Insulate battery terminal ends and starter ends to prevent shorting and corrosion.

Industrial: Insulate power cables up to 69 KV, waterproof telecommunications $cable\,above\,or\,below\,ground, wrap\,metal\,pipework\,for\,corrosion\,protection.$

- 1. Strip back film and stretch tape to reduce its width by between 1/3 or 1/2. 2. Keep tape under tension and wrap, overlapping each wrap by 50% until desired buildup of insulation is achieved.
- $\textbf{3.} \ \textbf{Finish} \ wrapping \ \textbf{by holding the tape under thumb and snap by stretching.}$

3M™ CLOTH FRICTION TAPE



Size	3M Part No.	Part No.
3/4" x 60'	50218	F4325
2" x 60'		F4563

- Used for sealing low voltage splices
- Excellent abrasion resistance



SCOTCH® ELECTRICAL MOISTURE **SEALANT TAPE**





06147 Quick and easy method of moisture-proofing electrical connections Protects against vibration, road grime and abrasion

3M Part No.



WRAP 'N SEAL SELF-FUSING SILICONE TAPE

Color	Part No.
Black	F41674
Red	F41336

- 1" x 20' roll
- Self-adhering silicone tape has no adhesive and leaves no sticky residue
- Fuses and cures to itself within 24 hours to form a permanent moisture tight seal
- Excellent choice for high temperature applications **Thickness:** .002"
- Operating Temperature: -65°F to +500°F
- **Dielectric Strength:** 400 volts per mil (vpm) **Tensile Strength:** 700 PSI

- Elongation: 300% Meets MIL-I-46852C Type I and II



SELF-FUSING TAPE

Thickness	Color	Part No.
20 mil.	Gray	F41677

1" x 12 yd. roll

Size

2-1/2" x 10'

- Silicone rubber tape provides an insulative barrier that is resistant to moisture, ozone and cozona
- Temperature Range: -65°F to 500°F



SELF- FUSING SILICONE TAPE

Thickness	Color	Part No.
0.030	Red	F44185
4" 44 1 11		

- " x 36 yd. roll
- Flexible Fits irregular shapes Withstands -65° F to 500° F
- Excellent Dielectric strength Low Profile and Aesthetic
- Contains No Glues or Adhesive
- **Excellent Resistances**



SCOTCH® GLASS CLOTH TAPE 27



- 7 Mil Thickness
- Pressure-sensitive rubber thermosetting adhesive Excellent tensile (150 lb/in) and dielectric strength (3000 volts)
- Temperature rating: 266°F (130°C)
- **Applications:** Insulating electric and induction furnace power supply leads, splicing wire that is rated at 130°C, securing systems requiring high mechanical strength and resistance to high temperatures, insulating motor lead connections, switches and controls for furnaces and ovens, reinforcing insulation in electrical installations where heavy loads cause high heat and breakdown of original insulation (e.g., motor leads and switches)



SCOTCH* FIRE RETARDANT ELECTRIC ARC **PROOFING TAPE 77**

- Designed to protect all types of electric cables where exposed to potential failures of other high voltage cables or exposed to other . high energy cables
- Extremely conformable, easily wraps irregular shapes Provides fault arc protection to adjacent wrapped cables and
- Self-extinguishing, will not propagate flame
 Non-corrosive to metallic cable sheaths and compatible with synthetic
- cable jackets (i.e. semiconducting URD type, polyethylene, PVC, etc.)
- Resistant to water, salt water, acids, sewage, and ultraviolet light **Thickness:** 30 mils (.030")
- Color: Black

TAPE — MASKING

PAINTER'S MASKING TAPE

	··· -
Size	Part No.
3/4" Wide x 60 Yards	F41694
1" Wide x 60 Yards	F4372
1-1/2" Wide x 60 Yards	F4956
2" Wide x 60 Yards	F41222




High heat range (275°F) allows for expansion under heat without lifting Highly conformable; easily applied to curved surfaces Strong adhesive bonding force to surfaces or to itself, yet strips cleanly and easily

SCOTCH° AUTOMOTIVE REFINISH MASKING TAPE 233+








Provides outstanding paint lines and a controlled, consistent unwind

Consistent performance under a variety of climactic conditions

Color: Green


SCOTCH® PLASTIC TAPE 471 — BLUE






- Superior holding power Packaged in individual poly bags

SCOTCH° LONG MASK™ **MASKING TAPE 2090**







Controlled crepe paper backing makes tape conformable and smooth for use when masking around damaged window, door and trunk openings

Color: Blue

3M™ GENERAL PURPOSE MASKING **TAPF 200**

17 ti E 200			
Size	3M Part No.	Part No.	
1" x 60 yards	71180	F4831	
2" x 60 yards	71177	F4653	
3" x 60 yards	71176	F4302	

- Utility grade paper masking tape
- Use for non-critical masking, sealing, and holding applications Not recommended for paint masking



3M™ DOOR APERTURE REFINISH

IAI L (D.A.	11.1./		
Size	Roll Size	3M Part No.	Part No.
12mm (1/2")	54.6 yds. (50 meters)	06297	F41061



- Soft edge foam masking tape Designed to be used in masking door jams, hood or deck lid openings or other areas of a vehicle which need to be sealed during the painting operation
- Provides a "soft edge" to prevent tape lines in the jam areas

TAPE — AUTOBODY TAPES & SUPPLIES


WRFCK WRAP

WILLERWIN			
Size	Part No.		
36" x 100'	F4457		

- Protects vehicle interior from rain, wind, snow, dirt, etc.
- Adheres to any clean, dry surface glass, metal, plastic and interior surfaces & fabric Can easily be peeled off without leaving any adhesive behind
- Can also be used for vehicle & sign transport protection and over-spray protection on building/home & glass

3M™ SEAM SEALER TAPE






- Self-adhering
- Directly and immediately paintable
 Designed to duplicate factory appearance on hem flanges, door jams and trunk gutter applications



TAPES — AUTOBODY TAPES & SUPPLIES (continued)

SURFACE PROTECTION TAPE



DURING ASSEMBLY

- Rework or cleaning can be avoided if interior surfaces are protected
- Suitable for rough surfaces due to the high adhesive level Standard polypropylene tape
- Color: Ivory

ANTI-ABRASION TAPE - RED

- 2" X 55yd
- Protects against over-sanding and scratching of body panels during paint prep
- Eliminates costly repaints
- More durable than masking tape Will not leave glue residue when removed



TRIM LIFTING TAPE F41143

- A specially designed masking tape with a flexable, clear plastic edge used for masking around wind shields, tail lights and sunroofs

- 10mm wide clear plastic strip Pertorated every 2 inches for easy tear off



TAPE — SAFETY


REFLEXITE® DOT CONSPICUITY (REFLECTIVE) TAPE

(ILLI LECTIVE) I/II L			
Size Style Part No.		Part No.	
2" x 150' Roll	Alternating 7" White and 11" Red Stripes	F41454	
2" x 150' Roll	Alternating 6" White and 6" Red Stripes	F4323	
2" x 150' Roll	Solid White	F454	
2" x 18" Strip	7" White and 11" Red Stripes	F41198	
1" x 150' Roll	School Bus Yellow Solid Yellow	F84356	
2" x 150' Roll	School Bus Yellow Solid Yellow	F84076	

- Enhanced daytime color Exceeds all minimum requirements for school bus conspicuity tape
- Impact resistant maintains photometric performance after impact - maintains conspicuity after collision or years of wear **Easy to apply** - thin and flexible with 100% adhesion. Superior
- durability with stands high pressure washing and resists edge lift

 OEM preferred can be riveted; no edge sealing requiredw







- Designed to mark the side andrear perimeter of trucks and trailers for enhanced visibility and detection In compliance with NHTSA ruling and DOT-C2 certification
- Guaranteed to meet NHTSA's minimum specifications for seven (7) years

TAPE — **SAFETY** (continued)

3M™ CONFORMABLE SAFETY WALK"





- Conformable slip-resistant material
- Adhesive backed roll
- Special aluminum backing conforms around corners and adheres to irregular surfaces
- Color: Black
- For use on steps and ladder rungs, heavy equipment, and vehicles

HIGH TRACTION SAFETY TAPE — ANTI SLIP

Color	Size	Part No.
Black	3" x 60'	F41074
Black	6" x 60'	F4365

- Thin tough waterproof silicone carbide fabric, coated with mineral partcles
- Adhesive backed
- Application: Use on ramps, staies, cab steps, and in plants where oily conditions exist



3M™ SAFETY WALK™



Size	3M Part No.	Part No.
1" x 60'	19220	F4749
2"x60'	19221	F4249
4" x 60'	19223	F41170

- General Purpose slip-resistant material
- Adhesive backed roll **Color:** Black
- For use on smooth, flat surfaces such as walkways, stairways, loading docks, etc.



SCHOOL BUS YELLOW CONSPICUITY TAPE

Size	Part No.
1" x 150'	F84356
2" x 150'	F84076

- **Enhanced daytime color** Exceeds all minimum requirements for school bus conspicuity tape
- Impact resistant maintains photometric performance after impact maintains conspicuity after collision or years of wear. **Easy to apply** - thin and flexible with 100% adhesion. Superior
- durability withstands high pressure washing and resists edge lift **OEM preferred** can be riveted; no edge sealing required.



FLAGGING TAPE

Color	Size	Part No.
Glo-Orange	2"x600'	F4215

- High tensile strength, resistant to breaking or tearing Remains pliable, resist cracking even in the coldest weather
- Used to identify boundries for surveying work, construction projects , recreational applications and for marking any other area.



AISLE MARKING TAPE

Color	Size	Part No.
Yellow	2" x 36 yards	F4286
Yellow/Black	2" x 36 yards	F4433
Red	2" x 36 yards	F41115
Blue	2" x 36 yards	F4779
Orange	2" x 36 yards	F4557
Yellow/Black	4" x 36 yards	F41568

- Material: Polyvinyl Chloride (PVC) with synthetic rubber adhesive
- Used for a wide range of color coding applications, lane marking and safety coding to meet OSHA requirements
- Durable, puncture and tear resistant



BARRICADE TAPE

Description	Color	Size	Part No.
Caution	Black on Yellow	3" x 200'	F479
Caution	Black on Yellow	3" x 1000'	F4495
Caution Do Not Enter	Black on Yellow	3" x 1000"	F4531

- Poly barricade tape for warning at temporary safety hazards
- Econmical, strong and disposable







TAPE — LABELING



POST-IT® REMOVABLE LABELING TAPE

Size	3M Part No.	Part No.
2" x 36 yards	06951	F41028

- White, general purpose labeling tape that is easily removable Use for shelf and bin marking and package identification
- Works great for correction and cover-up work.
- $Use \ for \ work \ piece \ and \ body \ parts \ temporary \ identification$



TAPE — ATTACHMENT

3M™ SCOTCH-MOUNT™ DOUBLE-COATED **ACRYLIC FOAM TAPE**



Size	Color	3M Part No.	Part No.
1/2" x 20 yards	White	06380	F4164
7/8" x 20 yards	White	06381	F4699
1/2" x 20 yards	Black	06382	F4362
7/8" x 20 yards	Black	06383	F41329

- OEM approved for attaching body side moldings, fascia nerf strips, bumper trim, wheel lip and door edge moldings, claddings, etc.
- Resists stress Good cold temperature adhesion
- Thickness: 1.2mm (.045")





3M™ SCOTCH-MOUNT™ DOUBLE-COATED **ACRYLIC FOAM TAPE**



Size	Color	3M Part No.	Part No.
1/2" x 10 yards	Black	06397	F41263
1" x 72 yards	White		F4187
			requiring a thicker tap impensate for part-to-

- body mismatch OEM approved for attaching body side moldings, fascia nerf strips, bumper trim, door edge moldings, claddings, and a wide variety of
- other trim components Good initial and cold temperature adhesion
- Thickness: 1.8mm (.060")





3M™ SCOTCH-MOUNT™ **NAMEPLATE REPAIR TAPE**



3M Part No. Size Color Part No. .23" x 5' yards Gray 06385 F4649

- Automotive acrylic foam tape
- Adheres emblems, nameplates, etc. to vehicle surfaces
- Thinner foam allows for a flush mount to the vehicle's surface
- Thickness: 0.8mm (.030")
- Permanently adheres to OEM and aftermarket paint systems



3M™ DOUBLE-COATED POLYETHYLENE FOAM TAPE



Size	Thickness	3M Part No.	Part No.
3/4" x 72 yards	.8mm (.031")	04492W	F41072
1" x 36 yards	1.6mm (.062")	04496W	F41614

- Conformable closed cell foam
- High strength acrylic adhesive provides good initial tack & offers high ultimate adhesion to a wide variety a of surfaces



3M™ DOUBLE-COATED



- 1" x 36 yards 1/16" F41732 $Ideal\,for\,a\,multitude\,of\,general\,purpose, indoor\,mounting\,and$ joining applications
- Open-Cell, soft and conformable, high in strength
- Functions well for extended periods at temperature of 104 C/200 F



ATTACHMENT TAPE — CLEAR

Description	Part No.
1/2" x 36' yards (12mm x 33mm)	F41718
3/4" x 36' yards (19mm x 33mm)	F4926

- Double-sided acrylic adhesive on a polyester film for permanent mounting of trim and emblems
- Adheres to plastics, metals and woods
- Thickness: .008'



GAFFERS TAPE

Size	Thickness	Part No.
2" x 60' yards	11.0 Mil.	F4206
11 11 11		

- Used to attach paper barrier between door panel and structure of door
- 11 0 mil thick
- Matte black finish to match OEM tapes



ACRYLIC TRANSFER TAPE

Description	Part No.
3/4" x 60' yards	F41423
1" x 60' yards	F41173

- 2 mil reinforced acrylic transfer tape
- Ideal for permanent bonding of papers, plastics and films Can also be used as a core start up tape
- Conforms to FDA 21 CFR 175.105 "Adhesives"



TAPE — SEALING

3M™ ALUMINUM FOIL TAPE

Size




KEn.	
POLYI TI	
M. P.	

- 2" x 60 yards F4959 Dead soft aluminum foil backing with an acrylic adhesive
- Aluminum backing acts as a heat shield, minimizing heat transfer
- Superior conformability to adhere to irregular surfaces Acrylic adhesive system developed for solvent resistance and clean removal

Part No.

- High adhesion and excellent aging resistance
- Can be used for numerous masking and sealing applications

DUCT TAPE







- Polyethylene coated cloth Strong, moisture proof barrier for packaging
- Uses: general purpose applications including binding, holding, sealing and construction.
 Use 11Mil for more demanding applications.




ALUMINUM FOIL TAPE

Size	Part No.
2" x 50 yards	F4686
Dead soft aluminum foil backing is extre	mely conformable to

- irregular surfaces
- Excellent adhesion and quick stick
- Appropriate for a variety of insulation uses
- Total Thickness: 5 mil
- Foil Thickness: 2 mil

THREAD SEALANT TAPE

Size	Import Part No.	USA Part No.
1/2" x 260"	F484	F43627
1/2" x 520"	F41748	F43628
3/4" x 520"	F4643	F43629
1"x260"	F4253	F43630



- $Lubricates, protects \, and \, seals \, threads$
- Thread sealant tape makes it easier to assemble or disassemble threaded fittings, without the risk of system contamination
- Tape Thickness: 4mil Standard Density: 0.28 gm/cm3 -100% virgin PTFE
- Temperature range: 375°F to 500°F





AIR CONDITIONING SEALANT TAPE

Size	Part No.
2"x30"	F41281

- Dum Dum tape 1/8" thick
- Black foam rubber
- Insulates, prevents condensation, deadens sound



FLEECE HARNESS & SQUEAK TAPE		
Size	Part No.	
3/4" x 25yd.	F4609	
Squeak and rattle and dash comport	reduction for interior panels	

- Cable harness securing wrap for the passenger compartment of vehicles.
- Rubber adhesive
- PET fleece textile
- Black



ANTI-SEIZE TAPE POLY-TEMP TAPE

Size	Description	Part No.
1/2" x 600"	Copper	F4628
1/2" x 600"	Nickel	F41190

- Unique lubricating products that assist in assembly and disassembly of threaded fasteners and connections
- $Provide the \, means \, to \, apply \, and \, control \, precise \, amount \, of \, lubrication \, while \,$
- maintaining a clean, non-greasy assembly Blended PTFE resin with Metal flake prevent the seizing and galling
- Provides protection from corrosion and dirt

 Poly-Temp Copper: Reduces required torque, applies easily, seals tightly, overcomes high temperature seizing. Protects against galvanic pitting; Temperature Range: -450° to 1800°F Poly-Temp Nickel: Increased chemical resistance, extremely high
- temperature, and harsh environments. Made especially for stainless steel threads; Temperature Range: -450° to 2600° F

CAP TAPE

Size	Part No.
3/16" thick x 1-1/2" wide 30 foot roll	F4836
3/16" thick x 2" wide 50 foot roll	F4470

- Single faced closed cell neoprene sponge material Designed to seal pickup truck camper caps
- Dampens vibration, helps prevent creaks & squeaks



YELLOW GAS LINE PTFE TAPE

Size	Part No.
1/2" x 260"	F3735
3/4" x 260"	F34297

- Meets USDA and FDA requirements
- Meets MIL-T-27730A Temperatures from -450° to +550°F (-240° to 287°C)
- Pressures rated up to 2000 psi



4

TAPE — PACKAGING

$3M^{\mathsf{TM}}\mathsf{TARTAN^{\mathsf{TM}}}$ **PACKAGING TAPE 3710**



Qty per Case Qty

		Part No.	Case	Partino.
F482	2" x 110 yards - Clear	18813	36	F42220

3M



- Commercial grade film tape
- Conforms to box surfaces

Part No. Description

Ideal for most packaging applications

3M™ SCOTCH° PACKAGING TAPE 3750

Part No.	Description	3M Part No.
F41212	2"x60 yards-Clear	06640
F4544	Promo Pack -12 rolls of #3750 (2" x 60 yards) Clear tape plus a free H-122 dispenser	06635
F4406	2"x60 yards-Tan	06642
- 11		

- Heavy-duty construction grade film
- Provides a consistent uniform seal Aggressive adhesive sticks instantly and holds tight



FILAMENT PACKAGING TAPE F4418

- 3/4" x 60 yard roll
- Fiberglass reinforced strapping tape



PACKAGING TAPE DISPENSERS

Description	Part No.
Pistol Grip Dispenser for 2" Packaging Tape	F41770
3MH-122 Dispenser for 2" Packaging Tape	F41706
3MH-180 Pistol Grip Dispenser for 2" Packaging Tape	F41519







SHIPPING SUPPLIES


TAGS

Size#	Size-inches	Manila Tag Stock Part No.	TyvekTag Stock Part No.
#5	2-3/8 x 4-3/4	F41001	F4487

- Write, stamp or print your own information on these blank tags. Use to identify and control parts.
- Available in:

13pt. Manila card stock and 10pt. Tyvek w/ metal eyelets for heavy and/or outdoor use

All tags come with 26 ga. 12" wire twisted onto eyelet



SHRINK/STRETCH WRAP F41151

- 18" x 1500' Roll
- Clear film used for bundling and palletizing
- Sold by the roll

PACKING LIST ENCLOSED ENVELOPE

TACKING LIST LINELOSED LINVELOT L		
Size	Part No.	
5-1/2" x 4-1/2"	F41410	
5-1/2" x 7"	F41637	
5-1/2" x 10"	F4564	




- Attach & protect packing lists Peel & stick backing

TAPE — VELCRO


3M™ DUAL LOCK™ RECLOSABLE **FASTENERS**





- $When \ pressed \ together \ hundreds \ of \ mush room-shaped \ stems$ interlock with one another
- An audible snap indicates the fastener is locked
- Compared to hook and loop fasteners, you get improved tensile strength with five times more holding power

3M™ HOOK AND LOOP RECLOSEABLE **FASTENERS**





- Mini-pak dispenser includes 1 roll of hook, and one roll of loop material
- When hook and loop fasteners are pressed together, hundreds of tiny, stiff hooks mesh with a surface of pliable loops
- Simply press together to fasten and pull apart to open
- Prolonged exposure to water does reduce hook and loop closure strength, but full strength returns after drying

TOOLS — SOCKET SETS

- Manufactured to ANSI & DIN industrial standards
- Quality chrome vanadium alloy steel.
- Precision heat treating for maximum strength

3/8" DRIVE SAE 12PT SOCKET SET - 15 PIECE F43006

Set contains: Standard Sockets - 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 1"

Adapter 3/8" Female x 1/2" Male; Universal Joint 2" Reversible Ratchet 8": Extension Bars 3" & 6"



Larger marking for easy size identification GRIPSTRIP™ ergonomic design. Identifying color for SAE and Metric.

3/8" DRIVE METRIC 12PT SOCKET SET - 15 PIECE F43005

Set contains: Standard Sockets - 9, 10, 11, 12, 13, 14, 15, 16, 17.19mm

Adapter 3/8" Female x 1/2" Male; Universal Joint 2" Reversible Ratchet 8", Extension Bars 3" & 6"



1/2" DRIVE SAE 6PT SOCKET SET - 19 PIECE F43003

Set contains: Standard Sockets - 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8",

15/16", 1", 1-1/16". 1-1/8"

Size

6mm

8mm

9mm

10mm

11mm

12mm

13mm

14mm

15mm

16mm

17mm

18mm 19mm

20mm

21mm

22mm

24mm

Adapter 1/2" Female x 3/8" Male; Universal Joint 3" Reversible Ratchet 10"; Flexible Head 15"; Extension Bars 5" & 10"



21,22, 24, 27mm Adapter 1/2" Female x 3/8" Male; Universal Joint 3" Reversible Ratchet 10"; Flexible Head 15"; Extension Bars 5" & 10"



1/2" DRIVE BUST-A-BOLT KIT F41942


Set contains: 1/2" Drive Ratchet w/ 10" Quick Release Knurled Handle; 11-1/2" Ratchet Extension Adjustable Handle; 105° L-Handle 12-1/2";



F01183

F01431

TOOLS — SOCKETS 3/8"



12PT	3/8" SAE DEEP SOCKETS 12PT		
Part No.	Size Part No.		
F01436	1/4"	F01205	
F01185	5/16"	F01206	
F01437	3/8"	F01336	
F01197	7/16"	F01175	
F01198	1/2"	F01337	
F01199	9/16"	F01412	
F01200	5/8"	F01210	
F01168	11/16"	F01213	
F01201	3/4"	F01169	
F01202	13/16"	F01396	
F01333	7/8"	F01221	
F01334	15/16"	F01170	
F01204	1"	F01233	
F01413			
F01335			



3/8" SPARK PLUG SOCKETS 6PT

Size	Part No.
5/8"	F01415
13/16"	F01338

TOOLS — SOCKETS 1/2"

1/2" METRIC SOCKETS 6PT		
Size	Part No.	
8MM	F01417	
9MM	F01418	
10MM	F01419	
11MM	F01420	
12MM	F01421	
13MM	F01179	
14MM	F01422	
15MM	F01315	
16MM	F01316	
17MM	F01285	
18MM	F01286	
19MM	F01287	
20MM	F01270	
21MM	F01271	
22MM	F01317	
23MM	F01288	
24MM	F01216	
25MM	F01397	
26MM	F01392	
27MM	F01393	
28MM	F01224	
29MM	F01231	
30MM	F01318	
32MM	F01377	
33MM	F01319	
34MM	F01245	
36MM	F01320	
38MM	F01247	
39MM	F01361	
41MM	F01354	
46MM	F01321	

1/2" SAE SOCKETS 6PT		1/2" SAE DE	1/2" SAE DEEP SOCKETS 6PT	
Size	Part No.	Size	Part No.	
5/16"	F01423	3/8"	F01390	
3/8"	F01424	7/16"	F01184	
7/16"	F01425	1/2"	F01225	
15/32"	F01426	9/16"	F01226	
1/2"	F01427	5/8"	F01227	
9/16"	F01180	11/16"	F01182	
19/32"	F01428	3/4"	F01229	
5/8"	F01177	13/16"	F01230	
11/16"	F01289	7/8"	F01323	
3/4"	F01167	15/16"	F01232	
25/32"	F01322	1"	F01324	
13/16"	F01272	1-1/16"	F01239	
7/8"	F01212	1-1/8"	F01340	
15/16"	F01401	1-3/16"	F01325	
1"	F01398	1-1/4"	F01176	
1-1/16"	F01220	1-5/16"	F01367	
1-1/8"	F01228	1-3/8"	F01362	
1-3/16"	F01383	1-7/16"	F01250	
1-1/4"	F01234	1-1/2"	F01290	



1/2" SPARK PLUG SOCKETS 6PT

Size	Part No.
5/8"	F01326
13/16"	F01407

TOOLS — SCREWDRIVERS

- Manufactured to ANSI & DIN industrial standards
- Quality chrome vanadium alloy steel. Precision heat treating for maximum strength

SLOTTED HEAD SCREWDRIVERS

Size	Part No.
3/16x3"	F01207
3/16 x 8"	F01311
1/4 x 1-1/2"	F01312
1/4 x 4"	F01209
1/4 x 6"	F01313
5/16" x 6"	F01314
3/8 x 8	F01386

Molded unitary construction

Oversize handle for maximum comfort & no-slip grip surface

PHILLIPS HEAD SCREWDRIVERS

Size	Part No.
#0 x 2-3/8"	F01203
#1 x 4"	F01414
#2 x 1-1/2"	F01416
#2 x 4"	F01406
#2x6"	F01405
#3 X 6"	F01310
#4 X 8"	F01283



TOOLS — COMBINATION WRENCHES

- $Manufactured \ to \ ANSI \& DIN \ industrial \ standards$
- Quality high polished chrome molybdenum alloy steel.

SAE 12PT COMBINATION WRENCH SET

- 9 PIECE

F43295 **Set contains:** 1/4",5/16",3/8",7/16",1/2", 9/16",5/8",11/16",3/4"



- Precision heat treating for maximum strength
- Larger marking for easy size identification

SAE 12PT COMBINATION WRENCH SET

- 13 PIECE

Set contains: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16" 7/8", 15/16", 1"



METRIC 12PT COMBINATION WRENCH SET

- 9 PIECE F43293

Set contains: 8, 9, 10, 11, 12, 13, 14, 17, 19mm



METRIC 12PT COMBINATION WRENCH SET

- 13 PIECE F43294

Set contains: 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 19, 22, 24mm



COMBINATION WRENCH SAE 12PT

Size	Part No.	Size	Part No.
1/4"	F01410	7/8"	F01304
5/16"	F01404	15/16"	F01249
3/8"	F01400	1"	F01256
7/16"	F01219	1-1/16"	F01305
1/2"	F01389	1-1/8"	F01262
9/16"	F01186	1-1/4"	F01276
5/8"	F01382	1-5/16"	F01267
11/16"	F01189	1-3/8"	F01341
3/4"	F01187	1-7/16"	F01268
13/16"	F42151	1-1/2"	F01188

COMBINATION WRENCH METRIC 12PT

Size	Part No.	Size	Part No.
5.5MM	F01408	19MM	F01373
6MM	F01409	20MM	F01273
7MM	F01211	21MM	F01242
8MM	F01403	22MM	F01302
9MM	F01215	23MM	F01303
10MM	F01217	24MM	F01248
11MM	F01218	25MM	F01254
12MM	F01391	26MM	F01255
13MM	F01388	27MM	F01349
14MM	F01301	28MM	F01261
15MM	F01384	29MM	F01274
16MM	F01381	30MM	F01275
17MM	F01380	32MM	F01265
18MM	F01269		



RATCHETING COMBINATION WRENCH SAE 12PT

Size	Part No.
5/16"	F01278
3/8"	F01279
7/16"	F01280
1/2"	F01281
9/16"	F01253
5/8"	F01358

Size	Part No.
11/16"	F01353
3/4"	F01351
13/16"	F01264
7/8"	F01282
15/16"	F01344

RATCHETING COMBINATION WRENCH METRIC 12PT

Size	Part No.
8MM	F01244
9MM	F01306
10MM	F01368
11MM	F01307
12MM	F01246
13MM	F01252
14MM	F01359
15MM	F01308

Size	Part No.
16MM	F01357
17MM	F01257
18MM	F01352
19MM	F01350
21MM	F01277
22MM	F01343
24MM	F01306

4

TOOLS — ADJUSTABLE WRENCHES

PIPE WRENCHES — HEAVY-DUTY

Description	Capacity	Weight Lbs.	Part No.
10" Pipe Wrench	1-3/16"	1.32	F42740
12" Pipe Wrench	1-9/16"	1.72	F4214
14" Pipe Wrench	2"	2.32	F42741
18" Pipe Wrench	2-3/8"	3.79	F41765

Forged steel jaw provides maximum strength Full floating hook jaw, provides instant grip, easy release Large knurl and power threads provide fast, positive jaw adjustment



ADJUSTABLE WRENCHES

Description	Capacity	Part No.
6" Adjustable Wrench-Chrome	15/16"	F4317
8" Adjustable Wrench-Chrome	1-1/8"	F4447
12" Adjustable Wrench-Chrome	1-1/2"	F41096

- Alloy steel and heat treated
- Tension spring stabilizes jaw and knurl adjusts easily Chrome plated finish resists rust and corrosion



TOOLS — PLIERS

TONGUE AND GROOVE PLIERS

Description	Capacity	Part No.
6-1/2" Tongue and Groove Plier	7/8"	F41278
9-1/2" Tongue and Groove Plier	1-1/2"	F41379
10" Tongue and Groove Plier	2	F41666
12" Tongue and Groove Plier	2-1/4"	F43271
16-1/2" Tongue and Groove Plier	2-1/4"	F43273
9-1/2" V-JAW Tongue and Groove Plier	1-1/2"	F43270
12" V-JAW Tongue and Groove Plier	2-1/4"	F43272

Channellock® brand

- Right angle teeth grip in all directions for maximum bite, and minimum wear Undercut tongue and groove design assures strong, can't
- Permalock fastener is stronger, safer, and smoother working than the old time bolt and nut
- V-JAW gives more points of contact round stock and tubing
- Made in USA



Description	Jaw Adjustment	Part No.
5" Curved Jaw w/wire cutter	0 - 1-1/8"	F42396
7" Curved Jaw w/wire cutter	0 - 1-5/8"	F4786
10" Curved Jaw w/wire cutter	0 - 1-7/8"	F41401

7" Curved Jaw w/wire cutter	0 - 1-5/8"	F4786
10" Curved Jaw w/wire cutter	0 - 1-7/8"	F41401
D. and affect	Jaw	5
Description	Adjustment	Part No.

10 Straight Jaw	0-1-3/8	F413/3
Description	Jaw Adjustment	Part No.
4" Long Nose	0-1-5/8"	F41579
6" Long Nose	0-2-1/4"	F4382

Description	Jaw Capacity	Part No.
8" Sheet Metal Tool	3-1/8"	F42389

Description	Jaw Capacity	Part No.
9" Welding Clamp	2-3/4"	F42390
	le	

Description	Jaw Capacity	Part No.
6" Swivel Pad C-Clamp	2-1/8"	F42397
11" Swivel Pad C-Clamp	4"	F42391
18" Swivel Pad C-Clamp	8"	F42398



- Used for turning, cutting, tightening, clamping, and twisting
- Hardened tooth design grips from any angle Convenient wire cutter cuts up to a 1/4" bolt
- Made from high grade alloy steel heat treated for maximum toughness and durability



- Makes bending, forming and crimping sheet metal easier
- U-shaped jaw provides enhanced visibility and more working space
- Swivel pads hold tapered work, cumbersome fabricating jobs and delicate projects without damaging the work surface



Description	Part No.
6-1/2" Slip Joint Plier w/Wire Cutter	F43274

- Channellock brand
- Polished high carbon drop forged steel
- Wire cutting shear
- Permalock fastener eliminates nut and bolt failure



MULTIPURPOSE WELDER'S PLIER

Description	Part No.
9" Welder's Plier	F43268

- Channellock® Brand
- An original groove-nose design for quick and clean spatter removal
- A unique diamond-shape welder tip installation and removal tool that prevents stripping by gripping four sides of the welder tip An elongated nose with cross-hatch grips for secure drawing of wire
- or gripping of hot metal
- A welder bushings and nozzle installation and removal tool Two hammering surfaces.
- $\mathsf{Made}\,\mathsf{in}\,\mathsf{USA}$

CUTTING PLIERS

Description	Part No.
6" Long Nose Plier w/Side Cutter	F41260
8" Long Nose Plier w/Side Cutter	F41785



Description	Part No.
8-1/2" Linemens Plier	F43269
9-1/2" Linemens Plier	F41539

Description	Part No.
7-1/2" End Cutting Plier	F43267
8" End Cutting Plier	F41425
Chammalla ale brand	

- Channellock brand
 Polished high carbon drop forged steel
- Perfectly mated cutter is heat treated to hold its edge
- Made in USA



TOOLS — PLIERS (continued)



- 8" Alloy Steel Long Nose Pliers F42379 Reaming Head Design - Smooth edges of metal pipe from 1/2" to 1" $\,$
- Loop Maker Built in loop maker for up to 10 ga, wire
- Wire Stripper Strip 10-14 AWG (Solid Wire); 12-16 AWG (Stranded)
- Laser Hardened Cutting Edges Cuts wires, bolts, screw and nails
- Forged Alloy Steel For Maximum tool strength
- Length: 8'



MILWAUKEE® QUICK ADUST REAMING PLIERS

Description	Part No.
10" Alloy Steel Quick Adust Reaming Pliers	F42380

- Exposed Reaming Handles Up to 1" Conduit Reaming Head Design – Smooths out rough edges of up to 2" pipe
- Quick Adjust Jaws V-groove jaws create a more precise fit with up to 2'
- Forged Alloy Steel For Maximum tool strength
- Lenath: 10'






- Cushion grip handles for comfort
- Made in USA

CAM-LOCK CONVERTIBLE RETAINING RING PLIERS

- Description Part No. 6-Piece Set (Includes one each of the F4683 following sizes in a storage case) Cam-Lock Convertible Retaining Ring Pliers .038 18° F41293 Cam-Lock Convertible Retaining Ring Pliers .047 F41189
 - Patented design allows for quick change over from internal to external use
 - No screw to tighten or come loose
- For 1/2" to 2" internal and external rings

RETAINING RING PLIERS WITH REPLACEABLE TIPS

Description	Retaining Ring Range Internal	Retaining Ring Range External	Part No.	Replacement Tip Kit Part No.
Small Retaining Ring Pliers w/Tip Kit	1/4" to 1"	1/8" to 1"	F464	F41477
Medium Retaining Ring Pliers w/Tip Kit	3/8" to 2"	1/4" to 2"	F41731	F41104
Large Retaining Ring Pliers w/Tip Kit	1-3/16" to 4"	1-1/2 " to 4"	F41122	



- Pliers come with one set of tips Replacement tip kits available
- Made in USA





COTTER PIN PULLER

- A safe and easy way to remove cotter pins
- Ideal for use in confined work areas
- Heavy-duty plastic handle

- Blade length: 4-1/2" Overall length: 7-1/2"

TOOLS — HAND TOOL WARRANTY INFORMATION

CHROME HAND SOCKETS:

- Do not use hand sockets with impact or power driven tools. Serious injury is possible.
- Use safety goggles. Eye injury is possible
- Do not hammer on sockets or drive tools
- Do not use extenders or cheater bars on drive tools.

BLACK IMPACT SOCKETS:

- Do not hold sockets, universal joint or other attachment when power tool is running.
- Do not use damaged sockets. Replace them before using. Do not continue to hammer with an impact tool once the fastener is tight.
- Use safety goggles. Eye injury is possible

WRENCHES:

- Do not use extenders or cheater bars. Injury is possible.
- Use safety goggles. Eye injury is possible. Instructions in using wrenches:
- - 1. Use correct size wrench
 - 2. Do not use fractional wrenches on metric fasteners or vice versa. 3. Use the type of wrench that is best fit for the job.
 - 4. Use the box end of the wrench if possible
 - 5. Pull the wrench towards you. Do not push. 6. Use a lubricant on a corroded fastener.
- **SCREWDRIVERS:**
- Use safety goggles. Eye injury is possible.
- Do not pry, punch, chisel, scrape, hammer or otherwise misuse
- Do not use screwdrivers on electrical circuits. There is no insulation.

- Prevent slipping. Keep tools clean.
- Fit screwdriver tip width and thickness to fastener slot size.

- Use safety goggles. Eye injury is possible. Do not use pliers with cushion grips on electrical circuits. There is no insulation.
- Do not use extenders or cheater bars on pliers handles

ADJUSTABLE WRENCHES:

- Use safety goggles. Eye injury is possible.
- Adjust wrench tightly on fastener.
- Use correct size wrench.
- Pull the wrench. Do not push.

TORQUE WRENCHES:

- Use safety goggles. Eye injury is possible.
- Do not use cheater bars, hammers or other damaging objects on torque wrenches.
- Do not exceed rated torque capacity of wrench.
- Do not exceed capacity of fastener.
- Do not use torque wrenches to break fasteners loose.
- Pull the wrench towards you. Do not push.
- Do not drop torque wrenches. May loose calibration. Torque wrenches should be re-calibrated every year.

Hand tools that are in our product line carry the manufacturer's warranty and fall under that manufacturers quidelines and procedures. We reserve the right to deny any warranty claim until evaluated by the manufacturer(s). We may choose to replace the item or issue credit for the warranty item up front before manufacturer evaluation. In those cases, Winzer will charge the salesperson for the replacement, if the item is determined by the manufacturer to not be considered as warranty. Such cases could be abused or misused tools. We do not condone or support the abuse and misuse of hand tools and accept no responsibility on the abuse or misuse of these tools. For this reason, tools that have been abused or misused, will not be accepted under warranty. Abuse and misuse of tools causes accidents and bodily injury. Tools are designed to perform specific functions. Misuse and abuse may put stress and fatigue on a tool, which are beyond the design of the tool and when this happens the tool will break. Examples of misuse and abuse are:

Broken screwdriver tips and bent shanks are the result of using the screwdriver as a pry bar, punch or chisel.

- A chrome socket with square drives that have rounded out corners and/or peened metal around the drive end show the normal signs of use on an impact or power wrench. Continued use on an impact wrench will cause the socket wall to crack or shatter.
- Ratchet handles and wrenches that have been dented, grooved and broken indicate abuse with "cheater bars" or a hammer.
- Plier handles that are bent or broken are the signs of prying or over torqueing.

TOOLS — HEX BIT KITS, INSERTS & ACCESSORIES

HEX BITS & KITS

Sizes	Description	Part No.
	Mag. bit holder	F4134
	Socket adapter	F4676
#0	Phillips insert	F41251
#1	Phillips insert	F4181
#2	Phillips insert	F41561
#3	Phillips insert	F4193
#1	Pozidrive insert	F4810
#2	Pozidrive insert	F4952
1-2	Slotted insert	F41045
4-5	Slotted insert	F4504
6-8	Slotted insert	F41522
8-10	Slotted insert	F4426
10-12	Slotted insert	F4938
#0*	Square insert (Robertson)	F4211
#1	Square insert (Robertson)	F4414
#2	Square insert (Robertson)	F4377
#3	Square insert (Robertson)	F4857

- Screwdriver Insert Bit Kit includes all the inserts listed above, packaged in a handy plastic case Choice of storage handle or cushion handle, both with
- magnetic insert holder Comes with 1/4" hex shank holder for electric screwdrivers
- Kit with storage handle driver # F41055
- Kit with cushion handle driver #F41125
- 1/4" shank insert bits *Not included in kit



WIHA® BIT SELECTOR SET

Set Contents (1 of each)	Part No.
Phillips Sizes: 0, 1, 2, 3 Slotted Sizes: 177, 216, .315 Torx Sizes: #10, #15, #20 1/4" Magnetic bit holder	F41046

- Compact, plastic storage box
- Slide out drawer allows quick bit access and secure storage
- 1/4" bits are made of hardened chromevanadium-mobdenum tool steel



32 PC DRIVER BIT SETS

- Made from S2 modified shock resistant steel for professional performance and durability.
- Proprietary precision CNC machined tips for excellent fit in fastener recess.
- Case includes convenient belt clip design.
- 1/4" shank

STANDARD BITS F44183

Phillips: 0, 1, 2, 2R, 3 Torx: 10, 15, 20, 25, 27, 30, 40 Slotted: 3-4, 4-5, 6-8, 8-10, 10-12 Hex: 5/64, 3/32, 7/64, 1/8, 9/64, 5/32 3/16, 7/32, 1/4, 5/16

Square: 1,2,3 1/4" x 1/4" Socket Quick Release Bit Holder



TAMPER BITS F44184

Contents:

Phillips Tamper: 2, 3 Torx Tamper: 5, 6, 7, 8, 9, 10, 15, 20, 25, 27, 30, 40 Hex Tamper: 5, 64, 3/32, 7, 64, 1/8, 9/64, 5/32 3/16, 7/32, 1/4, 5/16 Spanner: 4, 6, 8, 10, 12, 14

1/4" x 1/4" Socket Ouick Release Bit Holder



F42381

- 18 Piece Shockwave™
- Driver Bit Set



- **SET CONTAINS:** (1) SHOCKWAVE™ Magnetic Bit Holder
- (1) 1/4" Magnetic Nut Driver, (1) 5/16" Magnetic Nut Driver (1) Hex Bit 1" 1/4", (1) Hex Bit 1" 3/16" (1) Phillips Bit 1" P1, (4) Phillips Bit 1" P2, (1) Phillips Bit 1" P3
- (2) Phillips Bit 2" P2
- (1) Phillips Reduced 1" PR2 Bit (1) Slotted 1" #10 Bit, (1) Slotted 1" #8 Bit, (1) Slotted 2" #10 Bit
- (1) Square Bit 1" SQ1, (3) Square Bit 1" SQ2, (1) Square Bit 1" SQ3
- (1) Square Bit 2" SQ2 (1) TORX® Bit 1"T15, (2) TORX® Bit 1"T20, (2) TORX® Bit 1"T25, (1) TORX® Bit 1"T30
- (1) TORX® Bit 2" T20, (1) TORX® Bit 2" T25







Copyright © 2023

TOOLS — HEX BIT KITS, INSERTS & ACCESSORIES (continued)

TORX BIT SET WITH HOLDER SET INCLUDES ONE EACH OF THE FOLLOWING: F4100

- Magnetic hex bit holder
- Torx bits T10, T15, T20, T25, T30, T40 1/4" shank





- Nickel plated
- Impact resistant, plastic T-handle
- Magnetic Holds 1/4" Hex insert bits





Magnetic Screwdrivers, For use with 1/4" Bit size



16-IN-1 SECURITY SCREWDRIVER

Bits store securely and conveniently in the handle **Includes these security bits:** Spanner 4, 6, 8 and 10 Hex Security 1/8", 9/64", 5/32" and 3/16" Square Security 1 and 2 Phillips #2 and Slotted #8 Torx Security T10, T15, T20 and T25





DIAL-N-LOAD AUTO SCREWDRIVER

- All high grade metal component construction Chemical and shock resistant plastics
- Comfortable, attractive, anti-roll handle
- Rotating front collar for fine adjustment Comes loaded with 6 commonly used industrial grade bits Phillips: PH1, PH2, PH3; Slotted: 1/8", 3/16", 1/4"
- No contact bit changes
 Bit loads can be fully customized (1" length bits only)
- Bit tips are magnetic



OUICK CHANGE EXTENSION

201011 0111 1110 1111 1111			
Sizes	Part No.		
6"	F43860		
12"	F44087		

• For 1/4" Hex insert bits



POWER HEX BIT DRILL ADAPTER F41163

- Converts any 3/8" or larger drill motor into a quick change drill For use with 1/4" Hex shank power bits and
- 1/4" Hex shank drill bits
- For Hex Shank Drills please refer to the drill/tap section in the cutting tool chapter



QUICK CHANGE BIT HOLDER F41167

For 1/4" Hex insert bits



MINGHETIC HEX DIT HOLDER			
Sizes	Part No.		
2-1/8"	F43895		
3"	F4855		
6"	F4589		

For 1/4" Hex insert bits



FLEXIBLE BIT HOLDER EXTENSION

Sizes	Part No.	
7-1/2"	F41512	
 For 1/4" Hex 	insert bits	



DOUBLE END	BITS					
Туре	Hex Drive	OAL	Screw Size Phillips	Screw Size Slotted	Part No.	
Phillips/Phillips	1/4	2″	#2	N/A	F41140	Ī
Phillips/Slotted	1//	2"	#2	#0	E4141	

TOOLS — HEX BIT KITS, INSERTS & ACCESSORIES (continued)

TORX INSERT BITS, 1/4" SHANK



OAL	Part No.
1"	F4600
1"	F4566
1"	F41359
1"	F41064
1"	F41536
1"	F41374
1"	F474
	1" 1" 1" 1" 1" 1" 1"

HEX SOCKET INSERT BITS, 1/4" SHANK




Sizes	OAL	Part No.	
5/64	1"	F41500	
3/32	1"	F4465	_
7/64	1″	F41753	
1/8	1"	F4427	_
9/64	1″	F4384	

HEX SOCKET METRIC INSERT BITS, 1/4" SHANK



Sizes	OAL	Part No.	
2mm	1″	F4508	
2.5mm	1"	F493	
3mm	1″	F4763	
4mm	1"	F4340	
5mm	1″	F4479	
6mm	1"	F41093	

WIHA* INSERT BITS





- "Slotted"
- Made from impact resistant, modified chrome-vanadium-mobdenum hardened tool steel
- Hardness: RC 59-61
- The ideal multi-purpose bit for all around quality and performance

1/4" SHANK TORX PLUS INSERTS BITS

Sizes	Description	Part No.
#15	Torx plus insert	F4615
#20	Torx plus insert	F4854
#25	Torx plus insert	F41747
#27	Torx plus insert	F41607
#30	Torx plus insert	F41491
#40	Torx plus insert	F41139



PHILIPS INSERT BIT WITH SERRATED TIP





TAMPER RESISTANT SPANNER **INSERT BITS**


	1 0110	
Sizes	Description	Part No.
#4	Spanner Insert	F4173
#6	Spanner Insert	F4329
#8	Spanner Insert	F490
#10	Spanner Insert	F4834
#14	Spanner Insert	F42374





- 1/4" hex shank insert bits
- Made from hardened tool steel (RC 59-61) for durability and long life

5/16" SHANK PHILLIPS INSERT BITS





TAMPER RESISTANT TORX PIN-IN INSERT BITS

Sizes	Description	Part No.	_
TR-10	Torx Pin-in	F43634	Ī
TR-15	Torx Pin-in	F4318	
TR-20	Torx Pin-in	F41216	I
TR-25	Torx Pin-in	F41007	
TR-27	Torx Pin-in	F4577	
TR-30	Torx Pin-in	F41440	
TR-45	Torx Pin-in	F4767	
4 (4// C)	1.1 1.00		





- 1/4" Shank Insert Bits
- Drilled to fit tamper resistant screws

5/16" SHANK TORX INSERT BITS

Sizes	Description	Part No.	
#30	Torx insert	F4985	
#40	Torx insert	F4430	
#45	Torx insert	F41630	
#50	Torx insert	F4576	



TAMPER RESISTANT HEV DINI-IN INCEDT DITC

HEY LIM-IM IMPERT DITO		
Sizes	Description	Part No.
1/8	Hex Pin-in	F42373
5/32	Hex Pin-in	F4188
3/16	Hex Pin-in	F42399







- 1/4" Shank Insert Bits
- Drilled to fit tamper resistant screws

TOOLS — HEX BIT KITS, INSERTS & ACCESSORIES (continued)

IMPACTECH™ IMPACT DRIVER BITS AND ACCESSORIES

- Tested to outperform all leading brands in life cycle and tip failure testing
- Patented spiral torsion zone absorbs impact resulting in longer bit life

PHILLIPS INSERT BITS

Size	OAL	Part No.
#1	1"	F43218
#2	1"	F43219
#3	1"	F43220
#2	2"	F43221



TORX INSERT BITS


Size	OAL	Part No.
T15	1"	F43226
T20	1"	F43227
T25	1"	F43228
T30	1"	F43229
T40	1"	F43230



- Precision engineered tips are manufactured with proprietary CNC maching process Made from S2 Modified impact resistant steel

SQUARE RECESS BITS

Size	OAL	Part No.
#1	1"	F43222
#2	1"	F43223
#3	1"	F43224
#2	2"	F43225



MAGNETIC NUT DRIVERS

Size	OAL	Part No.
1/4"	2-9/16"	F43231
5/16"	2-9/16"	F43232
3/8"	2-9/16"	F43233



- Designed to Last 10-Times Longer then standard bits in high torque applications Compression Forged Tip Ideal Fit and reduces breakage

- $Shock Zone Geometry^{\text{\tiny M-}} Designed \ to \ flex \ with \ spring-like \ action. \ Reduces \ stress \ at \ the \ tip \ Custom \ Engineered \ Steel \& \ Heat \ Treatment High \ shock \ resistance$





Size	OAL	Part No.	
#1*	1"	F41949	
#2	1"	F41470	
#2**	1"	F4890	
#3	1"	F41950	
#1	2"	F41946	
#2	2"	F41300	
#3	2"	F41954	
#2	3.5"	F41348	
#3	3.5"	F41960	
#2	6"	F41961	
#3	6"	F41962	
*5 Pack			

**25 Pack



TORX INSERT BITS, 1/4" SHANK

Size	OAL	Part No.	
T15	1"	F41951	
T20	1"	F41952	
T25	1"	F41953	
T10	2"	F41957	
T15	2"	F41947	
T20	2"	F41767	
T25	2"	F41245	
T27	2"	F41948	
T30	2"	F41958	
T40	2"	F41959	



SQUARE RECESS BITS, 1/4 STIMIN			
Size	OAL	Part No.	
#1	1"	F41127	
#2	1"	F41782	
#2*	1"	F4586	
#1	2"	F41955	
#2	2"	F41586	
#3	2"	F41956	
#2	3.5"	F4904	

*10 Pack

F43235

3" Quick Release Magnetic Bit Holder





ONE WAY SCREW **REMOVAL TOOLS**

Size	Part No.	
#6-8	F130446	
#10-12	F130447	
1/4 (#14)	F130448	







ULTRA ONE WAY SCREW REMOVAL TOOLS

Size	Part No.	
#6	F130610	
#8	F130611	
#10	F130612	
#12	F130613	
#14	F130614	







MILWAUKEE® 11 IN 1 MULTI-TIP SCREWDRIVER

- All metal high torque ratchet delivers more durability and 2x driving speed 3-1/2" Power Groove Bits for power tool compatibility
- Chrome plated bits Marine grade rust protection Magnetic bit retention delivers consistent driving performance
- Up to 10ga wire stripper and loop maker



MILWAUKEE® 10 IN 1 ECX™ RATCHETING MULTI-BIT DRIVER F42517 Includes 6 bits and 3 nut drivers

- ECX Bit fits most specialty screws, including screws found in electrical boxes, conduit couplers and outlets Wire stripper strips up to 12-gauge wire for convenience
- Wire bending hole bends wire up to 12-gauge in size
- Length: 7-1/2"

TOOLS — POWER BITS & NUT SETTERS

POWER BITS

Overall Length	Description	Part No.
1-3/4**	1/4 Magnetic Nut Setter	F4884
1-3/4**	5/16 Magnetic Nut Setter	F41486
1-3/4**	3/8 Magnetic Nut Setter	F4879
1-3/4	7/16 Magnetic Nut Setter	F4118
2-9/16	1/4 Magnetic Nut Setter	F41335
2-9/16	5/16 Magnetic Nut Setter	F41254
2-9/16	3/8 Magnetic Nut Setter	F4843
2-9/16	7/16 Magnetic Nut Setter	F4524
6	1/4 Magnetic Nut Setter	F41054
6	5/16 Magnetic Nut Setter	F4958
6	3/8 Magnetic Nut Setter	F4751
1*	#1 Phillips Power Bit	F4724
1*	#2 Phillips Power Bit	F4581
1-15/16	#1 Phillips Power Bit	F4271
1-15/16	#2 Phillips Power Bit	F41147
1-15/16	#3 Phillips Power Bit	F4456

Overall Length	Description	Part No.
2-3/4**	#1 Phillips Power Bit	F4303
2-3/4**	#2 Phillips Power Bit	F4443
2-3/4	#3 Phillips Power Bit	F41043
2-3/4**	.250 Slotted Power Bit	F4667
2-3/4	5/16 Slotted Power Bit	F43889
3-1/2	#1 Phillips Power Bit	F41057
3-1/2	#2 Phillips Power Bit	F41563
3-1/2	#3 Phillips Power Bit	F41018
6	#1 Phillips Power Bit	F4128
6	#2 Phillips Power Bit	F4996
6	#3 Phillips Power Bit	F41069
6	1/4 Slotted Power Bit	F43890
6	5/16 Slotted Power Bit	F43891
2	#1 Square Power Bit	F4503
2	#2 Square Power Bit	F4196
2	#3 Square Power Bit	F41405
*Reduced	diameter	**Included in kit



- Bits attach directly to most electrical screw drivers
- 1/4" Hex shanks
- Set (#**F41590**) comes with metal index

MAGNETIC NUT DRIVERS,1/4" SHANK

Size	OAL	Part No.	
1/4"	1-7/8"	F41160	
5/16"	1-7/8"	F41307	
3/8"	1-7/8"	F4608	
7/16"	1-7/8"	F41146	
1/4"	2-9/16"	F4535	
5/16"	2-9/16"	F4515	
3/8"	2-9/16"	F4175	
7/16"	2-9/16"	F4822	

Size OAL Part No. 2-9/16" 1/2" F42387 7mm 2-9/16" F42382 8mm 2-9/16" F42383 10mm 2-9/16" F42384 12mm 2-9/16" F42385 13mm 2-9/16" F42386



- Proprietary steel & heat treat process for maximum strength and durability
- Strong magnetic tip for secure grip Color-coded band for easy identification
- Chamfered edge for improved clearance

TORX POWER INSERT BITS 1/4" SHANK — 2" LENGTH

Sizes	Description	Part No.
#10	Torx power insert	F4237
#15	Torx power insert	F4315
#20	Torx power insert	F41724
#25	Torx power insert	F4520

Sizes	Description	Part No.
#27	Torx power insert	F4629
#30	Torx power insert	F41217
#40	Torx power insert	F41291



TOOLS — FOLDING HEX KEY SETS

HEX KEY SETS FOLDUP — BONDHUS

Sizes	Description	Part No.
050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16	Inch 050-3/16	F4165
5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4	Inch 5/64 - 1/4	F4909
3/16, 7/32, 1/4, 5/16, 3/8	Inch 3/16-3/8	F4439





High quality metal handles Made in U.S.A.

HEX KEY SETS ERGO-FOLD — EKLIND

Sizes	Description	Part No.
5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4	Inch Ballpoint 9 pc.	F4713
3/16, 7/32, 1/4, 5/16, 3/8	Inch Ballpoint 5 pc.	F4266
050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16	Inch Regular 9 pc.	F41615
5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4	Inch Regular 9 pc.	F41042
5/32, 3/16, 7/32, 1/4, 5/16, 3/8	Inch Regular 6 pc.	F4698

Sizes	Description	Part No.	
2, 2.5, 3, 4, 5, 6	Metric Ballpoint 6 pc.	F4621	
4, 5, 6, 8, 10	Metric Ballpoint 5 pc.	F4734	
1.5, 2, 2.5, 3, 4, 5, 6	Metric Regular 7 pc.	F4294	
3, 4, 5, 6, 8, 10	Metric Regular 6 pc.	F4267	



- superior ergonomics A soft cushion-grip insert provides comfort and slip resistance
- A hard shell provides maximum strength

4

TOOLS — T-HANDLE HEX KEYS

HEX KEY WRENCHES — T-HANDLES — 6"

Size	Part No.	Size	Part No.		
T-Handle 3/32"	F4871	T-Handle 3/8"	F4673		
T-Handle 7/64"	F41343	T-Handle 2mm	F4390		
T-Handle 1/8"	F41442	T-Handle 2.5mm	F41540		
T-Handle 9/64"	F41943	T-Handle 3mm	F4432		
T-Handle 5/32"	F4537	T-Handle 4mm	F489		
T-Handle 3/16"	F41538	T-Handle 5mm	F4986		
T-Handle 7/32"	F4112	T-Handle 6mm	F41130		
T-Handle 1/4"	F4870	T-Handle 8mm	F4911		
T-Handle 5/16"	F4716	T-Handle 10mm	F4656		

HEX KEY WRENCHES — T-H

TIEN INE I WINE	1CIIL3	I III/MIDEES	
Size	Part No.	Size	Pa
T-Handle 3/32"	F41284	T-Handle 3/8"	F4
T-Handle 7/64"	F41556	T-Handle 2mm	F4
T-Handle 1/8"	F4853	T-Handle 2.5mm	F4
T-Handle 9/64"	F41412	T-Handle 3mm	F4
T-Handle 5/32"	F41754	T-Handle 4mm	F4
T-Handle 3/16"	F41162	T-Handle 5mm	F4
T-Handle 7/32"	F4739	T-Handle 6mm	F4
T-Handle 1/4"	F41299		
T-Handle 5/16"	F41154		

Size	Part No.	
T-Handle 3/8"	F4735	
T-Handle 2mm	F4519	
T-Handle 2.5mm	F41742	
T-Handle 3mm	F4841	
T-Handle 4mm	F4736	
T-Handle 5mm	F4754	
T-Handle 6mm	F4603	

SETS

Contents	Part No.
8 pc set in vinyl pouch includes sizes: 3/32",7/64",1/8",9/64",5/32",3/16",7/32",1/4"	F41203

F4943

8 pc set in vinyl pouch includes sizes: 2mm, 2.5mm, 3mm, 4mm, 5mm, 6mm, 8mm, 10mm

- High quality BONDHUS tools Made In U.S.A. Vinyl coated handles - comfortable grip Size is printed on the handle Length: 6 inches



SETS

Contents	Part No.
8 pc set in vinyl pouch includes sizes: 3/32",7/64",1/8",9/64",5/32",3/16",7/32",1/4"	F4125
8 pc set in vinyl pouch includes sizes: 2mm, 2.5mm, 3mm, 4mm, 5mm, 6mm, 8mm, 10mm	F4408

- High quality Eklind brand Made In USA
- One piece construction for extra strength Vinyl coated handles to reduce hand fatigue
- Length: 9 inches



TOOLS — HEX KEYS

HEX KEY WRENCHES — SHORT & LONG ARM

SHORT ARM — INCH		SHORT ARM — METRIC	
Size	Part No.	Size	Part No.
(short) .035	F4583	(short) 1.5mm	F4299
(short) .050	F4467	(short) 2mm	F4132
(short) 1/16"	F41622	(short) 2.5mm	F4405
(short) 5/64"	F4319	(short) 3mm	F41126
(short) 3/32"	F41373	(short) 4mm	F4579
(short) 7/64"	F4217	(short) 5mm	F4802
(short) 1/8"	F41589	(short) 6mm	F4440
(short) 9/64"	F41099	(short) 7mm	F41059
(short) 5/32"	F41301	(short) 8mm	F41213
(short) 3/16"	F41681	(short) 9mm	F4575
(short) 7/32"	F4140	(short) 10mm	F4322
(short) 1/4"	F41073	(short) 12mm	F41316
(short) 5/16"	F4146	(short) 14mm	F4990
(short) 3/8"	F4282		
(short) 1/2"	F4137		
(short) 9/16"	F4902	_	
(short) 5/8"	F41268		
(short) 3/4"	F4399	_	

- High quality tools Made In U.S.A. De-burred ends provide smooth engagement Metric and Standard (Inch) Sizes
- Size is stamped on each hex key

Size	Part No.
(long) .050	F41421
(long) 1/16"	F4446
(long) 5/64"	F4476
(long) 3/32"	F41632
(long) 7/64"	F4243
(long) 1/8"	F41382

LONG ARM — INCH

(long) 7/64"	F4243
(long) 1/8"	F41382
(long) 9/64"	F41662
(long) 5/32"	F4451
(long) 3/16"	F494
(long) 7/32"	F4335
(long) 1/4"	F4816
(long) 5/16"	F41658
(long) 3/8"	F4682
(long) 7/16"	F4296
(long) 1/2"	F4552
(long) 9/16"	F41497
(long) 5/8"	F4466
(long) 3/4"	F41473
(long) 7/8"	F4525
(long) 1"	F41346

LONG ARM — METRIC

Size	Part No.
(long) 1.3mm	F41472
(long) 1.5mm	F4974
(long) 2mm	F480
(long) 2.5mm	F4723
(long) 3mm	F41292
(long) 4mm	F4830
(long) 5mm	F4593
(long) 6mm	F41344
(long) 7mm	F41277
(long) 8mm	F41480
(long) 9mm	F41280
(long) 10mm	F41075
(long) 12mm	F41337
(long) 14mm	F41543
(long) 17mm	F4144
(long) 19mm	F4742

HEX KEY WRENCHES — IMPORT (METRIC)

Size	Part No. Short Arm	Part No. Long Arm	0
1.5mm	F4269		
2.mm	F4240		
2.5mm	F4156	F4539	
3mm	F4729	F41350	
4mm	F4264	F41067	
5mm	F41707	F4895	
6mm	F4874	F4679	
8mm	F4417	F4645	
10mm	F4821	F4192	
12mm	F41544	F41369	
14mm	F41020	F4905	
17mm	F4820		
19mm		F41457	

Alloy Steel Economical

TORX KEY WRENCHES — SHORT ARM

Size	Part No.
T-10	F4434
T-15	F41102
T-20	F41705
	h. 10 1. 1 as 1 as 2

- High quality eklind tools Made In U.S.A.
- Size is stamped on each tool

TOOLS — HEX KEY SETS

Description	Part No.
Hex-Pro Hex Key Sae Set - 5 pc Includes: 3/16, 7/32, 1/4, 5/16, and 3/8 Inch Wrenches	F43864
Hex-Pro Hex Key Metric Set - 5 pc Includes: 3, 4, 5, 6, 8, and 10 MM Wrenches	F43658

- 180 degree swivel head with extra long handle for accessing hard to reach places Pivot design allows for easy rotation around obstructions Pivot design allows you to keep the wrench and fastener engaged when access is limited
- Great time saver Heat treated alloy tool steel
- Chrome plated finish
- Includes heavy duty folding canvas storage pouch
 Takes up less storage space than a typical hex key set
- Lifetime Limited Warranty



BONDHUS® - L-WRENCH SETS

Description	Description	Part No.
13pc Short Arm Fractional	.050, 1/16, 5/64, 3/32, 7/64,1/8, 9/64, 5/32, 3/16, 7/32, 1/4, 5/16, 3/8	F41734
13pc Long Arm Fractional	.050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4, 5/16, 3/8	F4574
9pc Short Arm Metric	1.5mm, 2mm, 2.5mm, 3mm, 4mm, 5mm, 6mm, 8mm, 10mm	F4804
9pc Long Arm Metric	1.5mm, 2mm, 2.5mm, 3mm, 4mm, 5mm, 6mm, 8mm, 10mm	F4123





- Bondhus brand Made in USA
- ProGuard™ corrosion-resistant finish
 Made from Protanium™ steel that is 20% stronger than competitive wrenches
- Bondhex[™] plastic case locks keys securely in place

TOOLS — HEX & TORX KEYS

BALLDRIVER® POWER BITS

Size	Part No.
5/64"	F41289
3/32"	F4179
7/64"	F4471
1/8"	F4309
9/64"	F469
5/32"	F41727
3/16"	F4387
7/32"	F498
1/4"	F4705
5/16"	F4435
3/8"	F4194

Size	Part No.
1/2"	F41603
2.0 mm	F41600
2.5 mm	F4709
3.0 mm	F4571
4mm	F4404
5 mm	F41258
6 mm	F4624
12 mm	F41693



- Designed for power tools having 1/4" hex adapter
- Saves time and increases productivity Overall length 3"



 $Ball driver ^{^{\circ}} L\text{-}wrench sets are ideal where a variety of tool sizes are require. All set are$ packaged in key case. Wrenches slip easily into individually marked slots and twist to lock secure place.

BALLDRIVER® L-WRENCH SETS

Description	Sizes	Part No.
Inch set	.050,1/16,5/64,3/32,7/64,1/8,9/64,5/32,3/16,7/32,1/4,5/16,3/8	F4701
Metric set	1.5, 2, 2.5, 3, 4, 5, 6, 8, 10	F463

BALLDRIVER* - L-WRENCHES (LONG ARM)

INCH	
Size	Part No.
.050"	F4875
1/16"	F4803
5/64"	F472
3/32"	F4587
7/64"	F41678
1/8"	F41098
9/64"	F41762
5/32"	F41478
3/16"	F41435
7/32"	F4265
1/4"	F4869
5/16"	F4920
3/8"	F41366
7/16"	F41287
1/2"	F4644
9/16"	F41036
5/8"	F4963
3/4"	F41101

METRIC

Size	Part No.
1.27 mm	F4788
1.5 mm	F41654
2 mm	F4424
2.5 mm	F4139
3 mm	F456
4 mm	F4792
5 mm	F41318
6 mm	F41481
8 mm	F4964
10 mm	F4218
12 mm	F41030
14 mm	F41761
17 mm	F41243
19 mm	F41642



- Save time with the ballpoint on the long blade to reach remote and blind location The short end allows high torque and features precision chamfering that eliminates
 - $cut\,off\,burrs$

TOOLS — PUNCHES & CHISELS

FLAT CHI	SELS	70 MANES	CIA 1/2
Stock	Blade	Length	Part No.
7/16	1/2	6	F41100
1/2	5/8	6-1/2	F41145
3/4	7/8	7-1/2	F4324
7/8	1	8	F4501

		THE WAYNER OLD PASS		
LONG T	APER DR	IFT PUNCHES		
Stock	Point	Taper Length	O.A.L.	Part No.
3/8	5/32	4-1/4	9	F4235
1/2	3/16	5	10	F41270

PIN PUN	ICHES		VIS MAYDEW D	SA VII
Stock	Point	Pin Length	O.A.L.	Part No.
5/16	1/8	1	4-3/4	F4428
5/16	5/32	1	5	F41269
3/8	3/16	3-1/2	5-1/4	F41684
1/2	1/4	1-1/4	6	F41574

	m 91		
LOT PUNC	HES		
Number	Size	Part No.	
	1/16	F4685	
1	5/64	F41097	
}	3/32	F41758	
1	1/8	F4727	
	5/32	F4295	
j	3/16	F4898	
3	1/4	F473	
)	5/16	F4338	





ANCH PUNCHES		
Size	Part No.	
1/4	F696	
1/4 3/8 1/2 5/8 3/4	F6146	
1/2	F6365	
5/8	F61397	
3/4	F61593	

- For punching holes in leather, rubber, gasket material, and soft metals
- Inside taper for clearance Heat treated Sheffield forged steel

CENTER PU	INCHES —	415-376 MAYHEW USA 3770 PT
Stock	Length	Part No
3/8	5	F41571
5/16	5	F43588

TOOLS — CLAMPTITE™ BINDING

CLAMPTITE™ BINDING TOOL

Clamp anything....any size, any shape, anywhere.

The Clamptite™ tool provides a means for tightening wires wrapped around an object and then locking it in place. It can be used with various wire sizes, which eliminate space and strength issues often encountered with screw operated worm gear type clamps

• Quickly replace ineffective or damaged conventional hose clamps

• Clamps formed using Clamptite™ seal a full 360° with no flat spots & can be used to band any type or size material



F72972

– Small Clamptite™ Tool (use for wire up to .080" Dia.) – Medium Clamptite™ Tool (use for wire up to .125" Dia.) – Large Clamptite™ Tool. (use for wire up to .250" Dia.) F4929 F4184

STAINLESS STEEL WIRE F41077 -.032" Dia., 1 lb dispenser F4747 -.041" Dia., 1 lb dispenser -.041" Dia., 1 lb dispenser -.051" Dia., 1 lb dispenser -.063" Dia., 1 lb spool F4122





TOOLS — CLAMPS AWLS & PICKS

QUICK-GRIP SPRING CLAMP

• • • • • • • • • • • • • • • • • • • •		
Jaw Size	Part No.	
1"	F4599	7
2"	F41056	
3"	F4268	
 Jaw contoured to hold re 	ound and odd-	



- shaped objects Non-slip handles designed for comfortable
- hand span

DEBURRING TOOL

DEDOMINIO TO DE	
Description	Part No.
Deburring Tool with 2 Blades	F4940
Blade for steel, copper, aluminum, and plastic	F41581

- Swivel head for ease of use Comes with two interchangeable blades
- 5" aluminum handle
- Replacement blades are available

SCRATCH AWL



- Alloy steel blade
- Hardwood fluted handle is contoured for a comfortable grip Blade length: 3-1/2"
- Overall length: 6-1/2"

4 PIECE HOOK AND PICK SET

F41121

- Set includes 4 screw in tips plus aluminum handle
- Set includes 4 screw in tips plus au....
 All in a compact zipper pocket pouch



TOOLS — HAMMERS

DEAD BLOW HAMMERS

Description	Part No.
Dead Blow Hammer 21 oz.	F41357
Dead Blow Hammer 42 oz.	F4131

- $\bullet \quad \text{Non-sparking, soft face hammers will not mar surfaces or} \\$ equipment
- Steel reinforced handles
- Steel shot in head absorbs impact and eliminates rebound



TOOLS — TAPE MEASURES

TRU-LOK MEASURING TAPE

Size	Part No.
1"x25'	F41065
1"-8M x 25'	F4928

- Positive locking bladeImpact resistant case



TOOLS — LEVELS

SAVAGE™ MAGNETIC TORPEDO LEVEL F41008

- 9" overall length Professional, heavy-duty cast aluminum construction Three rare earth magnets for hands free use Four leveling vials at 0°, 90°, 45° and 30° (30° vial is perfect for correctly bending pipe)
- $Bright view^{{\scriptscriptstyle\mathsf{TM}}} milled \textit{ vial windows for improved readability}$
- V-grove edge accepts round stock and pipe up to 10" in diameter
- Laser etched SAE/Metric rules and offset scales



TOOLS — TOOL HOLDERS

MECHANICS TIME SAVERS

- Increases productivity by allowing you to keep your tools next to you Eliminates loss of valuable hand tools and sockets


- Magnetically attaches to any metal surface such as a tool cart or vechicle Magnetic material will not magnetize tools or damage on-board computers


MACNA CADDY


Part No.	Description	Color	Picture
F06045	1/4" Drive Hex Bit Organizer	RED	Α
F42152	1/4" Drive Socket Holder Shallow/Deep	BLUE	В
F42153	1/4" Drive Socket Holder Shallow/Deep	RED	В
F42154	3/8" Drive Socket Holder Shallow	BLUE	С
F42155	3/8" Drive Socket Holder Shallow	RED	С
F42156	3/8" Drive Socket Holder Deep	BLUE	D
F42157	3/8" Drive Socket Holder Deep	RED	D



- Non-stick, high-impact plastic
- Powerful magentic rubber base












Low profile, 3/8 thick

Designed to hold a variety of tools: screwdrivers, wrenches, sockets, pliers - not to mention nuts & bolts







Easy, yet strong, twist locking system

Easily expandable to add more posts



DRILL — CHUCKS & CHUCK EYES

IACOR® DRILL CHUCKS

JACOD DIVILL CITOCKS		
Description	Thread Size	Part No.
3/8" Capacity Keyed Drill Chuck*	3/8-24	F41149
1/2" Capacity Keyed Drill Chuck*	3/8-24	F453
1/2" Capacity Keyless Drill Chuck	3/8-24	F4773



- Working parts are hardened and ground Pointed nose for extra clearance
- Keyed chucks come with key*



STAINLESS STEEL UNIVERSAL **DRILL CHUCK KEYS**

Description	Part No.
Large Key – Fits heavy duty 3/8" to 3/4" chucks	F4781
Small Key – Fits 1/4" to 1/2" light duty chucks	F4159
Two sizes open almost any 1/4" to 2/	4" drill churck



- With these two sizes you can open over 200 different chucks
- Save wear on chucks by having the proper key size The squared center of the keys opens acetylene tanks
- Stainless steel construction for long life

1/4" RIGHT ANGLE DIE GRINDER

Lever throttle for feathering control

Compact and lightweight

Free speed: 20,000 rpm

Front exhaust

Specifications:

Collet size: 1/4"

Overall length: 5"

Motor: 1/3 hp

TOOLS — PNEUMATIC

1/4" STRAIGHT DIE GRINDER F4894

- Compact and lightweight
- Lever throttle for feathering control
- Rear exhaust

Specifications:

- Collet Size: 1/4" Free Speed: 22,000 rpm
- Overall length: 5-3/4'
- Net weight: 1-1/4" lbs. Motor: 1/3" hp
- Air inlet thread: 1/4" NPT
- Air hose ID size: 3/8"
- Avg. air consumption: 4 cfm Air pressure: 90-120 psi





1/8" COLLET

Allows use of 1/8" shank tools in die grinder with 1/4" collet

3" CUT-OFF TOOL

F4191

- Self-locking throttle lever
- Chrome plated steel spark guard Build-in speed regulator
- Heavy duty motor for tough cutting jobs Specifications:
- Wheel size: 3" x 3/8" hole
- Free speed: 20,000 rpm Overall length: 7-1/2"
- Net weight: 1-3/4" lbs.



- Air inlet thread: 1/4" NPT
- Air hose ID size: 3/8" Avg. air consumption: 6 cfm Air pressure: 90-120 psi

3/8" REVERSIBLE AIR DRILL F4502

- Compact and lightweight
- Full power in forward or reverse Built-in muffler for noise reduction
- Planetary gear system for long life
- Specifications:
- Chuck capacity: 3/8"
- Free speed: 1,800 rpm Overall length: 7-7/8"
- Net weight: 2-1/2 lbs.
- Motor: 1/2 hp



- Avg. air consumption: 7 cfm Air pressure: 90-120 psi

AIR FILE BELT SANDER F44098

- Great for Spot Weld Removal
- Simple belt tension lever
- Non-slip handle grip Variable speed control
- Specifications
 Belt Size: ½" X 18"
- Power: 0.5HP
- Free Speed: 16,000 rpm
- Air Consumption: 4 cfm Overall Length: 15.15" (385mm)
- Net Weight: 1.98 lbs. (0.9kg) Air Inlet: 1/4"
- Air Pressure: 90 psi





"Abrasive - Portable Belts" section to

select the belt for your application

AIR FILE BELT SANDER

- Belt will rotate 360° and allow sanding in normally inaccessible working areas such as internal surfaces and narrow corners
- Uses 3/8" x 13" abrasive belt

Specifications:

- Pad size: 3/8" x 13" Free speed: 20,000 rpm
- Overall length: 11-1/2'
- Net weight: 1-1/3 lbs. Air inlet thread: 1/4" NPT
- Air hose ID size: 3/8"
- Avg. air consumption: 7 cfm Air pressure: 90-120 psi



1/4" STUBBY RATCHET WRENCH F41741

- Compact and lightweight
- Ideal for confined working areas
- Built-in regulator **Specifications:**
- Square drive: 1/4"
- Free speed: 240 rpm Overall length: 6-1/2"
- Net weight: 1-1/8 lbs. Max. torque: 30 ft/lbs.
- Air hose ID size: 5/16"
- Air pressure: 90-120 psi



- Air inlet thread: 1/4" NPT
- Avg. air consumption: 3 cfm

1/2" SUPER DUTY IMPACT WRENCH F4598

- Durable twin hammer impact mechanism
- Steel hammer case provides maximum protection
- Two piece construction for easy maintenance Pressure feed lubrication system

1/2" REVERSIBLE AIR DRILL

Variable speed throttle

Specifications:

Chuck capacity: 1/2" Free speed: 500 rpm

Overall length: 9-1/4" Net weight: 4-1/3 lbs. Motor: 1/2 hp

Side handle for greater operator control

Built-in muffler for noise reduction

Planetary gear system for long life

- Specifications:
- Square drive: 1/2" Free speed: 7,000 rpm
- Overall length: 6-3/4"
- Net weight: 5-3/4 lbs. Max. torque: 450 ft/lbs.

- Air inlet thread: 1/4" NPT Air hose ID size: 3/8"
- Avg. air consumption: 4.20 cfm Air pressure: 90-120 psi

Air hose ID size: 3/8"









Avg. air consumption: 7 cfm Air pressure: 90-120 psi



See "Abrasive - Portable Belts" section to select the belt for your application

TOOLS — PNEUMATIC (continued)

HEAVY DUTY AIR RECIPROCATING SAW

F41418

- Ideal for body shop repair, muffler, and exhaust work
- Adjustable blade guide increases blade life
- Cuts all types of aluminum, plastic, fiberglass and sheet metal
- Cuts intricate shapes on flat and curved surfaces Specifications:
- Cutting capacity: 1.6mm 2mm steel thickness
- Strokes per minute: 10,000
- Overall length: 8-1/2" Net weight: 2 lbs.
- Piston stroke: 1/4"
- Air inlet thread: 1/4" NPT
 Air hose ID size: 2/0" Air hose ID size: 3/8"
- Avg. air consumption: 5 cfm Air pressure: 90-120 psi

6" DAQ RANDOM ORBITAL SANDER F4632

- DAQ Dual Action, Quiet performance
- Built-in silencer and motor insulation provides quiet performance
- Balanced ball bearing construction for vibration-free performance Built-in regulator for positive speed control
- Includes 6" sanding pad
- Used for feather edging, metal preparation, and finish work on body filler

Specifications:

- Disc size: 6"
- Free speed: 10,000 rpm
- Overall length: 9-1/2'
- Net weight: 4-1/4 lbs.
- Spindle thread size: 5/16-24
- Air inlet thread: 1/4" NPT Air hose ID size: 3/8"

- Avg. air consumption: 5 cfm
- Air pressure: 90-120 psi

TOOLS — BLOW GUNS

TYPHOON° PRO HIGH VOLUME BLOW GUN F41184

- Variable flow control for precise air delivery
- Silicone free so ideal for use in paint applications
 Lightweight aluminum body with a rugged, chrome-plated brass high
- 34 CFM at 125 psi

4

OSHA Compiant — Made in USA



SAFTEY TYPE BLOW GUN F4809

Maximum Working Pressure: 110 psi

COMFORT GRIP BLOW GUNS

Maximum Working Pressure: 142 psi

- Saftey type metal tip
- 1/4" NPT brass air inlet

F4367 - With 4" extension.

F4236 - With 10" extension.

1/4" NPT air inlet Plastic body

Plastic body



TYPHOON BLOW GUN WITH EXTENSIONS

Length	Part No.
12"	F4530
24"	F4782
36"	F41080

NON-RESTRICTED RUBBER TIP

To be used on blow guns with 30 PSI max pressure



COMPACT SAFTEY LEVER BLOW GUN F4549

- Maximum Working Pressure: 150 psi
- Both saftey nozzle and rubber tip nozzle 1/4" NPT air inlet
- Zinc die-cast body



(MAY BE USED WITH PISTOL GRIP AND HEAVY DUTY BLOW GUNS)

Flow (CFM) @ 100 PSI	Description	Part No.
.50	air screen nozzle	F41644
(*)	needle tip nozzle	F4257

*Nozzles 677.54 and 677.55 are not self relieving styles and should only be used on air lines regulated



F4257

IN-LINE BLOW GUNS

- Unique "full flow" straigth-design will not restrict downstream air flow
- Made of zinc and chrome-plated for durability and
- superior corrosion resistance 1/4" supply ports; 1/8" nozzle port
- Presure rating: 150 psi





ADJUSTABLE POCKET BLOW GUNS

Description	Milton Part No.	Part No.
M-style Adjustable Blow Gun. Fits all Milton M-style or any 1/4" basic size Industrial Interchange Coupler body.	S115	F4565
A-style Adjustable Blow Gun. Fits all Milton A-style or any 1/4" ARO (No. 210) style Coupler Body.	S116	F4400
T-style Adjustable Blow Gun. Fits all Milton T-style or any 1/4" Tru-Flate/Parker style coupler body.	S117	F43184

- Two finger air control adjusts from a mere whisper to full volume air flow Specially designed knurled tip allows secure handling, even with oily or greasy hands
- Maximum inlet pressure 150 PSI
- SCFM 15.9 @100 PSI

WATER BIB

F41365

- Zinc alloy body Nitrile rubber spout
- Operating Pressure: standard
- municipal water pressure 30 to 35 psi Female 1/4" NPT thread



LUBRICATION EQUIPMENT — GREASE GUNS

GREASE GUN — GENERAL PURPOSE

- Lincoln No. 1142
- Provides pressure up to 10,000 PSI
- Rugged cast iron head

 Three way loading: cartridge, suction or bulk
- Delivery: 1 oz. per 21 strokes



GREASE GUN — GENERAL PURPOSE F41133

- Lincoln No. 1147 Comes with 18" whip hose and coupler
- Rugged cast iron head
- Three way loading: cartridge, suction or bulk
- Delivery: 1 oz. per 33 strokes



GREASE GUN — PISTOL GRIP

- Lincoln No. 1134
- Includes a heavy-duty 18" flexible hose with coupler and a rigid 4" tube
- Rugged single piece cast aluminum head Variable stroke provides both high pressure and high
- **Three way loading:** cartridge, suction or bulk Develops up to 7500 PSI





POWERLUBER GREASE GUN F41643

- Lincoln No. 1162 Automatic Air Operated Grease Gun
- Durable, long lasting motor
- Self-priming, cycles continuously
- when trigger is pulled Low operational noise
- 40:1 ratio
- 6000 PSI capacity



CORDLESS POWERLUBER™ GREASE GUN

- Lincoln No. 1242
- $Rechargeable\ battery\ pack\ for\ unrestricted\ mobility$
- 12 volt motor
- Plated steel barrel with exclusive flip-over follower for convenient three way loading
- Delivers consistent grease flow at up to 6000 PSI

Comes complete with: 110 volt fast charger 12 volt NiCad battery 30" flex hose with spiring guar Custom carrying case

CORDLESS POWERLUBER™ GREASE **GUN KIT**

F4950

- Two-speed 14.4 volt high torque motor 7500 psi working output pressure
- 10oz/min. Grease output at 1000 psi
 Comes complete with: 110 volt fast charger 14.4 volt batteries (2) 30" high pressure

hose with spring guard and coupler Carrying

GREASE GUN — HEAVY DUTY

- Provides pressure up to 10,000 psi
- Automatic variable stroke/pressure
- Delivery: 1 oz. per 21 strokes
- Features air vent fitting, vinyl grip, deluxe pull handle,
- positive lever stop Heavy-duty one-piece head
- 3-way loading
- Loader fitting included
- Rigid extention



GREASE GUN - PISTOL GRIP

- Provides pressure up to 4,500 psi Automatic variable stroke/pressure
- Delivery: 1 oz. per 33 strokes
- Features air vent fitting, vinyl grip, handle, positive lever stop
- Heavy-duty one-piece head
- 3-way loading Loader fitting included



SUCTION GUN


F483

- For draining and refilling brake master cylinders, differentials, oil filters, gear cases, etc. 16 oz. capacity
- Includes flexible plastic extension 323821 **Gun outlet:** 1/4" NPTF (f)



GREASE GUN — ECONOMY

- Provides pressure up to 10,000 psi
- Features cartridge or suction fill
- One-piece metal head construction





ECONOMY SUCTION GUN

F41691

- For filling and draining clutches, differentials and transmissions
- 16 oz. capacity Use with any type of non-corrosive lubricants
- Needs no priming Comes with 12" flexible vinyl hose

LUBRICATION EQUIPMENT — GREASE GUNS (continued)

ULTRAVIEW™ CLEAR GREASE GUNS

- Identify which type of grease is in the gun
- Eliminate cross-contamination
- Shatter-proof, high-tech polycarbonate see-through barrel

LEVER ACTION

F42412

- Develops 8,000 PSI
- Variable stroke feature built in for use in confined areas
- Delivers 1.5 oz grease per 40 strokes
- High tolerance aluminum die cast head
- Heavy-duty follower spring
- Complete with 5.5" curved steel extension & 12" flexible hose and coupler with ball check



- Multiple loading via cartridge, suction, bulk
- For use with 14 oz grease cartridge or 16 oz bulk

PISTOL GRIP

F42413

- Develops 5.000 PSI
- Delivers 1 oz grease per 40 strokes
- Comfortable one-hand operation
 Unique bulk loader fitting doubles as air bleede
- Pistol handle designed to prevent fingers from "pinching"
 High tolerance aluminum die cast head
- Complete with 5" steel extension & 12" flexible hose and coupler with ball check



ULTRAVIEW™ CLEAR SUCTION GUN SUCTION GUN

F42414

- Visually see exactly what is inside
- Determine amount of dirt or impurities in system
- Shatter-proof, high-tech polycarbonate see-through barrel
- Great for draining gear cases, transmissions and differentials
- Use with any type of non-corrosive liquid
- 16 oz (one pint) capacity
- 12" clear hose
- 9-3/4" stroke



PUMP OILERS

Description	Part No.
6 oz. Oiler	F41683
16 oz. Oiler	F41749

- Pistol style pump oilers
- Drawn steel bodies Rugged epoxy finish resists rust
- Flex spout is zinc plated and replaceable





LUBRICATION EQUIPMENT — GREASE GUNS HOSES

GREASE GUN HOSE ASSEMBLY

- For use on hand operated grease guns only Assembly consists of 18" hose and 1/8" hydraulic coupler
- End connections are 1/8" nptf (m)
- Maximum working pressure is 4,800 PSI



GREASE GUN HOSES

12"Length — F4378 18"Length — F41604

For use on hand operated grease guns only Heavy-duty 1/8" NPT male fittings on each end

5,000 PSI recommended working pressure

HEAVY-DUTY GREASE GUN HOSES

12" Length — F41461 18" Length — F4252

For use on hand or air-operated grease guns

- Strategically placed coil spring provides non-slip, push-pull grip and prevents accidental "kinking" which could cause hose ruptures
- 4500 PSI maximum working pressure

LUBRICATION EQUIPMENT — COUPLERS & ADAPTERS

HYDRAULIC COUPLERS





F41716 Narrow 1/8" NPTF

- Provides quick, positive and leakproof connections with hydraulic fittings
- Equipped with built in check valve

HYDRAULIC COUPLERS (LINCOLN)







F41449 Model 5845 7500 PSI maximum operating pressure

HYDRAULIC BALL CHECK COUPLER - 4 JAW



F4965 20,000 PSI maximum working pressure 1/8" NPT female 1-7/16" length

Copyright © 2023

LUBRICATION EQUIPMENT — COUPLERS & ADAPTERS (continued)

F41685

LOCKNLUBE® GREASE COUPLER F79228

- WIII not leak once locked on.
- Hands-free, does not release under pressure
- Rated up to 10,000 PSI.
- Will not leak once locked on.
- 1/8 NPT thread. Compatible with all grease guns.
- Works on all Zerk fittings, SAE and metric.



HEAVY-DUTY HYDRAULIC COUPLER

- F41525 4-element jaws turned out of a single piece of
- highly elastic steel $\bar{\text{Precise}} \, \text{coupling} \, \text{and} \, \text{consistent} \, \text{jaw alignment}$
- with every use
- Case-hardened steel jaws and case Safely handles pressures up to 10,000 psi Maintains a positive seal at all times
- Eliminates leakage at case assembly point
- Durable elastic interior plug with high-performance spring

F41393

F41389

- Lincoln No. 5803
- type fittings



90° ANGLE ADAPTER

HYDRAULIC ADAPTER


extension when required


7000 PSI maximum operating pressure


Locks in any one of eight 45° positions

Built-in swivel allows full 360° circle

Lincoln No. 5848







NEEDLE ADAPTER

- Allows operator to contact flush type or hard-to-reach hydraulic

UNIVERSAL SWIVEL F41459

Lincoln No. 81387

- 7500 PSI maximum operating pressure
- Thread sizes 1/2-27 Male x 1/4

BUTTON HEAD COUPLER

- F4635
- 1/8" NPT Female
- Pull on, push on, hook on



NEEDLE NOSE ADAPTER

- For use in all universal joints and lubrication tight spots
- Consists of contact nozzle and locking sleeve
- Length: 5"



GREASE JOINT REJUVENATOR® PROFESSIONAL MODEL

- Loosens hardened grease in joints Cleans, replenishes & maintains old, dirty greasy fittings
- Cleans bearings on farm, lawn & construction equipment Provides a quicker and better option than fishing wire through, heating or disassembling the joint
- Includes 5" flex hose for hard to reach fittings

EASY-OUT FITTING TOOLS

- All-in-one tool to extract broken fittings, rethread holes and install new straight
- and angle-type fittings For fittings with thread



TOOLS — MAGNETS

10-lb Pick-up swivel head magnet with

MAGNETIC PICK-UP TOOL

- Heavy-duty magnetic pick-up tool with a blue molded grip for comfort Simply wave over ferrous material then retract the pull rod to release
- Perfect for picking up metal chips and shavings around machinery and work areas; can also be used for moving fasteners in and out of bins; hundreds of other uses and applications

MAGNETIZER/DEMAGNETIZER

- Magnetize or demagnetize tools and small parts instantly
- Shatterproof box is made from high quality plastic
- Cadmium free

telescopic shaft

- Size: 2.1" x 2.0" x 1.1"
- To magnetize, lead tool slowly through the (+) opening
- To demagnetize, lead tool slowly through the (-) opening **Note:** parts under 1" length or 1/8" diameter may not demagnetize





Bent magnetic pick-up 19" length with bendable aluminum shank



RAZOR BLADES

STANDARD # 9

F41446

- Regular duty single edge (.009 gauge)
- Aluminum backing
- Individually wrapped for rust prevention
- Ideal for cutting, scraping and trimming Fits standard razor blade tools

- 100 per tray 1000 pc bulk pack F42138

ECONOMY#9

- Single edge razor blade (.09 gauge)
- Steel Backing
- Fits standard razor blade tools
- Sold 100 blades per box

PLASTIC BLADE

- F4670
- Plastic scraper blade
- Safely removes stickers from plastic, coated windshields
- $Ideal\,for\,cutting, scraping\,and\,trimming$ Will not cut or scratch work surfaces
- Fits standard razor blade tools



STANDARD # 12 (HEAVY DUTY) F41672

- Heavy duty single edge (.012 gauge)
- Aluminum backing Similar quality as #9, but heavier gauge
- Ideal for cutting, scraping and trimming
- Fits standard razor blade tools
- 100 per tray

ECONOMY # 12 (HEAVY DUTY) F41218

- Single edge razor blade (.012 gauge)
- Steel Backing
 Fits standard razor blade tools
- Sold 100 blades per box

POLYCARBONATE BLADE

F43170 F43171 – 5 pack with holder

- Dual-sided blade
- Will not scratch underlying surface
- Chemical resistant and durable
- $Edge\ dulls\ at\ a\ slower\ rate\ than\ other\ blades$
- **Applications:** Gasket cleaning, fiberglass, tile, porcelain, ceramic, metal surfaces, and windows
- Sold 100 per box







TOOLS — SCRAPERS

WINDSHIELD SCRAPER

F41191

4

- Folds and locks closed for safe storage and carrying
- 1-1/2" wide by 5" long, unfolds to 8" overall length
- Blades lock open in 3 different positions
- Comes with one razor blade

DELTA HEAVY-DUTY GLASS SCRAPER



- Bio-engineered shape for better grip and precise control
- Longer handle keeps hands farther away from blade
- Blade is held at 5° offset angle for improved scraping Extra firm blade clamp holds blade under scraping pressure
- Comes with one blade

RAZOR BLADE SCRAPER

F4208

- Stainless Steel Hand Scraper
- Positive Brass Retention Slide
- Comes With a Package of 5 single edge blades
- Overall length 3-3/4"
- Made in USA

RETRACTABLE UTILITY BLADE GLASS SCRAPER

F41082

- Use to remove paint and stickers from glass, mirrors or windshields
- Rugged polystyrene construction
- Retractable blade with positive lock
- Built in scraping guide produces clean edges while leaving paint in contact with glass for proper seal
- 1 blade included



F4605 5 Pack Replacement Universal Utility Blades

TOOLS — RAZOR BLADE & UTILITY KNIVES

OLFA- SNAP - OFF BLADE KNIVES

EXTRA HEAVY-DUTY RATCHET

HEAVY-DUTY AUTO LOCK

Anti-slip cushion-grip handle

Built-in metal for prying paint cans and more

Superior Quality

LOCK CUTTER F41531

Cushion grip Chemical resistant

UTILITY KNIFE F41244

Always Sharp

Economical

EXTRA HEAVY-DUTY REPLACEMENT BLADE



- 7 cutting edges per blade
- Package of 5

H H /////

ULTRAMAX SNAP-OFF BLADE

18mm double honed blade for extreme sharpness

SafetyEasy Blade Adjustment

- 8 cutting edges per blade Package of 5

RATCHET-LOCK UTILITY KNIFE

Contoured durable handle

MULTI-PURPOSE UTILITY KNIFE F4527

- For light duty cutting jobs Slide lock and pocket clip

MULTI-BLADE AUTO LOAD UTILITY KNIFE

Automatic blade load-holds 5 blades







CUSHION GRIP RATCHET-LOCK UTILITY KNIFE

· Ratchet-wheel blade lock



SNAP-OFF BLADE

- 9mm carbon tool steel
- 13 cutting edges per blade
- Package of 10



ULTRA MAX SNAP-OFF BLADE

F4650

Copyright © 2023

- 9mm double honed for extreme sharpness
- Package of 10



F41238

TOOLS — RAZOR BLADE & UTILITY KNIVES (continued)

STAINLESS STEEL SNAP-OFF BLADE

- 13 cutting edges per blade
- Package of 10



13 Sharp points per blade





STAINLESS STEEL SLIDE LOCK **UTILITY KNIFE**

F41521

· For moist environment where rust is a concern

REPLACEMENT SNAP-OFF BLADES (18MM)

F4506

F4151

- 8 sharp points per blade
- Carbon steel (5 blades/pack)



STAINLESS STEEL AUTO-LOCK **UTILITY KNIFE**

F41166

Automatic blade lock
 Replacement blade - F4650

REPLACEMENT SNAP-OFF BLADES (9MM)

- 7 cutting edges per blade Carbon steel (10 blades/pack)



SNAP-OFF BLADE KNIFE (9MM)

- Cut cardboard, foil, paper, wallcovering, etc.
- 13 Sharp points per blade Retractable blade with AUTO-LOCK
- Stainless steel blade track
- Built-in blade breaker
- 3 Blades included (2 Blades stored in handle)

FASTBACK™ FLIP UTILITY KNIFE F42354



- Tool free blade change Wire stripper strip up to 10 ga wire
- Integrated gut hook cut without opening knife
- Length: 7-1/4

SNAP-OFF BLADE KNIFE (18MM)

F41384

- Cut carpeting, drywall, wallcovering, cardboard, etc.
- 8 sharp points per blade
- Retractable blade with one-piece positive lock
- Stainless steel blade track
- Built-in blade breaker
- 3 blades included (2 blades store in handle)

UTILITY BLADES

- Heavy duty utility blade #92 (.025 gauge) F41305 Fits most utility knives including Stanley, Red Devil, and Fuller
- Ideal for cutting drywall, fiberglass, wood, plastic, cardboard, etc.
- Use with F4208 tool
- Dispenser unit with 100 H.D. Blades F41234



UTILITY KNIFE

F41003

- Ergonomic Shape, 6" overall length
- Handle is painted safety orange Industrial Quality, Retractable Blade With 3 position Zinc Retractor
- Safety Nose overlaps top & bottom for blade security
- Store extra blades in handle (comes with one blade)
- Made in USA
- Use utility blade F41305 as replacement

LENOX

LENOX GOLD BI-METAL **UTILITY KNIFE BLADES**

- Patented bi-metal construction
- Gold coated edge is double the harness of ordinary utility blades
- Shatter-resistant and virtually unbreakable Up to 5X the life of standard carbon steel blades
- 4 notch design extends blade further for deeper cutting



SELF-RETRACTING SAFETY KNIFE

- Smooth self-retraction spring loaded shuttle
- Comfortable, non-slip handle ergonomic design Dual function utility knife and box cutter settings
- No tool needed for blade change quick blade changes
- Stores up to 5 blades

BLADE BANK

- Bright, yellow plastic, one-time-use blade container (9 1/2" H x 3 1/2" W x 2 1/2 D)
- Get used blades out of the workplace, off the floor, out of trash containers and all potentially hazardous locations Holds approximately 1000 utility style blades
- When plastic unit is full dispose of in any approved receptacle



With Wall Bracket

LENOX

LENOX GOLD UTILITY KNIFE PACK F41458

- Retractable utility knife with 3 Lenox Gold Utility Knife Blades
- Extremely durable stainless steel nose resists wear
- Quick release allows operator to change blades without opening handle
- Able to store up to 5 blades in the handle

BLADE DISPOSABLE CONTAINER F41047

Includes wire holder

For utility-Knife blades and single-edged razor blade



LENOX

3 MaintenanceTools & Supplies

WIPERS — TORK ADVANCED 430

- Highly absorbent excellent wipe-dry capabilities Soft, cloth-like feel
- Strong & durable, won't tear easily

- - Absorption excellent for cleaning up both oil and water Particularly good for cleaning glass does not leave any lint or streaks on surfaces

F4935

- Pop-Up Box
- **Size:** 9.5" x 16.5" **Color:** White
- Case Qty: 8 Boxes
- Box Qty: 100 Wipers



F41671

- Centerfeed Roll
- **Size:** 9.5" x 16.5" **Color:** White
- Roll Qty: 300 Wipers
- Case Qty: 2 Rolls Dispenser F4748



F44125

- Top-Pack Refill **Size:** 13.6" x 16.3'
- Color: White
- Box Qty: 150 sheets
- Case Qty: 5
 - Dispenser: F43284



WIPERS — TORK ADVANCED 450

- Highly absorbent excellent wipe-dry capabilities
- Strong enough to power through oil, grease & solvents versatile enough for everyday, general cleanup & spills
- Thick, low linting cloth-like construction excellent replacement for cloth rags
- Durability & high performance characteristics make these a perfect choice for a wide variety of uses



- Pop-Up Box
- Size: 9.5" x 16.5"
- Color: White Box Qty: 100 Wipers
- Case Qty: 8 Boxes



- ShopMax Centerfeed Box
- **Size:** 9" x 13"
- Color: White
- Box Qty: 200 Wipers
- Case Qty: 4 Boxes



F41342

- ShopMax Roll
- **Size:** 9" x 13"
- Color: Blue
- Roll Qty: 56 Wipers
- Case Qty: 30 Rolls



F4444

- ShopMax Centerfeed Dry Wipe Bucket Dispenser Refill
- Size: 10" x 13"
- Color: White
- Roll Qty: 200 Wipes
- Case Qty: 2 Rolls



F41692

- ShopMax Centerfeed Dry Wipe
- **Bucket Dispenser**
- Size: 10" x 13"
- Color: Blue Bucket Qty: 200 Wipes
- Case Qty: 2 Buckets
- Refill: F41494



F41494

- ShopMax Centerfeed Dry Wipe Bucket Dispenser Refill
- Size: 10" x 13"
- Color: Blue Roll Qty: 200 Wipes
- Case Qty: 2 Rolls



- Centerfeed Jumbo Roll **Size:** 9.8" x 13.25"
- Color: Blue
- Roll Qty: 800 Wipes Dispenser - F4731

WIPERS — TORK PREMIUM 510/530 MULTI-PURPOSE CLOTH

Premium cloth wipers are perfect choice for cleaning surfaces, tools & other heavy-duty



- F41738
- Pop-Up Box **Size:** 8.5" x 16.5"
- Color: White Box Qty: 80 Wipers Case Qty: 5 Boxes

F4316

- 1/4 Fold Box **Size:** 12.6" x 13"
- Box Qty: 50 Wipers
- Color: White
- Case Qty: 6 Boxes

- Centerfeed Roll Size: 10" x 12 6"
- Color: White
- Roll Qty: 500 Wipers Case Qty: 1 Rolls Dispenser - F4731
- F4307

High absorbency makes cleaning oil, grime and solvents quick & easy

Low lint design makes them perfect for most jobs

Soft, flexible cloth can fit in tight spaces

TORK

- Unique gray color distinguishes it from typical wipers Ideal for cleaning oil and grease

- Excellent absorbency cleans overspray
 Contains 100% synthetic and virgin fibers
 Extremely durable cloth with low-lint brushoff
- Top-Pak style Size: 15"x16.5"
- Color: Gray
 Package Qty: 140 Wipers
 Case Qty: 5 packs
 Dispenser 865.05.1000

4

WIPERS — TORK WASHROOM REFILLS



- Centerfeed Hand
- Towel Roll
- Size: 8.25" x 11.8"
- Color: White Roll Qty: 600 Towels
- Case Qty: 6 Rolls



- Universal 2-Ply Bath Tissue Roll
- Roll Width: 4.5"

- Roll Length: 156.25 ft Roll Dia.: 4.35" Roll Qty: 500 Sheets
- Case Qty: 96 Rolls

WIPERS — TORK DISPENSERS



F4748 Centerfeed Dispenser 14"H x 9.75"W x 9"D



F42171 Centerfeed Dispenser 17.5"H x 12.9"W x 11.9"D



F43284 Folded Towel Dispenser Capacity 225 Wipers 15.51"H x 16.81"W x 8.11"D



F4731 Floor Stand Dispenser

SHOP TOWELS & WIPES

SHOP TOWELS

Description	Size	Packaging	Part No.
Shop Towel (Red)	15" x 15"	25 Towels/bundle	F4744
Terry Towel (White)	14" x 17"	12 towels/bundle	F4730
Cotton Rags(White)		25# Box	F4121





- Multi-use
- 100% cotton; pre-washed
- Shop towel (Red), Terry towel (White) Sold by the bundle

HEAVY WEIGHT WIPERS

Color	Wipers/Box	Part No.
Blue	100	F4538

- Made for the toughest clean-ups
- Extra Strong
- **Pop up box-wiper size:** 9.5" x 16.5"



CHUX GENERAL PURPOSE WIPER

Color	Wipers/Box	Part No.
White	150	F41333

- Absorbant four-ply scrim towel
 Wipe dry feature for streak-free wiping
- Low linting 9.5 x 16.5





GEORGIA PACIFIC — MULTI-FOLD & C-FOLD TOWELS



The EPA Comprehensive Procurement Guideline Program is a federal buy-recycled program that is managed by the U.S. Environmental Protection Agency. This program has been developed to promote the use of recovered materials. It also designates items with minimum recovered fiber content that procuring government agencies must purchase.

EcoLogoTM is North America's largest, most respected environmental standard and certification mark. The EcoLogo program compares products and services with others in the same category and awards the EcoLogo certification to those that are environmentally preferable.

SIGNATURE® 2-PLY PREMIUM **MULTIFOLD PAPER TOWELS** F41404



- Premium 2-Ply towel offers super absorbency with every hand dry Customer-preferred patented honeycomb pattern creates thick, luxurious softness
- Designed to fit into a wide range of multifold dispensers **Dispensers:** F41327 (Chrome)
- Sheet Size: 9.2" x 9.4"
- 125 Sheets per pack/16 packs per case
- Sold by case

4



ACCLAIM® MULTIFOLD **PAPER TOWELS** F4210



- Designed to fit into a wide range of multifold dispensers Offers dependable absorbency, thickness, and strength
- Low per-unit cost make these paper towels an affordable, good everyday choice **Dispensers:** F41327 (Chrome)
- Sheet Size: 9.2" x 9.4"
- 250 sheets per pack / 16 packs per case
- Sold by case



ENVISION® MULTIFOLD BROWN PAPER TOWELS F4800



- Designed to fit into a wide range on multifold dispensers Offers dependable absorbency, thickness, and strength
- Low per-unit cost make these paper towels an affordable choice for high traffic areas
- Recycled material meets or exceeds EPA Comprehensive Procurement Guidelines for minimal post consumer waste percentage
- Dispensers: F41327 (Chrome)
- **Sheet size:** 9.2" x 9.4" 250 sheets per pack / 16 packs per case
- Sold by case



SIGNATURE® 2-PLY PREMIUM C-FOLD PAPER TOWEL



- Premium 2-Ply towel offers more absorbency with every hand dry Designed to fit into a wide range on multifold dispensers
- Customer-preferred patented honeycomb pattern creates thick, luxurious softness
- **Dispensers:** F41327 (Chrome) **Sheet Size:** 10.1" x 13.2"
- 120 Sheets per pack / 12 packs per case
- Sold by case



MULTIFOLD PAPER TOWEL **DISPENSERS**



Offers an economical and versatile approach to towel dispensing



COMBINATION C-FOLD OR

4

PAPER — GEORGIA PACIFIC UNIVERSAL ROLL TOWELS

SIGNATURE® 2-PLY PREMIUM HIGH **CAPACITY ROLL TOWELS**

F4203

- 2-Ply towel offers more absorbency with every hand dry
- Customer-preferred patented honeycomb pattern creates thick, luxurious softness
- Designed to fit into a wide range of universal hardwound roll dispensers
- Dispenser: F41094
- Roll Width: 7.87"
- Core Size: 1.625"
- 600 Feet per roll
- 12 Rolls per case Sold by case





ENVISION® HIGH CAPACITY ROLL TOWEL EcoLogo..

F4461

- Offers dependable absorbency, thickness, and strength
- Designed to fit into a wide range of universal hardwound dispensers
- Low per-unit cost make these paper towels a good everyday choice
- Dispenser: F41094
- Roll Width: 787
- Core Size: 1.625
- 800 feet per roll 6 Rolls per case
- Sold by case



PREFERENCE® 2-PLY PERFORATED **ROLL TOWEL**

F4851

- Lasting strength and absorbency make this towel ideal for everyday cleaning and wiping tasks.
- Fits any "household" paper holder / dispenser
- 85 Sheets per roll
- 30 Rolls per case
- Sold by case Roll Width: 11
- Core Size: 1.625"






PREFERENCE® HIGH CAPACITY ROLL TOWEL

F41150

- High quality, white hardwound towels offer quality & reliable performance while keeping costs under control
- High Capacity 1000 foot roll reduces maintenance intervals and risk of run out
- Designed to fit into a wide range of universal hardwound
- Preferred choice for high traffic washrooms
- Dispenser: F41094 Roll Width: 7.87"
- Core Size: 1.625"
- 1,000 feet per roll
- 6 Rolls per case
- Sold by case

ENVISION® HIGH CAPACITY ROLL BROWN PAPER TOWEL EcoLogo.





- Dependable absorbency, thickness, and strength
- Designed to fit into a wide range of everyday dispensers
- Affordable choice for high-traffic areas
- Dispenser: F41094 Roll Width: 7.87"
- Core Size: 1.625"
- 800 Feet per roll
- 6 Rolls per case
- Sold by case

VISTA® HYGIENIC PUSH PADDLE ROLL

PAPER TOWEL DISPENSER F41094

- Great combination of portion control for operational efficiency and an enhanced push paddle design for hygienic dispensing
- The push-paddle design allows for "limited hand contact" dispensing which helps reduce the risk of crosscontamination Dispenses high capacity 8 Inch diameter rolls
- ADA compliant when mounted properly
- Perfect for manufacturing, offices, schools and other high traffic areas



PAPER — GEORGIA PACIFIC ENMOTION, ROLL TOWELS


en MOTION° HIGH CAPACITY ROLL **TOWEL**

F4813

- One-at-a-time, touch free dispensing reduces usage and minimizes the risk of cross contamination
- Premium towels for dependable, cost-saving performance and customer satisfaction
- Each high capacity roll provides up to 800 hand dries for continuous service and reduced service visits
- Specifically designed to be used with the innovative wall mounted enMotion * touch-free dispensers
- 800 Feet per roll
- 6 Rolls per case
- Sold by case



en MOTION° HIGH CAPACITY BROWN ROLL TOWEL EcoLogo



- Each high capacity roll provides up to 800 hand dries for continuous service and reduced service visits
- Specifically designed to be used with the innovative wall mounted enMotion touch-free dispensers
- 800 Feet per roll
- 6 Rolls per case
- Sold by case



en MOTION° WALL MOUNT AUTOMATED TOUCHLESS TOWEL DISPENSER

- "Touchless" dispensing minimizes the risk of cross-contamination & creates a more hygienic environment
- $Adjustable settings for sheet length, time delay, sensor range and dispensing mode \'{controls} usage and increases operational efficiency and the setting of the sensor of the sensor$
- One-at-a-time towel dispensing reduces waste and lowers operating costs
 When compared to standard folded towel system, the enMotion "dispenser helps achieve waste reduction at the source by reducing towel usage by up to 30%
- Powered by 4 Standard D-Cell Batteries (Included)
- **UL Listed**







PAPER — GEORGIA PACIFIC CENTERPULL TOWELS

SOFPULL® PREMIUM 1-PLY REGULAR CAPACITY **CENTERPULL PAPER TOWELS**

F41395

- Touchless dispensing minimizes the risk of cross contamination Soft, absorbent towel dries hands quickly or wipes up large spills $and \, tough \, messes \,$
- One-at-a-time dispensing minimizes waste
- Must use with SofPull towel dispenser (F4231)
 Roll Width: 7.8"
- Core Size: 2.375" Sheet Size: 7.8" x 15"
- 320 Sheets per roll / 6 Rolls per case
- Sold by case



SOFPULL® REGULAR CAPACITY CENTERPULL **TOWEL DISPENSER**

- Touchless dispensing minimizes the risk of cross contamination Dispenses regular capacity 320 sheet rolls ideal for steady traffic
- areas and extended service intervals Easy to load, self-threading design
- Durable construction to maintain aesthetics
- Must use with SofPull centerpull towels (F41395)



4

ACCLAIM® 1-PLY CENTERPULL PERFORATED TOWELS

- Quick and easy hands free dispensing helps reduce the risk of cross contamination
- High capacity centerpull rolls great for high-traffic areas
- Sheet Size: 7-1/2" x 12"
- Roll Width: 7.25"
- 1000 Sheets per roll / 6 Rolls per case
- Sold by case



CENTERPULL TOWEL AND WIPER DISPENSER

F41026

- High-Impact plastic construction is durable, washable, and stands up to most cleaning agents, ensuring years of cost-saving
- High-capacity multi-substrate centerpull dispenser dispenses a variety of medium duty wipers for all your particular wiping tasks
- Ideal for use in manufacturing, education, stadium, travel and other high-traffic facilities





PREFERENCE® 2-PLY CENTERPULL PERFORATED PAPER WIPERS

- $Hands-free\ dispensing\ minimizes\ the\ risk\ of\ cross\ contamination$
- Embossed for superior absorbency and softness
- Can be used as a premium hand towel or as a medium-duty wiper
- Ideal for high traffic areas
- Roll Width: 8.25"
- Core Size: 2 375

- Sheet Size: 8-1/4" x 12" 520 Sheets per roll / 6 Rolls per case
- Sold by case





PAPER — GEORGIA PACIFIC FACIAL TISSUE

PREFERENCE* FACIAL TISSUE, FLAT BOX

F41105



- Soft, absorbent, value-oriented white 2-ply facial tissue offers a cost-effective solution for high-traffic facilities Color contrast sheets help indicate when it's time to
- change the tissue box
- 100 Sheets per box
- 30 Boxes per case
- Sold by case



ENVISION® FACIAL TISSUE, FLAT BOX

F4239





- Affordable solution for locations with multiple areas
- Economical facial tissue employees, guests, tenants will appreciate
- 100 Sheets per box
- 30 Boxes per case
- Sold by case



PAPER — GEORGIA PACIFIC BATHROOM TISSUE

ANGEL SOFT PS® 2-PLY PREMIUM EMBOSSED **BATHROOM TISSUE**

- High capacity 450-sheet count saves decreases roll changes which reduces labor costs.
- Safe for all standard sewer and septic systems
- 450 Sheets per roll
- 80 Rolls per case
- Sold by case





PREFERENCE® 2-PLY EMBOSSED **BATHROOM TISSUE** F4398

Safe for all standard sewer and septic systems 550 Sheets per roll

- 80 Rolls per case
- Sold by case





ENVISION® 2-PLY EMBOSSED BATHROOM TISSUE F41124



- 2-Ply embossed sheet engineered for improved softness & durability Safe for all standard sewer and septic systems
- 550 Sheets per roll
- 80 Rolls per case
- Sold by case





PAPER — VON DREHLE FOLDED TOWELS

You don't have to choose between recycled paper and superior performance. These soft, absorbent towels have a drying strength that reduces consumption. Packaged for easy handling and storage, these premium towels provide softness and absorbency your customers will appreciate. Ideal for office buildings, hotels, restaurants, college or universities.

- F43082 -C-fold

 Towels combine a quality look & feel with economy and practicality
- Sheet Size: 10-1/8" x 13"
- 150 Towels per pack
- 16 packs per case
- Made from 100% recycled fiber
- Dispenser: F43080
- Sold by case



- F42176 -Multifold

 Each full size towel is dispensed individually assuring superior hygiene & continuous dispensing **Sheet Size:** 9-1/4" x 9-1/2"
- 250 Towels per pack
- 16 Packs per case Green Seal Certified
- Dispenser: F43080
- Sold by case





F43080

- C-Fold/Multifold Combination Dispenser
- Transparent smoke cover Holds 300 C-fold or 500 Multifold towels at one time
- Size: 5"D x 11.25"W x 15.25"H





PAPER — VON DREHLE FACIAL TISSUE

These soft, white tissues are designed for use alone or in a countertop dispenser. Because these tissues easily pull out one at a time, fewer are

- 2 Ply
- Sheet Size: 8.5" x 7.5"
- 100 Sheets per box
- 30 boxes per case Sold by case





PAPER — VON DREHLE HARDWOUND TOWELS

These bulky, thirsty towels are soft, strong and absorbent, yet competitively priced. Designed to fit into a wide range of dispensers, economy hardwound everyday towels help you keep costs under control. Low per-unit costs makes these towels the affordable choice for high-traffic areas such as washrooms in government and public facilities, office buildings, foodservice facilities and lodging.

F42137

- Mechanical Hands-Free Dispenser
- For standard 8" wide hardwound roll towels
- Attractive design is perfect for most any application
- No batteries to replace
- Controls usage





Preserve

2-Ply

Premium

Towels

- Roll Width: 7.9"
- Core Size: 2"
- 800 feet per roll
- 6 rolls per case Green Seal Certified
- Mechanical Hands-Free Dispenser: 865 07 8861
- Electronic Hands-Free Dispenser: 865.07.2245\
- Sold by case





F42175

- Perforated Household Roll Towel
- Highly absorbent & durable ideal for tough jobs
- 2 ply construction 11" x 9" sheets
- 85 sheets per roll
- 30 rolls per case
- Green Seal Certified
- Sold by case



- Roll Width: 10" Core Size: 1.75"
- 800 feet per roll
- 6 rolls per case Green Seal Certified
- Designed to fit 10" major brand electronic hands-free dispensers Dispenser: 865.07.1080
- Sold by case





PAPER — VON DREHLE CENTERPULL TOWELS

Centerpull systems are the most efficient, economical, hands-free drying method available. Ideal for restrooms, kitchens, food preparation areas, and other high-traffic locations where sanitation is important. You use only the towel you touch, eliminating cross-contamination. Each roll is perforated to deliver only one clean, dry, germ-free sheet at a time tocontrol usage and reduce waste. Green Seal Certified.



F42177

- 2 Plv
- Roll Diameter: 8.3"
- Roll Width: 7.6"
- Core Size: 2 36'
- 600 feet per roll 6 rolls per case
- Dispenser 865.07.6622
- Sold by case



F42549

- Roll Diameter: 8.4"
- Roll Width: 7.6"
- Core Size: 2.36" 1000 feet per roll
- 6 rolls per case Dispenser - 865.07.6622
- Sold by case



F42178

- Standard Centerpull Dispenser Transparent smoke cover
- Unique mounting system with removable mounting plate
- No moving parts simplest, most cost effective, hands-free towel dispenser available
- Watertight can be used in moist environments or where washdowns are required





- 2 Ply Mini-Roll
- Roll Diameter: 5.8"
- Roll Width: 8.3" 264 feet per roll
- 12 rolls per case Dispenser - 865.07.2644
- Sold by case





F42133

- Mini Centerpull Dispenser
- Transparent smoke cover
- Perfect for high-traffic limited space areas
- Unique mounting system with removable
- mounting plate Size: 7"D x 14"H x 8"W



4

PAPER — VON DREHLE BATHROOM TISSUE

Feather Soft is a universal, soft, absorbent, economical 2-ply tissue that delivers quality, value and performance. Elegantly embossed, enhances bulk and softness. Each roll is overall wrapped, ensuring sanitary protection. Easy start tail seal prevents waste. Special tightly wound rolls for source reduction and space savings benefits. Rapid break-up capabilities are ideal for all plumbing systems.

Biodegradable and safe for use in septic systems, boats, RVs and motorhomes

Made from 100% recycled fibers an environmental benefit, and a positive image builder.



F42136

- Tissue Size: 4.5" W x 3.6" L
- Safe for sewer and septic systems
- 500 sheets per roll
- 96 rolls per case
- Twin Roll Dispenser 865.07.2500
- Sold by case





F43081

- Standard Twin Roll Dispenser
- Holds 2 rolls of standard bath tissue up to 5.3" diameter and 4.5" width
- Translucent cover to monitor tissue supply
- Rolls selector eliminates stub roll waste
- Reserve roll is enclosed for maximum hygiene





PAPER — VON DREHLE JUMBO ROLL TOILET TISSUE

 $Jumbo\,Roll\,Bathroom\,Tissue\,(JRT\,tissue)\,is\,an\,affordable\,choice\,for\,high-traffic\,areas, such as\,washrooms\,in\,hotels, office\,buildings, public facilities, schools, foodservice\,and\,fine and the such as a constant of the such a$ healthcare facilities. Each jumbo-sized roll delivers an economical 1,000 feet of tissue, which means reduced maintenance time and greater customer satisfaction by decreasing the chances of run-out during peak times.



F42173

- Two ply construction for the softest feel
- Industry standard 9" diameter roll 1000 feet per roll
- 12 rolls per case
- JRT Single Roll Dispenser 865.07.4200
- JRT Twin Roll Dispenser 865.07.3253
- Sold by case





F42135

- Single Jr. Jumbo Roll Dispenser
- Perfect for high traffic areas where space is limited
- Holds one 9" diameter rolls with 3.3" cores
- Virtually indestructible





F42134

- Twin Jr. Jumbo Roll Dispenser
- Perfect for high traffic areas Holds two 9" diameter rolls with 3.3" cores Access control slide eliminates stub roll waste
 - **RENO**





ECOSAC CAN LINERS

	THE EITHER				
Part No.	Size	Color	Gauge	Gallon Capacity	Case Qty
F41295	24" x 32"	Brown	.35 mil	15	500
F4116	33" x 39"	Black	1.5 mil	33	150
F4978	40" x 48"	Black	1.5 mil	40-45	100
F495	38" v 60"	Black	1.5 mil	55	100

- Tri-extruded can liner with a center layer of recycled raw material
- Star-sealed bottom prevents vacuum at bottom of container that can restrict easy lifting
- All resins are 100% recyclable, inks and colorants
- are heavy-metal free

DETERMINING CORRECT LINER SIZE:

Bag Width: To calculate the proper width of the can liner for your container, simply divide the circumference of your container by 2 **Square Container Circumference** = sum of all four sides added together

Round Container Circumference = diameter multiplied by 3.14

Bag Length: (Round + Square Containers) add the height of the container, plus 4-5 inches for overhang



Part No.	Size	Color	Gauge Microns	Gallon Capacity	Case Qty
F42206	24" x 33"	Natural	8	12-16	1,000 (20 rolls of 50)
F42207	30" x 37"	Natural	13	30	500 (10 rolls of 50)
F42208	33" x 40"	Natural	16	33	250 (10 rolls of 25)
F42211	38" x 60"	Natural	17	55	200 (8 rolls of 25)
F42217	40" x 48"	Natural	13	45	250 (10 rolls of 25)
F42213	43" x 48"	Natural	16	56	200 (8 rolls of 25)

- Excellent economical choice for heavy, wet trash & soft refuse as long as there are no sharp or irregular shaped objects.
- Great for offices, restrooms, waiting areas & restaurants
 Manufactured with star seal bottoms, which will virtually
- eliminate leaks & also conform better to shape of the waste receptacle.
- Liners are on coreless rolls
- **SOLD BY CASE**



TRASH CAN LINERS (continued)

PREMIUM LOW DENSITY CAN LINERS

Part No.	Size	Color	Gauge Mils	Gallon Capacity	Case Qty
F06965	24" x 32"	White	.5	12-16	500
FW121606	33" x 39"	White	.75	33	150

- Superior strength, puncture & tear resistance
- Stretchable Great for trash with sharp, irregular edges such as bolts, glass, sticks, utensils etc.. Individually folded & manufactured with star seal
- bottoms for maximum performance **SOLD BY CASE**



HEAVY-DUTY MUNICIPAL CAN LINERS

Part No.	Size	Color	Gauge Mils	Gallon Capacity	Case Qty
F43169	38" x 58"	Black	1.6	60	100

- Heaviest, true gauge recycled can liners available Exceptional puncture & tear resistance
- Ideal for automotive, industrial, public facilities, food service & construction applications
- Individually folded & manufactured with star seal bottoms for maximum performance **SOLD BY CASE**




BRUSHES

PAINT BRUSHES

	···
Width	Part No.
1"	F31445
2"	F31860
3"	F31545
4"	F31940

- 100% black bristle for general
- purpose painting Plastic handle
- 9" Overall Length

PAINT BRUSHES





- Blended polyester bristle for general
- purpose painting Varnished wood handles

PARTS CLEANING BRUSH

F41496

- Nylon Bristles
- Natural Lacquered Handle 11" Overall Length

CHIP AND OIL BRUSH

Width	Part No.
1/2	F4332
1	F4957
1 1/2	F4547
2	F4760
21/2	F41392
3	F41194
4	F4285



- Smooth sanded handle with
- tin ferrule 7-1/2" Overall Length

SHOE HANDLE SCRATCH BRUSH

F41433

- Stainless steel bristles
- Hardwood handle
- Overall length 10"
- Length of trim 1-1/8"



SHOE HANDLE SCRATCH BRUSH

F41394

- Carbon steel bristles Hardwood handle
- Overall length 10"



HEAVY DUTY MILL DUSTER

F41006

- With brown plastic fill 1-3/4" trim length
- Clear lacquered hardwood block Popular in machine shops for clearing metal chips from drill
- presses, lathes, etc. Overall Length: 13"

SHOE HANDLE SCRATCH BRUSH

- Stainless steel bristles
- Hardwood Handle Overall Length 10"
- Length of trim 3/4"



ACID BRUSHES

F41205 — 3/8" F4376 — 1/2"

CURVED HANDLE SCRATCH BRUSH

Carbon Steel Bristles

Hardwood Handle Overall Length 14"



PLASTIC HANDLE "TOOTHBRUSH"

F41235 — Stainless Steel Bristles

F4528



WOODEN HANDLE "TOOTHBRUSH" SCRATCH BRUSH

F41228
• Stainless Steel Bristles



BRUSHES (continued)

PREMIUM WOOD HANDLE FITTING BRUSHES

F41609 — 3/8" F41367 — 1/2" **F41312** — 3/4" F4651

- 4" solid birch wood handle
- Single spiral 2-ply tempered carbon steel bristles Bristles contain 20% more material than standard fitting brushes

TRUCK WASH BRUSHES

Professional quality brushes for trucks, trailers & large vehicles



FOUNTAIN BRUSHES

- Professional quality for all types of vehicle wash downs Polystyrene bristles are resistant to acids, detergents, oil & solvents
- Nylon bristles are resistant to rot, mildew, alkalis, most solvents & heat
- Use with fountain brush handle 691.601



FOUNTAIN BRUSH HANDLE

- Tubular steel with baked enamel finnish
- Standard threads on the brush end with a water hose
- connector on the other end 7/8" diameter, 5 foot length



FENDER WASH BRUSH

- White Tampica
- 2" bristles set in hardwood block



WIRE WHEEL SPOKE BRUSHES

Perfect for removing built-up dirt between spokes F3908 - Large 17" long brush made with natural tampico bristles F3394 - Small 11-1/4" long brush made with cream polypropylene bristles



HEAVY-DUTY INTERIOR & UPHOLSTERY BRUSH

F42501

- Extreme flare is convenient for scrubbing hard-to-reach areas
- Crimped, cream polypropylene fibers set in a foam block



HANDLE SCRUB BRUSH

- Crimped white polypropylene bristles One piece plastic block and handle

 - Raised handle design Block size: 6-1/2"L x 2-1/4"W
 - Length of Bristles: 1-1/8"




HAND AND NAIL BRUSH

F41517

- Smooth hardwood block
- Natural tampico bristles **Block size:** 4-3/4"L x 1-1/2"W
- Length of Bristles: 5/8"



HAND AND NAIL BRUSH





Designed to be used in just about any environment where extra hand and nail cleanliness is required

- **HEAVY-DUTY FENDER/WHEEL SCRUB BRUSHES** $Crimped, stiff \ Blue \ Polyropylene \ bristles \ provide \ extra \ scubbing \ action$
- Bristles are highly resistant to acids, heat, chemicals & solvents



BODY BRUSHES

- Flagged-tip bristles provide for gentle washing of any surface Green Polystyrene bristles are resistant to acids & detergents



WHITE SIDEWALL BRUSH

F42500

- Brass wire
- Foam plastic block will not crack when left in tire cleaning solution
- Overall Length: 8-1/2" long
- Length of Bristles: 3/4"



VENT & DASH BRUSH F42504



- dust & debris from hard-to-clean seams in automobile dashboards, around vents, radios & speakers
- Soft natural boar bristles
- 6" long



PAINT SUPPLIES — ROLLER COVERS & FRAMES

PAINT ROLLER COVERS

Length	Nap	Use On	Use With	Part No.
4"	3/8"	Metal, Semi-Smooth Wood, Concrete	Enamels, Epoxies, Adhesives, Paint	F32604
9"	1/4"	Metal, Smooth Wood, Smooth Concrete	Enamels, Epoxies, Adhesives, Paint	F31263
9"	3/8"	Metal, Semi-Smooth Wood, Concrete	Enamels, Epoxies, Adhesives, Paint	F32154
9"	1/2"	Drywall, Rough Wood, Rough Cement	All Paint	F3360











PAINT ROLLER FRAME AND TRAYS

Description	Part No.
Paint Roller Frame 4"	F32557
Paint Roller Frame 9"	F32126
Paint Tray Metal 9"	F31184
Paint Tray Plastic 9"	F32106

- $Heavy\,duty\,roller\,frame$
- 5 wire cage and reinforced handle Galvanized metal and plastic paint trays

PAINT SUPPLIES — PUTTY & JOINT KNIVES

SCRAPERS

- High carbon steel blade
- Nylon handle
- 8" overall





O CHYDE

CHISEL PUTTY KNIFE

F3344 1-1/4" Stiff

- Extra heavy duty
- 8" overall
- Soft-grip ergonomic handle
- Great gasket scraper

CHISEL PUTTY KNIVES

- High carbon steel blade
- Nylon handle
- 7-1/2" overall






ECONOMY CHISEL PUTTY KNIFE F32332

1-5/16" Stiff

- High carbon steel blade Nylon handle

6-IN-1 PAINTER'S TOOL

F31474 2-1/2" Stiff



- High carbon steel blade
- Nylon handle

BENT CHISEL SCRAPERS

- 3" wide high carbon steel blade is angled at 20° for easy paint removal
- Polypropylene handle





BROOMS — FLOOR

FLOOR SWEEP — MEDIUM F4711

- For wet or dry sweeping rough or semi-smooth concrete, wood, asphalt, etc. Black plastic 3–1/8" bristles
- 24" wide clear lacquered hardwood block
- Comes with 5 ft. hardwood lacquered handle

FLOOR SWEEP — FINE



- For sweeping smooth, highly polished floors, varnished woods and smooth concrete.
- Will sweep very fine dust and grit.
- Silver flagged-tip plastic 3 inch long bristles 24" wide clear lacquered hardwood block
- Comes with 5 ft. hardwood lacquered handle

GARAGE BRUSH

- For wet or dry heavy-duty sweeping of concrete,
- sidewalks, garage and factory floors 24" wide lacquered hardwood block
- Palmyra fill, 4" trim
- Use with hardwood handle #691,1516 or plastic coated metal handle #691.1518
- Handle sold separately

FLOOR SWEEP — COARSE



- F41523
- For wet or dry sweeping of rough concrete or asphalt floors. Will not soften when exposed to water, oils, or greases
- Coarse brown plastic 3-1/8" bristles
- 24" wide clear lacquered hardwood block Comes with 5 ft. hardwood lacquered handle

BROOMS — **FLOOR** (continued)

TOUGH SWEEP - MEDIUM



- For semi-smooth tile, concrete and blacktop
- Yellow synthetic 3" trim bristles
- 18" wide snythetic block will not split, crack or warp
- Comes with 5' handle

REPLACEMENT HANDLE THREAD

Made of heavy duty fiberglass for any 15/16" diameter




REPLACEMENT HANDLE

Made of hardwood with a clear lacquered finnish

- One end rounded and the other with crimped-on
- metal threads to fit standard floor sweeps 15/16" diameter, 5 foot long

PLASTIC COATED METAL HANDLE

- Reinforced, heavy-duty metal handle
- Yellow plastic coating with hang tab
- 15/16" diameter, 5 foot length



- Fiberglass construction
- Threaded tip
- 1" Diameter, 60" long
 White *approved for food industry

HANDLE BRACE

F41317

- Heavy Duty handle brace made of alumínum bar stock
- Fits all the above brooms
- Comes with all screws and wing nuts
- Broom sold separately

DUST PANS

12 inch edge F41447 F4947 16 inch edge

- 20 gauge metal dust pans
- Black enamel finish Corrugated ribs for added strength



SNOW BROOM

F450

- Industrial Grade polyethylene foam molded head endures the harshest conditions and hundreds of vehicle clearings. Approved for use on Class A finishes and received the highest rating
- possible from an independent testing lab for non-abrasiveness, freeze resistance and durability 5-3/4" x 17" head weighs only 8 ounces
- 48" Vinyl coated metal handle
- Used by Auto Dealers, Municipal Agencies, Utility Company Fleets, Park 'n' Fly lots, Valet Services

FLOOR AND DRIVEWAY SQUEEGEES

F41274 — Straight Squeegee, 24' **F4714** — Curved Squeegee, 24"

- 2" wide x 1/2" thick high grade neoprene
- squeegee strip attached with plated screws Aluminum frame with taper handle socket
- Use with taper handle below (order separately)



LIGHT-DUTY

F43061

MODERATE-DUTY

F41779

- Made of best quality broom corn and fibre
- Sewed 5 times
- Broom cap has velvet trim
- Handle has a black lacquered finish

LOBBY DUST PAN - BLACK

12" wide mouth and 30" metal handle

Pivoting bucket locks open for hands-free disposal Designed for use on hard and soft surfaces



HEAVY-DUTY F41103

- Made of best quality broom corn and fibre
- Sewed 4 times and reinforced with wire band Made on a heavy-duty handle


WHISK BROOM F41352

- Made of selected fine broom corn
- 11 inch wide sweep



MAXIROUGH® LOBBY BROOM

- Thicker diameter polycorn bristles provide superior sweeping ability
- Offers liquid and chemical resistance as well as 250°F temperatures
- . Double sewn, hand wound construction increases durability
- 30" handle with an 8" sweeping surface



F41769 Red — fat and oil resistant F4534 Black — standard

- Use handle F4970 Soft and durable neoprene blade Heavy duty metal frame
- For Use On: Uneven, grouted and smooth surface floors For Use In: Shop areas, supermarkets, warehouses, kitchens and much




SQUEEGEE TAPERED HANDLE

15/16" diameter, 5 foot length



1-1/8" diameter, 5 foot length



MOPS

COTTON AND RAYON MOP HEADS

Description	Part No.		
24 oz. cotton	F41608		
32 oz. cotton	F4242		
24 oz. rayon	F41332		
32 oz. rayon	F4176		
AA 1 (A 1 1: 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			

- Made of 4 ply highly absorbent, long wearing yarns Mops are sewed 2 times
- Band is 1-1/4" wide
- Cotton = better absorbency
- Rayon = better durability



2407

MOP HANDLE

- Zinc-plated steel construction securely fastened to a No. 1 grade 1-1/8" diameter handle
- Quick-change type
- 7" head for 20 to 32 oz. mop heads



WET FLOOR SIGN - YELLOW F05997

- Professional quality, two-sided sign Specially contoured feet to minimize contact with floor to floor finishes
- Durable Polypropylene; $25'' \, tall \, x \, 11'' \, wide$
- BPA free



DELUXE TOILET BOWL MOP

- Full 1.oz, 5-3/4" mop head for greater absorbency
- Acid-resistant polypropylene strands
- 12" strong l-beam plastic handle, polypropylene White mop head with blue handle



SYR CLEANING PRODUCTS

SYR 8" FLOOR SCRAPER WITH BLADE F32393

- 8" metal floor scraper with blade
- Works with interchange handle Does not include handle



SYR 22" BLACK MOSS FLOOR SQUEEGEE

F32350

- 22" Black Moss Floor Squeegee
- Works with interchange handle Handle not included

SYR SWIVEL DECK BRUSH BLUE F32144

- Tough polypropylene bristles
- For use on hard floors Ideal for confined spaces
- 360 degree rotation
- Great for baseboards Works with interchange handle
- Handle not included



SYR 9" GROUT BRUSH

F32385

- Tough polypropylene bristles Angled Bristles for cleaning grout
- between tiles and floor edges Works with interchange handle
- Handle not included



SYR 53" INTERCHANGE ALUMINUM HANDLE

- Use with SYR interchange mops, brushes, squeeges....
- Heavy Duty aluminum handle



SYR COMBO BUCKET/WRINGER F42401

- Polypropylene bucket and wringer basket
- Ergonomic design taller for less bending
- Casters are non marking
- Designed to be used with SYR changer mops



AUTO DETAIL — APPLICATORS, SPONGES & TOWELS

SPUN GOLD® **CAR WASH PAD** F42477

- 9"x9"
- Made from heavy-duty synthetic fibers
- No cuff, all ends closed



GOLD NUGGET® PROFESSIONAL CAR WASH PAD

F3818

- 9"x9"
- Made from downy soft Lorene Fibers for Superior water absorbtion & retention
- No cuff, all ends closed



WASH MITT

- **F32114** 8" x 12"
- Made of long lasting soft synthtic fleece
- Has cuff & thumb



WASH & SCRUB COMBO SPONGE

F42478

- Heavy-Duty. 2 sponges in 1
- Gently cleans auto, truck, rv & marine surfaces
- Durable scrubbing back cleans auto grills
- & bumpers

 Material: Microfiber & polyester mesh exterior, Sponge interior
- Size: 9"x4-3/4"x2"



SURE SCRUB™ SPONGE F42480

- 3" x 5" x 1-1/2"
- Specially designed "honey comb" material will carry an abundance of soap & water.
- Safely scrub away stubborn bugs, bird $droppings\,\&\,other\,contaminants\,without$ harming clear coat finish




TIRE DRESSING APPLICATORS

- Contour design conforms to tires Non-absorbing foam reduces product waste
- Spreads dressing evenly and eliminates runs & drips
- Washable & reusable
- Excellent for low profile tires



MICROFIRER TOWELS

	DENTIONEED
Color	Part No.
Yellow	F42363
Green	F42365
Blue	F3465
White	F3880



- Picks up dust & microparticles like a magnet Machine washable without bleach or softeners
- 16" x 16"
- Sold 12 per bag

PVA IMITATION CHAMOIS

- F3646
 PVA material drys any surface without
- Absorbs water much faster then a towel or regular chamois
- Great to use in place of a regular leather chamois when dtying automobiles 17" x 27"



GENUINE WATER SPRITE® DRYING CLOTH

- Exclusive proven PVA material that gently cleans & dries fine finished surfaces Water Sprite actually lifts off residual dirt & grime away from the
- surface, leaving it clean & dry. It is not affected by mildew, bacteria or common household
- chemicals 791 sq. inches



SMARTRAGS™ MICROFIBER CLOTHS

Color	Part No.
Blue	F44579
Green	F44580
White	F44581
Yellow	F44582
Red	F44583

- Attract dust better than any other cloth 12" x 12"

- Tough on grease and grime
 Gentle lint-free and streak free
 Small and handy enough to take anywhere Use on glass, metal, wood, ceramics and paint



SPILL CONTROL — ABSORBENTS

UNIVERSAL ABSORBENT SOCKS

Description	Packaging	Part No.	
Universal Sock	Single Sock	F4796	
Universal Sock	40 Sock Case	F42229	



- Color: Grav



UNIVERSAL ABSORBENT PADS

Description	Single Pad Part No.	Case Qty	Case Part No.
Light Pad 15 x 18	F4356	200	F42223
Medium Pad 15 x 18	F4847	100	F42224
Heavy Pad 15 x 18	F4133	100	F42225

- Use for water and oil based fluids
- Point bonded for strength
- Perforated so you use only what you need
- Color: Gray

UNIVERSAL ABSORBENT ROLL

Description	Packaging	Part No.
Universal Absorbent Roll	Single Roll	F4941
Universal Absorbent Roll	2 Roll Pack	F42226
 Use with water and oil ba 	sed fluids	

- 30" x 150" Perforated Roll
- Color: Gray



OIL BASED ABSORBENT PADS

Description	Single Pad Part No.	Case Qty	Case Part No.	
Oil Pad 15" x 18"	F4104	100	F42231	
Heavy Pad 15" x 18"	F4861	100	F42232	

- Use for petroleum based fluids only
- Point bonded for strength
- Color: White

OIL BASED ABSORBENT ROLLS

Description	Part No.	THE STATE OF THE S
30" x 150" Roll	F41157	
Use for Petrolem based fluids only Color: White		

UNIVERSAL HI-VIS CAUTION ABSORBENTS

Description	Single Pad Part No.	Case Qty	Case Part No.
15" x 18" Pad	F44283	100	F44299
30" x 150' Roll	F44284	1	



- Hi-Vis yellow w/the international symbol for slip hazard repeating throughout the product making it ideal for use anywhere from factory to hospitality
- Spunbond side is abrasion-resistant, great for foot traffic or heavy-duty wiping applications
- Fine fiber side grips smooth surfaces (like cement) to reduce slips, trips & falls
- Absorbs most non-aggressive fluids, including oil (hydrocarbon-based fluids), water, glycols
- Perforated to help reduce waste.

DRUM TOP ABSORBENT PAD

Description	escription Packaging A		Oil Only Part No.
Drum Top Pad	Single Pad	F4801	F4391
Drum Top Pad	25 Pad Case	F42228	F42227

Cut to fit the top of any 55 gallon drum



SPILL MAGIC

Description	Part No.
3 lb. Bottle	F44607
 All-purpose absorbent powder 	

- Lightweight, high performing
- Quick clean-up
- Leaves surface dry and residue-free
- Ideal for cleaning industrial, food or biohazard spills
- Pour direct from bottle

SPILL CONTROL — SPILL KITS

MRO BUCKET SPILL KIT F4313

- Self-contained kit packed in reusable 5 gallon pail
- Absorbs all types of fluids Kit Contains:
- (10) universal perforated pads (16" x 20")
- (2) universal socks (3" x 48") (1) disposable bag with tie



QUIKLEEN® RECYCLE KIT

Designed specifically to ensure the most economical use of Quikleen® absorbent. By sifting and reusing the clean absorbent, you can save money on product and disposal costs Contents:

• (1) Plastic Dust Pan – F42326

- (1) Screen Sifter **F42327**
- (1) Wheeled Trash Can **F42328** (1) 24" Coarse Floor Broom **F41523**



OUIKLEEN® ABSORBENT

QUINCLEIN	ADSCREEN
Size	Part No.
Gallon Jug	F42324
Gallon Jug x 4	F42402
20 lb Pag	EADDDE

- $\label{eq:Quikleen} Quikleen \begin{tabular}{l} on the property of the process of the process$
- All natural, non-toxic, non-flammable, non-biodegradable, non-leaching, reusable
- Landfill acceptable and EPA certified

 1.5 lbs of Quikleen® will absorb an entire quart of motor oil vs 15 lbs of clay.
- Absorbs oils, fuels, grease, solvents, acids (except hydrofluoric), paint, coolants, bodily fluids, sewage



SHOP SUPPLIES

WELDING — STAR ALLOYS WELDING SUPPLIES

BRAZING, ELECTRODES, MIG WIRE & WELDING ACCESSORIES

- Premium alloys for all types of Automotive & MRO welding, joining, and brazing repairs
- The best welding electrodes in the industry, in the highest quality packaging available For repairing all types of metals and alloys, and all types of vehicles, equipment and structures Products for welding and joining many materials, including mild steel, low & medium carbon steels, low alloy steels, stainless steels, cast iron, aluminum, aluminum alloys, manganese, zinc alloys, dissimilar steels combinations, sheet metal, galvanized metals, copper and brass. High quality MIG Alloys in spools of solid wire or flux-coated wire

- High performance cutting/chamfering electrodes
 Brazing technology for brazing repairs made easy, clean and strong
 Fewer products to accomplish all of your repair needs, with no sacrifice in performance
- Accessories that make your job safer, easier and more efficient



WELDING — CHARTS

WELDING WALL CHARTS

- 18" x 24", full color
- Individual charts available for Star Alloys Electrodes, MIG, and TIG products

F012132 F012133 F012134 STARALLOYS STAR 🕰 LLOYS. STAR ALLOYS

F012136 Set of 3 charts

WELDING TOOL STEEL PREHEAT CHART F0812135

11" x 17", full color

 $Handy\, chart\, shows\, recommended\, preheat\, temperatures\, for the commendation of the$ welding various types of tool steels



WELDING — MACHINE



F44407


- Input Power voltage: 115/120
- Frequency: 50/60 hrz
- Rated output: 180a/24.2v mig 180a/28.2v mma
- Rated duty cycle: 104 degrees f 35%@180a mig/mma Imax(amps): 9 amps 115v, 36amp 220v
- Gross weight: 18 pounds

Compliant to: Can/csa-en60974-1:2 Ansi/ies 60974-1:2008 Aster contract: 265955



WELDING — BRAZING ROD

67FC SILVER BRAZING



- Superactive flux coated, cadmium free, silver brazing alloy with maximum silver content Special "Fast Flow" flux coating provides twice the base metal cleansing action of
- conventional silver flux coatings No odors from rubberized compounds yet the flux coating is totally flexible and non-fragile
- The only flux coated silver brazing alloy strong enough to clean oxidized stainless steel Can be used on almost any ferrous or non-ferrous metal except aluminum and magnesium
- Excellent for color matching on stainless steel and nickel
- Works on brass, copper, and stainless steel
- 67FC Silver can be used with either an oxy/acetylene torch or MAPP $^{\circ}$ gas



- Torch Setting: Slightly carburizing
- Working Temperature: 1210°F Melting Range: 1140°F (Solidus); 1200°F (Liquidus)
- Work Hardness: Rockwell C41-54; Brinell 380-550, Vickers 400-580
- **Tensile Strength:** 71,000 psi **Yield Strength:** 60,000 psi
- Elongation: 25%
- Hardness: Brinell 130

WELDING — BRAZING ROD (continued)

STAR ALLOYS **80FC BRONZE BRAZING** Package Size Flux Color Diameter Length Part No. 3/32" 5 lbs. F41821 18 Blue 1/8' Blue 5 lbs F41979

- Triple deoxidized bronze brazing alloy with "Anti-Glare" moisture sealed flux coating
- Unique "Anti-Glare" flux coating eliminates harsh chemical odors and the bright orange, visibility blocking glare of conventional sodium type flux coatings
- Flux cleansing action is exceptional on dirty steels and cast irons
- Ideal for joining copper base metals, cast iron, steels, including galvanized plated steels, thin sections and dissimilar metal combinations
- Fills gaps and holes
- 80FC Bronze is used with an oxy/acetylene torch



- Torch Setting: Neutral flame
- Working Temperature: 1595°F Melting Range: 1583°F to 1620°F
- Tensile Strength: 71,000 psi
- Yield Strength: 64,000 psi
- Elongation: 27%

31AZ BRAZING ROD

- 5/32" diameter x 18" long
- Packed in 1 lb. tubes
- Self-fluxing brazing alloy for thin aluminum, magnesium and zinc base metals Can be used with MAPP $^{\circ}$ gas or Propane
- Provides a good color match in many cases where appearance is important
- Deposits can be painted, plated, and machined
- Anti-drip properties

4

- Melting point: 732°F Tensile Strength: 50,000 PSI



- Bond Strength: 28,000 PSI
- Meets Mil Spec: MIL-R-4208
- No flux required
- Will not cause galvanic corrosion
- Cadmium and Lead free Excellent hole filling, pinhole and larger holes
- Exceptional gap filling properties

WELDING — ELECTRODES

220MS (MILD STEEL)



STAR A LLOYS

Diameter	Length	Flux Color	Package Size	Part No.
1/16"	12"	Tan	5lbs.	F41835
3/32"	14"	Gold	10 lbs.	F42010
1/8"	14"	Gold	10 lbs.	F41836
5/32"	14"	Gold	10 lbs.	F41838
3/16"	14"	Gold	10 lbs.	F41837

- Universal all-position electrode ideally suited for repair and fabrication of most types of mild steel and sheet metal
- Excellent for poor fit situations and joining sheet metal to thick stock
- No sticking and easy restrike
 Easily repairs galvanized steel even if dirty and greasy. Saves prep time.
- Replaces many 60 series (6010, 6011, 6013, etc.) electrode but has a higher tensile strength and elongation %
 Electrode can be bent without flux breakage



- Contact (drag) type transfer allows electrode to weld by itself **Welding Positions:** flat, horizontal, flat up and down, and overhead

- Recommended Current: DC Straight (-), Reverse (+) or AC Recommended Amperage Settings (min/max): 1/16" (20/40); 3/32" (50/70); 1/8" (70/110); 5/32" (115/140); 3/16" (150/200)
- Tensile Strength: 83,000 psi
- Yield Strength: 75,000 psi Elongation: 25%

1116LH (LOW HYDROGEN)



Diameter	Length	Flux Color	Package Size	Part No.
3/32"	14"	Gray	10 lbs.	F41992
1/8"	14"	Gray	10 lbs.	F41826
5/32"	14"	Gray	10 lbs.	F41828
3/16"	14"	Gray	10 lbs.	F41827

- Low Hydrogen, high strength DC electrode for joining low and medium carbon steels. low alloy steels, and construction steels
- Low spatter yield, self-releasing slag and uniform ripple deposits
- 1116LH has an extra low moisture content to reduce hydrogen induced cracking in the weld
- Welds even dirty and greasy steel. Saves prep time.
 Replaces many 70 series electrodes (7014, 7018, 7024, etc.) but has a higher tensile strength and elongation %
- Operates in all positions
- Welding Positions: Flat, Vertical Up and Down, Horizontal, and Overhead



- Recommended Current: DC Reverse (+)
- Recommended Amperage Settings (min/max): 1/8" (100/140); 5/32" (140/190) Tensile Strength: 120,000 psi
- Yield Strength: 96,000 psi
- Elongation: 23%
- Welding Techniques: For the majority of materials to be welded with these elctrodes, minimum preheats between 212°F 176;F (100°F 176°C) and 392°F 176°F (200°F 176°C) is required to avoid hydrogen induced "cold" cracking. Remove all surface contaminants. Maintain a short arc gap and use a stringer or slight weave technique. Chip slag thoroughly between passes

SHOP SUPPLIES

WELDING — ELECTRODES (continued)

2200DS (DISSIMILAR STEELS) Length

Diameter

3/32"

1/8"

5/32"



F41841

Lt. Gray Lt. Gray Special all-position high tensile strength electrode for all steels and dissimilar metals Excellent for stud pulling and broken stud and bolt removal Unique "Quick Freeze" coating simplifies vertical down and up welding

Lt. Gray

- Ideal for poor fit up joints in all positions Controlled weld puddle allows for filling holes and joining dissimilar steels
- Welds even dirty and greasy metal, Saves prep time
- Use to solve the problem of welding "mystery metals" Creates very little smoke compared to other electrodes
- Runs with very low spatter, so it's safer to operate
- Ideal for repairing tools, dies, spring steel and any dissimilar metal combinations, except for aluminum and copper alloys



- **Welding Positions:** flat, horizontal, vertical up and down, and overhead **Recommended Current:** DC reverse (+) or AC
- Recommended Amperage Settings (min/max): 5/64" (35/55); 3/32" (35/70); 1/8" (60/110); 5/32" (75/140)
- Tensile Strength as Welded: 128,000 psi
- Tensile Strength Work Hardened: 186,000 psi
- Yield Strength: 90,000 psi Hardness: Rockwell B97; Brinell 320
- Elongation: 32%

513MN (MANGANESE)



Diameter	Length	Flux Color	Package Size	Part No.
1/8"	14"	Dk. Grey	10 lbs.	F42047
5/32"	14"	Dk. Grey	10 lbs.	F41848
3/16"	14"	Dk. Grey	10 lbs.	F42048

- Joining, cladding, and repairing electrode for manganese steel that can be flame cut
- Spray transfer allows for smooth uniform overlays
- Work hardens easily in service
 Outlasts conventional hard facing alloys by as much as 10 to 1 in high impact applications
- Welds even dirty and greasy metal. Saves prep time.
- Ideal for repairing rail and construction equipment manufactured of manganese steel. Also recommended for hammers, crushers, and a variety of parts designed to resist impact.



- Welding Positions: flat, vertical up, horizontal, overhead
- Recommended Current: DC reverse (+) or AC
- Recommended Amperage Settings (min/max): 1/8" (90/125); 5/32" (125/170); 3/16" (160/225)
- Tensile Strenath: 116.000 psi
- Elongation: 38%
- Hardness: Rockwell B87-96; Brinell 170-220; Vickers 180-230
- Work Hardness: Rockwell C41-54; Brinell 380-550, Vickers 400-580

1120HF (HARDFACING)



Diameter	Length	Flux Color	Package Size	Part No.	50# Bulk Pack Part No.
1/8"	14"	Gray	10 lbs.	F41849	Turtitor
5/32"	14"	Gray	10 lbs.	F42055	F42056
3/16"	14"	Gray	10 lbs.	F42053	

- $A unique \, electrode \, combining \, unsurpassed \, weld ability \, and \, high \, hardness \, for \, excellent \, description \, and \, high \, hardness \, for \, excellent \, description \, descri$ abrasion resistance and moderate impact resistance
- Ideal alloy combination where hardness and toughness are required on carbon and alloy
- steels, manganese steels, and cast iron Wide-bead capability with low spatter, easy restrike, smooth overlays, high deposition, and self-releasing slag
- Welding Positions: Flat, Horizontal



- **Recommended Current:** DC Reverse (+) or AC Recommended Amperage Settings (min/max): 1/8" (110/140); 5/32" (160/200); 3/16" (210/270) Tensile Strength: N/A
- Elongation: N/A
- Hardness: Rockwell C58-60, Vickers 670-700
- Flux Color: Gray

111C (CHAMFERING)

Lenath

Diameter



1/8" 14" Black 10 lbs F41846 5/32" 14" Black 10 lbs. F42036 Chamfering/Cutting electrode with excellent arc blast force and restrike capability Reactionary black coating creates the highest levels of arc blast

Size

- Special coating elements form an electrically conductive "cup" for ease of restrike

Flux Color

Can be used on all metals that can't be cut with an oxy/acetylene torch Can gouge, bevel or cut all metals including stainless steels, aluminums and copper



- Excellent for the removal of stainless steel joints and overlays. No oxygen required **Welding Positions:** Flat, Vertical up, Vertical down, Horizontal, Overhead
- Recommended Current: DC Straight (-) or AC
- Recommended Amperage Settings (min/max): 1/8" (170/250); 5/32" (220/330)

WELDING — ELECTRODES (continued)

STAR ALLOYS 51CI (CAST IRON)

Diame	ter Length	Flux Color	Package Size	Part No.
3/32"	14"	Black	5 lbs.	F42044
1/8"	14"	Black	5 lbs.	F41847
5/32"	14"	Black	5 lbs.	F42045

- One of a kind heavily copper clad "Tri-metal" cored cast iron electrode High efficiency weld metal transfer totally eliminates electrode overheating Proprietary copper-nickel-iron deposit chemistry yields the ultimate combination of
- softness, ductility and tensile strength, for exceptional machinability Easily welds even dirty and greasy cast iron. Saves prep time. High deposition rate creates an extremely narrow heat affected zone
- Suitable for all weldable cast irons that require post weld machining
- Welding Positions: flat, vertical up, horizontal, overhead



- Recommended Current: DC reverse (+) or AC
- Recommended Amperage Settings (min/max): 3/32" (50/70); 1/8" (70/100); 5/32" (100/130) Tensile Strength: 77,000 psi
- Yield Strength: 54,000 psi
- **Elongation:** 30% **Hardness:** Rockwell B84-88; Brinell 176; Vickers 185
- Work Hardness: Rockwell C41-54; Brinell 380-550, Vickers 400-580

521AL (ALUMINUM)

4



Diameter	Length	Flux Color	Package Size	Part No.
3/32	10"	White	5 lbs	F42066
5/64"	10"	White	2.5 lbs.	F42068
5/64"	10"	White	5 lbs.*	F41853
1/8"	14"	White	5 lbs.	F41852

- Silicon aluminum ARC welding and TORCH brazing electrode with exceptional flux durability and self-lifting slag
- A universal electrode for welding all cast, wrought and extruded aluminum and aluminum alloys in all positions.
- Excellent for joining dissimilar grades of aluminum and clean, painted or dirty aluminum
- Recommended Current: DC reverse (+)



- Recommended Amperage Settings (min/max): 5/64" (35/70); 1/8" (60/110)
- Elongation: 18%
- Welding Positions: All Positions Tensile Strength: 34,000 psi Yield Strength: 20,000 psi

38SS (STAINLESS STEEL)



Diameter	Length	Flux Color	Package Size	Part No.
5/64"	12"	White	5 lbs.	F42032
3/32"	12"	White	5 lbs.	F41845
1/8"	12"	White	5 lbs.	F41844

- Special all position stainless steel electrode
- Unique "Quick Freeze" coating simplifies vertical down and up welding
- Ideal for poor fit up joints in all positions
- Controlled weld puddle allows for filling holes on stainless steels Welds all stainless steels, including those that contain molybdenum Welds even dirty and greasy stainless steels. Saves prep time.



- Welding Positions: flat, horizontal, vertical up and down, and overhead
- Tensile Strength: 80,000 psi Yield Strength: 56,000 psi
- Elongation: 42% Hardness: Rockwell B96; Brinell 209

WELDING — MIG WIRE

220MS (MILD STEEL) SOLID WIRE



Part No. F41833

F41832

2lb. 11 lb

Wire Diameter	Spool Size	Part No.	Wire Diameter
.023	2 lb.	F41997	.035
.023	11 lb.	F41829	.035
.030	2 lb.	F41831	.035
.030	11 lb.	F41830	.045
.030	33 lb.	F41998	

- 33 lb. 33 lb. F42004 A mild steel welding wire that produces high quality welds when used on dirty, oily or rusted steel, sheet metal, galvanized steel, and construction work
- Engineered to provide porosity-free, x-ray quality welds at the highest tensile strength
- Welding Positions: all positions

- **Tensile Strength:** up to 85,000 psi **Elongation:** 25%
- Operating Range: .023 (35-70 amps); .030 (50-100 amps); .035 (100-150 amps) Shielding Gas: 75%Ar/25%CO2

220MS (MILD STEEL) FLUX CORED WIRE



Wire Diameter	Spool Size	Part No.	Wire Diameter	Spool Size	Part No.
.030	2 lb.	F42000	.035	11 lb.	F42002
.030	10 lb.	F41999	.045	33 lb.	F42005
.035	2 lb.	F42003	-		

- A mild steel flux cored welding wire designed to weld carbon steel Produces smooth arc action, low spatter, full slag coverage and easy slag removal
- Use for lap and butt welds on galvanized sheet metal and repair of automotive sheet metal
- Welding Positions: all positions



Tensile Strength: up to 85,000 psi

Elongation: 26%

Operating Range: .030 (40-100 amps); .035 (100-130 amps); .045 (130-160 amps) Shielding Gas: 75% Ar/25% CO2




WELDING — MIG WIRE (continued)

1116LH (LOW HYDROGEN) SOLID WIRE

STAR ALLOYS

Wire Diameter	Spool Size	Part No.	Wire Diameter	Spool Size	Part No.
.023	11 lb.	F41822	.035	11 lb.	F41823
.030	11 lb.	F41982	.035	33 lb.	F41985
.035	2 lb.	F41824			
035	10 II-	E41004			



- Can be used as a build-up prior to applying harder overlays
- Welding Positions: all positions



- Elongation: 23%
- Operating Range: .023 (35-70 amps); .030 (75-120 amps); .035 (90-150 amps); 1/16 (150-200 amps)
- Shielding Gas: 75%Ar/25%CO2



1116LH (LOW HYDROGEN) FLUX CORED WIRE



Wire Diameter	Spool Size	Part No.
.030	2 lb.	F41983

- A flux cored welding wire designed for low and medium alloy steels
- Welding Positions: all positions Tensile Strength: up to 120,000 psi



- Elongation: 23% Operating Range: .030 (75-120 amps); .035 (90-150 amps) Shielding Gas: 75%Ar/25%CO2



38SS (STAINLESS STEEL) SOLID WIRE



Wire Diameter	Spool Size	Part No.	Wire Diameter	Spool Size	Part N
.023	10 lb.	F42023	.035	2 lb.	F41843
.030	2 lb.	F41842	.035	12.5 lb.	F42028
030	10 lb	F42025			

- Excellent for welding 300 series stainless steels
 Designed to deposit smooth, corrosion resistant welds without cracking or porosity
 Can be used as a build-up prior to applying harder overlays

- Welding Positions: all positions Tensile Strength: up to 83,000 psi

- Elongation: 36%
- Operating Range: .023 (50-125 amps); .035 (100-150 amps)
- Shielding Gas: Ar or CO2 mix



38SS (STAINLESS STEEL) FLUX CORED WIRE



Wire Diameter	Spool Size	Part No.
.035	2 lb.	F42030

- A flux cored welding wire designed for welding 300 series stainless steel
- Designed to deposit smooth, corrosion resistant welds without cracking or porosity
- Welding Positions: all positions Tensile Strength: up to 85,000 psi

- Elongation: 42%
- Operating Range: 75-100 amps
- Shielding Gas: Ar or CO2 mix



1120HF (HARDFACING) FLUX CORED WIRE



Wire Diameter	Spool Size	Part No.
.045	10 lbs.	F42050
.045	25 lbs.	F42051
1/16	25 lbs.	F42052


- A complex alloy designed to offer excellent abrasion resistance along with moderate impact resistance
- Ideal alloy combination where hardness and toughness are required on carbon and alloy
- steels, manganese steels, and cast iron
 Low spatter, smooth overlays, and high deposition rate
 Use on crusher jaws, hammers, bucket lips and teeth, wear plates, pins, axles, shafts, cams, etc.
- Welding Positions: Flat, Horizontal Tensile Strength: N/A Elongation: N/A


- Hardness: Rockwell C59-62 Operating Range: .045 (125-250 amps); 1/16 (150-300 amps) Shielding Gas: 75%AR/25%CO2



WELDING — MIG WIRE (continued)

521AL (ALUMINUM) SOLID WIRE





Produces a bright weld finish that is less sensitive to cracking **Welding Positions:** all positions

Tensile Strength: up to 34,000 psi

Elongation: 18%



Operating Range: .023 (50-80 amps); .030 (60-100 amps); .035 (100-150 amps); .045 (150-200 amps) Shielding Gas: 100% Ar

Note: alloy contains silicon and is not recommended if finished work is to be anodized.

5356 (ALUMINUM) SOLID WIRE

Wire Diameter	Spool Size	Part No.
.035	1 lb.	F42070

Only style MIG wire approved by ICAR

A wire suitable for castings repair or wrought and sheet work

Designed for high corrosion resistance and color matched smooth deposits on cast and sheet aluminum

Welding Positions: all positions

Tensile Strength: up to 25,000 psi

Elongation: 19% Operating Range: .030 (60-100 amps); .035 (100-160 amps) Shielding Gas: 100%Ar



STAR ALLOYS 5554 (ALUMINUM) SOLID WIRE

Wire Diameter	Spool Size	Part No.
1.2	5 lb.	F43197

Most common 5xxx filler alloy for welding 5454 base

Does not become sensitive to stress corrosion cracking at elevated temperatures

Higher ductility/formability AWS/ASME A5.10 ER554

Recommended by Ford for aluminum repair

Tensile Strength: up to 35,000 psi Elongation: 17%

Shielding Gas: 100% Argon

Operating Range: 1.2 mm (70-100 amps)



WELDING — TIG WIRE

220MS (MILD STEEL)

220MS (MILD STEEL)			STAR ALLOYS.
Diameter	Length	Package Size	Part No.
1/16"	36"	5 lbs.	F41995
3/32"	36"	5 lbs.	F42001
1/8"	36"	5 lbs.	F41996

Universal, all position, mild steel TIG alloy

Designed for welding all types of mild and common steels

Produces quality weld deposits with superb bead appearance Excellent for filling holes and general repair and fabrication applications

Tensile Strength: 85,000 psi

Yield Strength: 75,000 psi



Elongation: 22%

Recommended Current: DC Straight Polarity

Shielding Gas: Argon Product ID Flag Color: No Flag Tag

2200DS (DISSIMILAR STEEL)			STARALLOYS
Diameter	Length	Package Size	Part No.
1/16"	36"	5 lbs.	F42012
3/32"	36"	5 lbs.	F42014
1/8"	36"	5 lbs.	F42013

High alloy TIG wire for all tool steels

Designed to produce crack-free welds with very high mechanical properties

Ideal for emergency repairs on steels of unknown type Use on all carbon and alloy steels, all tool steels, manganese steel, and specialty steels

Use on any dissimilar metal combinations except for aluminum and copper alloys $\textbf{Tensile Strength:}\ 126,000\ psi$



Yield Strength: 90,000 psi

Elongation: 32% Heat Treatable: No

Recommended Current: DC Straight Polarity

Shielding Gas: Argon Product ID Flag Color: Light Blue

WELDING — TIG WIRE (continued)

38SS (STAINLESS STEELS)



Diameter	Length	Package Size	Part No.	
1/16"	36"	5 lbs.	F42022	
3/32"	36"	10 lbs.	F42027	
 Fast, smooth 	th corrosion-resistant	welds in all positions o	on 302, 304, 308, 309, 316, and 316L	

- stainless steels Used for fabricating and repair of normal and low carbon molybdenum-bearing austenitic
- stainless steels
- Can be used to overlay steel that must resist corrosion
- Used to weld pipes, fittings, tanks, etc. in paper mills, food processing, and chemical plants
- Tensile Strength: 80,000 psi



- Yield Strength: 56,000 psi
- Elongation: 42%
- Hardness: Brinell 209, Rockwell B96
- Recommended Current: DC Straight Polarity Shielding Gas: Argon
- Product ID Flag Color: Clear

STAR ALLOYS **PURGE ROD FLUX COATED SS** Package Flux Color Diameter Part No. Lenath Size

- 3/32" F43276 Yellow 5lbs. 6316 TIG Rod is an extremely low carbon stainless steel alloy with molybdenum added to provide superior corrosion resistence. It is especially well suited for welding stainless steel pipe wherever a backing ring or a purge gas is required in order to provide impurity free weldments
- A very special TIG that eliminates the expense and wasted time associated with purging pipes with inhert backing gasses Easy to handle 18" length works in multiple positions without having to bend the wire



- Tensile strength: 80.000 PSI
- Yield Strength: 56,000
- Elongation: 42% Hardness: Brinell 209, Rockwell B96
- Recommended Current: DC Straight polarity



- The ultimate TIG welding wire for all cast irons (except white)
- Use to weld heavy or thin sections of cast iron to itself or to steel
- Welds are fully machinable
- Parts to be joined should be clean and free of contaminants. Use DC Straight Polarity with a shielding gas of Argon or Helium. No preheat is necessary.
- Tensile Strength: 70,000 psi



- Yield Strength: 38,000 psi
- Hardness: 88-90 Rockwell B
- **Elongation:** up to 35% **Recommended Current:** DC Straight Polarity
- Shielding Gas: Argon
- Product ID Flag Color: Black

521AL (ALUMINUM)



STAR ALLOYS

Diameter	Length	Package Size	Part No.
1/16"	36"	5 lbs.	F42057
3/32"	36"	5 lbs.	F42062
1/8"	36"	5 lbs.	F42058

- Low heat, thin flowing, aluminum TIG alloy
- For use on all known weldable aluminums including dissimilar grades
- Deposits have good color match to aluminum
- Produces high strength welds with good electrical conductivity
- Use for joining all grades of aluminum sheet, cast, plate, tubing and piping, extrusions, rod,
- Commonly used to manufacture and repair furniture, truck bodies, window frames, instruments, and appliances



- Tensile Strength: up to 35,000 psi
- Elongation: up to 15%
- Working Temperature: 1070°F (575°C)
 Recommended Current: AC (High Frequency)
- Shielding Gas: Argon
- Product ID Flag Color: White

A2 (AIR HARDENING STEEL)



- High alloy TIG welding wire for Air Hardening Tool Steel
- Weld deposits are completely heat-treatable and have resistance to high abrasion, mild impact, and wear. Suitable for both hot and cold working applications
- Used to weld extrusion dies, punches, mandrels, trimmers, coining and forming dies
- Hardness: 45-50 RC as welded



- Maximum Hardness: 59-62 RC
- Heat Treatment: use A-2 procedure
- Recommended Current: DC Straight Polarity
- Shielding Gas: Argon
- Product ID Flag Color: Red

WELDING — TIG WIRE (continued)

H13 (HEAT-TREATABLE STEELS)



Diameter	Length	Package Size	Part No.	
1/16"	36"	5 lbs.	F42075	
 Premium quality, 	medium hardness al	lloy for most tool stee	ls	•

- Unique formulation makes this alloy outstanding for repair of all air hardened steels
- Weld deposits are highly crack resistant, forgeable, and temperable
- Multiple passes can be made
- Ideal for repair and build-up of tools and dies, shearing blades, planer plates, anvils, earth borers, pressure rollers, mixer arms, and dredger teeth



Hardness: 38-42 RC as welded

- Maximum Hardness: 59-61 RC
- **Heat Treatment:** use D-2 procedure **Recommended Current:** DC Straight Polarity
- **Shielding Gas:** M1 (Ar+CO2); M2+M3 (Ar+CO2+O2)
- Product ID Flag Color: Lime Green

P20 (HIGH TEMPERATURE STEEL)



Package Size Diameter Length Part No. 1/16" 36" F42077 5 lbs.

- Low alloyed, high temperature, solid TIG welding wire
- Outstanding for repair of many air hardened steels
- Weld deposits are highly crack resistant, forgeable, and temperable Multiple passes can be made
- Deposits offer good mechanical properties and toughness. Good resistance to cracking when attacked by caustic soda. Suitable for nitriding.



- Tensile Strength: 57,000 psi
- Elongation: 23%
- Recommended Current: DC Straight Polarity Shielding Gas: Argon + CO2 (15-25%)
- Product ID Flag Color: Yellow

S7 (SHOCK-RESISTANT TOOL STEEL)



Diameter	Length	Package Size	Part No.	
1/16"	36"	5 lbs.	F42079	

- High alloy TIG welding wire for shock resistant tool steels Weld deposits are highly shock resistant, dense, and completely heat treatable
- Excellent for medium hot, cold working, and metal to metal wear areas
- Retains high hardness at 600°F
 Primarily used on blanking dies, trimmer dies, bending dies, chisel points, hammer faces, punches, and most high shock, cold working applications



- Hardness: 54-58 RC as welded
- Maximum Hardness: 62 RC
- Heat Treatment: use S-7 procedure Recommended Current: DC Straight Polarity
- Shielding Gas: Argon
- Product ID Flag Color: Orange

WELDING — CABLE

WELDING CABLE

Gauge	Color	Roll	Part No.
	DII-	Length	F42242
#4	Black	25'	F42342
#4	Black	50'	F42343
#2	Black	25'	F42336
#2	Black	50'	F42337
#1	Black	25'	F42332
#1	Black	50'	F42333
1/0	Black	25'	F42330
1/0	Black	50'	F42331

Gauge	Color	Roll Length	Part No.
2/0	Black	25'	F42334
2/0	Black	50'	F42335
3/0	Black	25'	F42338
3/0	Black	50'	F42339
4/0	Black	25'	F42340
4/0	Black	50'	F42341

- Our all-weather cable defies cold, heat, a brasion, sunlight, moisture, oil, ozone, solvents and a sunlight of the cold, and the cold of the cold, and the cold, and the cold of the cold of the cold, and the cold of the cold of the cold, and the cold of the cold ofcomparison.
- Flex-a-prene 600 volt all-weather grade welding cable is rated at +105C to -50C.
- $Made\ with\ a\ special\ jacketing\ compound,\ this\ standard$
- stock welding cable gives you high flexibility without sacrificing weather resistance. Also used as battery cable.

WELDING — ACCESSORIES

WELDERS PENCILS


Description	Part No.
Silver-Streak®	F42405
Red-Riter®	F42407



 $Markal \, Silver-Streak \, and \, Red-Riter \, welders \, pencils \, make \, torch-resistant \, marks \, that \, will \, not \, burn \, or \, rub \, off \, continuous \, contin$ like soapstone. Ideal for fine line marking during metal layout and fabrication, these highly visible marks illuminate when cutting or welding.

ROD GUARD® CANISTERS

Description	Length	Part No.
Rod Guard [®] Canister	18"	F41078
Rod Guard [®] Canister	36"	F4766
High-Temperature Rod Guard® Canister	18"	F41257
Storage Rack	14" to 18"	F4573
Meter Storage Rack	36"	F4127



WELD CHIPPING HAMMER

"Safety Tomahawk"

Head Style Part No. Cone & Chisel

- Used for cleaning arc welding slag only
- Safety pinned head Induction hardened head
- "Flex-O" steel handle
- Approved eye protection should be worn



WELD CHIPPING HAMMER / BRUSH F41079

- Removes slag easily
- Wire brush for cleaning welds Metal Handle



GROUNDING CLAMP

F41553

- 300 amp capacity
- Copper alloy jaws, fully insulated spring
- 1-1/2" jaw opening 8" overall length
- Cable capacity: Ball Point 3/0 Tweco equivalent: GC-300



ELECTRODE HOLDER

F41490 • 250

- 250 amp capacity
- High copper alloy construction for optimum conductivity 3/16" electrode capacity

- 9-1/4" overall length

 Cable capacity: Ball Point 2/0

 Tweco equivalent: A316




WELDING TIP CLEANER SET

- Set features a blue anodized aluminum cover
- Contains 13 wires (wire sizes 6-26; drill sizes 77-49)
- Stainless steel wires have tapered ends for ease of entry and uniform ridges for optimum cleaning
 Use to clean welding, brazing, and soldering tips
- Also excellent for cleaning clogged orifices in sprinklers, shower heads, gas range burners, windshield washers, etc.

MIG CONTACT TIPS

Description	Wire Size	Part No.
Tweco Style 11	.023	F41572
Tweco Style 11	.030	F4189
Tweco Style 11	.035	F4168
Tweco Style 11	.045	F4893
Tweco Style 14	.023	F41594
Tweco Style 14	.030	F41232
Tweco Style 14	.035	F41593
Tweco Style 14	.045	F4394
Miller Style	.023	F41023
Miller Style	.030	F41248
Miller Style	.035	F41315
Miller Style	.045	F4917







Miller Style

MIG PARTS

Description	Part No.
Miller Style Nozzle	F4158
Miller Style Adapter	F41408
Tweco Style Nozzle	F4814
Tweco Style Adapter	F41113

Nozzles and Adapters for Tweco and Miller style guns











TUNGSTEN ELECTRODES

IONGSTEN ELECTRODES				
Color	Part No.			
Green	F4595			
Green	F41784			
Green	F41453			
Red	F4555			
Red	F41398			
Red	F4135			
Red	F41504			
Gold	F4770			
Gold	F41558			
	Green Green Red Red Red Red Gold			

Pure Tungsten electrodes are basically unalloyed; they contain a minimum of 99.5% tungsten. Pure Tungsten readily forms a ball on the end. Generally used for AC welding of aluminum. Principally used on Aluminum, Magnesium.

2% Thoriated Tungsten

WELDING — ACCESSORIES (continued)

The most common electrode used today. Generally used for DC welding of steel and stainless steel and offers good overall performance. This tungsten has a low-level radiation hazard. Principally used on Carbon Steels, Stainless Steels, Nickel, Nickel Alloys, Titanium, Copper Alloys.

1.5% Lanthanated Tungsten
Lanthanated tungsten is a popular substitute for 2% Thoriated tungsten. It offers good arc starting characteristics, longer life than 2% Thoriated, and no radiation hazard. It can be used for both AC and DC welding. Principally used on Carbon Steels, Stainless Steels, Nickel, Nickel Alloys, Titanium, Copper Alloys.



Tungsten electrodes for Gas Tungsten Arc Welding (GTAW) or TIG welding

- All electrodes are 7" in length
- Precision centerless ground to remove surface imperfections Made from the highest quality tungsten steel
- Sold 10 electrodes per box

SELF-IGNITING TORCH F43280

4

- Use MAPP or Propane gas
- Instant flame action
- Swirl combustion for high energy efficent flame that's stable even in windy conditions
- Operates in any position, even upside down Trigger lock with safety feature and instant release
- Perfect flame adjustment knob
- 360° Swirl tip
- Made in USA



CYLINDER TANK WRENCH



- 10 way wrench with socket for commercial acetylene
- 3/8" socket (actual .390)
- Dropped forged alloy steel for maximum durability Baked black powder coated finish for rust protection

OXY-ACETYLENE TWIN HOSES

I.D.	Length	Connection	Part No.
1/4"	25 ft.	B (9/16-18)	F4521
1/4"	50 ft.	B (9/16-18)	F4919

- Twin line hose (red cover for acetylene, green cover for oxygen)
- Grade R use with acetylene fuel gas only

SHURLITE*THREE FLINT **SPARK LIGHTER**



Description	Packaging	Part No.
Three Flint Renewal	1 per card	F41050
Three Flint Spark Lighter	1 per card	F4797

- Ignites under all working conditions
- Three flint design for three times as many lights
 Round file provides sharp surface for continuous sparking
- Durable round edges steel frame built to last
- Plated for rust prevention Made in USA



LIGHTNIN' BUG **TORCH LIGHTER** F41528

- Multi-spark discharge instantly ignites all fuel gases including
- oxyacetylene, propane, MAPP, etc.
 Zinc plated body resists rust and corrosion
- Long Life Never needs flints, batteries, or charging

SOAPSTONE MARKERS

Part No.	Description	
F4700	Flat Soapstone (single piece)	
F32860	Flat Soapstone (144/Box)	
F41322	Round Soapstone (single piece)	
F32861	Round Soapstone (144/Box)	
F4998	Flat Soapstone Holder	
F4825	Round Soapstone Holder	

- Made of natural soapstone for superior marking Use for temporary marking of metal surfaces during welding
- Marks will not contaminate welds and are easily removed
- Flat markers are 1/2" x 3/16" x 5"
- Round markers are 1/4" x 5"
- Sold by the single piece or by the box of one gross (144 pcs)



THERMOMELT INDICATOR MARKERS

Temperature Rating	Part No.
350°F (177°C)	F3602

- Accurate to within + 1% of rated temperature
- Melts instantly when surfaces reach rated temperatures
- All metal construction
- Bigger design makes Thermomelt® the industry's longest
- Meets ANSI/ASME B32.1 & B31.3; AWS D1.1 and ASME Code Sec. I. III and VII: NIST traceable



4-4-10

WELDING — **ACCESSORIES** (continued)





GROUND CLAMP MAGNET

Dimensions	Pull lbs.	Amps	Aprox. Weight	Part No.
3-1/2 x 23/32"	55	250	1.75	F4868
3-1/2 x 23/32"	55	800	1.85	F476

- Specifications:
- Stud height approx. 2-1/2" Spring loaded electrode secures ground to work surface
- Rotating stud assembly



ARROW MAGNET

•	Dimensions	Pull lbs.	Pre-set Angles	Aprox. Weight	Part No.
Ī	4x2-1/2x9/16	41	90°/45°	0.76	F41717



WELDER MAGNET

Dimensions	Pull lbs.	Pre-set Angles	Aprox. Weight	Part No.	
3-3/4 x 4-3/8 x 3/4	66	90°/45°	1.10	F41387	



CARRIAGE C-CLAMPS

Capacity	Throat Depth	Part No.	
0"-2"	1-1/8"	F4393	
0"-3"	2"	F41371	

- Ductile iron frame with black oxide screws, swivels, and sliding handle
- Designed for the home craftsman, woodworker, and light industrial service



FORGED C-CLAMPS

Capacity	Throat Depth	Min. Proof Test Lbs.	Part No.
0"-4"	2-3/4"	3,500	F4753
0"-6"	3-5/8"	6,900	F41665
0"-8"	4-1/2"	6,900	F41351

- Drop forged frame with extra deep throat
- Acme roll spindle threads provide maximum strength and clamping force Sliding pin handle with rounded, ergonomic ends





F41353

F41364

QUICK CONNECTORS WITHBUILT-IN CHECK VALVES

Description	Part No.
Hose to torch, Pair, w/Check Valve	F41353
Regulator to Hose, Pair, w/Check Valve	F41364

- Built-in automatic reset check valves prevent the reverse flow of gases The quick connect design eliminates hand threading of fittings

- 9/16-18 connectors ("B" fitting)
 Before disconnection, gases must be shut off at regulators
- Color coded for added safety
- Maximum working pressure: 29 psi for fuel gases; 145 psi for oxygen



CHECK VALVES

CITECK VALVES		
Description	Style	Part No.
Torch End Set, Pair	Attaches to torch with 9/16-18 "B" fitting	F4883
Regulator Adapter Set, Pair	Attaches to regulator outlet bushings	F4450

- Check valves prevent the reverse flow of gases The use of check valves between torch and regulator is recommended at all times
- 9/16-18 connectors ("B" fitting)

 Maximum working pressure: 29 psi for fuel gases; 145 psi for oxygen





F41219

F4425

FLASHBACK ARRESTORS

Capacity	Part No.
Torch Set	F4425
Regulator Set	F41219

- Specially designed to prevent personal injury and damage to equipment from severe flashback
 - 9/16-18 ("B" fitting)
- Sintered metal flame arresting filter quenches the flame from severe flashbacks Built-in automatic reset non-return valve prevents the reverse flow of gases
- by temporarily shutting off the gases

 Maximum working pressure: 15 psi for fuel gases; 145 psi for oxygen

WELDING — STUDS

F4473B500

- Uni-Spotter Welding Stud 2.6mm
- 500 lbs fusion strength
- Heavy duty stud
- Ideal for rockers, rails and post
- Copper coated finish
- 500 pc Clamshell Pack

F41570B500

- Uni-Spotter Welding Stud 2.2mm
- 500 lbs. fusion strength
- Super Flexible for hard-to-reach areas and compound pulls
- Copper coated finish
- 500 pc Clamshell Pack

WELDING — SOLDER

SILVER SOLDER SYRINGE

F41210

Five times stronger than regular solder

- Solders most metals
- Stress and vibration resistant
- Use with low heat



ROSIN CORE SOLDER

Tin	Lead	Diameter	Melting Point	Part No.
40%	60%	.125	460° F	F4172
60%	40%	.031	374° F	F41492
60%	40%	.062	374° F	F41211
60%	40%	.093	374° F	F4505



- Non-corrosive
- 1-pound roll



SOLID WIDE SOLDED

JOLID WINE JOLDEN		
Tin-Lead	Melting Temp.	Part No.
50/50	420° F	F4516

- For non-electrical repairs
- Use with Fluxpaste .125 diameter
- 1 pound roll

4



ACID CORE SOLDER

Tin-Lead	Melting Temp.	Part No.
40/60	460°F	F41599

- For non-electrical repairs Acid core provides the flux

- 1 pound roll



- 96/4 tin-silver
- Tensile Strength up to 15,000 PSI
- Melting Temp: 430° F Wire Dia: .0625" (1/16")

- Cadium Free FDA Approved, Non-Toxic
- Free of Zinc, Antimony and Lead

POCKET PAKROSIN CORE SOLDER

Tin	Lead	Diameter	Weight	Melting Point	Part No.
60%	40%	1/32"	.5 oz	374°F	F41661
60%	40%	3/64"	.75 oz	355°F	F41587

WELDING — CHEMICALS

COOL GEL HEAT BARRIER SPRAY

- Helps prevent heat damage to components and surrounding materials during soldering, brazing, and welding Clear, non-staining gel leaves no residue eliminating clean-up
- Safe, non-toxic, odorless Protects painted and finished surfaces discoloration due to
- adjacent torch operations Reduces risk of fire to surrounding surfaces such as rubber and
- plastic seals and gaskets Unique gelled formula sticks to surfaces without dripping and
- running off Easy to build thick layers
- Convenient 16 oz. trigger sprayer

SOLDERING FLUX PASTE

F4234

- 2 oz can
- Super detergent action cleans as it solders
- Water soluble for faster flushing from pipe lines
- Non-acid non-toxic, lead free
- Containe no zinc chloride
- Use with all lead-free and common soft solders
- For use on most metal types Meets Mil. Spec. Mil-F-4995 Type II

SOLDERING FLUX PASTE

F4962

- 4 oz. brush-in-cap can
- Super detergent action cleans as it solders Non-acid, non-toxic, lead-free
- Contains no zinc chloride
- Use with all common solders including tin-silver, 96/4, 94/6, 95/5, 50/50, 40/60, and 60/40
- For use on copper, brass, galvanized iron, lead, zinc, tin,
- silver, nickel, mild steel, terne plate, and malleable iron Certified to ANSI/NSF Std. 61 for use with potable water
- Water soluable for faster flushing from pipe lines
- Meets Mil. Spec. MIL-F-4995 Type II

CRC WELDER'S ANTI-SPATTER



- Advanced technology water-based, non-silicone anti-spatter lubricant
- Eliminates need to chisel, grind, or wire brush welding spatter
- Film is easily removed by wiping with cloth or rag Saves time, leaves surface ready for paint or protective coating
- Prevents flash rust of in-process and surrounding metal surfaces
- Low odor promotes better work environment and user comfort **Applications:** resistance welding tips, Mig and Tig tips, weldments, electrode holders, contact tips, tools, metal molds and bench top splash guards

NOZZLE GEL

F4677

- Welding gel lubricates nozzles and tips, prevents spatter buildup for longer nozzle life
- Recommended product for all MIG welders



STAR SHIELDHEAT RESISTANT COMPOUND

- An asbestos free, easy to mold, dual-purpose material used for insulating and positioning parts for welding, soldering, or brazing
- Shapes like putty and will not burn, crack, melt, swell, or interrupt alignment
- Protects plastics, rubber, glass, and paint from the effects of heat and with stands temperatures to 3000°F; stops heat transfer
- Reduces distortion when welding light gauge metals such as stainless steel
- Available in a 2 lb. container



WELDING — CHEMICALS (continued)

METALTEC 7100

F43173

- Brushable ceramic composite designed for coasting new and worn surfaces exposed to wet or dry particle abrasion, entrainment, frictional, wear, erosion, cavitation and corrosion
- Formulated with abrasion resistant ceramic fibers in various pre-calculated shapes and sizes, the unique chemistry produces a coating with ultra high compressive strengths to provide excellent adhesive strength and very high temperature resistance.
- Has consistency of heavy syrup for coating: pumps, valves, slurry lines, augers, feed screws, flue gas scrubbers, demineralizing beds, vacuum pumps, salt spreaders, exhaust fans, fertilizer dryers, heat exchangers, impellers, and chemical tanks.
- USDA accepted for incidental food contact
- 4.4Lbs.

HILO SILVER BRAZING FLUX F41819

- Formulated to be used in silver brazing applications
- Used on steel, stainless steel, copper, nickel, carbides, precious
- metals and heat resistent alloys
 The creamy-white silver brazing flux is active and protective to 1600°F
- Available in a 1 lb. container
- Meets AMS 3410 specifications



WELDING — SAFETY

PREMIUM TIG WELDING GLOVES

Size	One Pair
Medium	F4360
Large	F4223
X-Large	F4297



MetalTec™ 7100

BMETAL COMPONENT

- Premium grain kidskin for excellent softness and good durability
- Lined back blocks out heat along the back of hands and fingers Palm side is unlined for dexterity
- Reinforced palm rest provides extra protection while welding on hot surfaces
- Kevlar * stitched for strength and spark resistance
- Sold by the pair

ECONOMY WELDING GLOVES

One Pair

F4637

- Gray shoulder leather
- Lined
- Welts added to seams for strength
- Sold by the pair



PREMIUM WELDING GLOVES

Size	One Pair	
Medium	F4819	
Large	F4592	
X-Large	F41702	
Premium, blue side split cowhide for quality and durability		

- Double reinforced and full welting for cushioned comfort and heat insulation
- Kevlar stitched for strength and spark resistance
- Sold by the pair

FLAME RETARDANT WELDING JACKET

Size	Chest Measurement	Sleeve Measurement	Part No.
Medium	40-42	34	F41605
Large	44-46	34	F4889
X-Large	48-50	36	F4873
XX-Large	52-54	36	F41252



- 9 oz. flame retardant cotton welding jacket
- 30" length
- Color: Green
- Reinforced snap front and handy inside pocket

FIBERGLASS WELDING BLANKET F41752

- 24 oz. white fiberglass
- **Size:** 6' x 6' .050 thickness
- Melting Temperature: 1000°F



NEOPRENE COATED FIBERGLASS WELDING BLANKET

- 30 oz. gold neoprene coated fiber glass resists abrasion
- better than uncoated blankets
- Size: 6' x 6'
- .053 thickness
- Melting Temperature: 1000°F



HIGH PERFORMANCE WELDING BLANKET

Size	Part No.
6"x6"	F4903
6"x8"	F4612

- 16 oz. black carbon fiber felt material
- **Size:** 6' x 6'
- 170" thickness
- Working Temperature: 1800°F (3000°F Short Durations)
 Soft and flexible, flame-resistant material will not scratch delicate surfaces
- For heavy sparks, spatter, and slag. Limited abrasion resistance. Perfect for automotive applications



3M WELDING RESPIRATOR N95

3M Part No.	Respirator Per Box	Part No.
07189	10	F41132

- applications such as welding, cutting, grinding, and sanding Fiber media and protective layer of this respirator are flame resistant as
- demonstrated per ASTM D2859-96. Not a substitute for a faceshield. **3M Cool Flow™ exhalation valve improves comfort**
- "M" nose clip adjusts to many face shapes
- NIOSH approved



WELDING — EYE PROTECTION

CARRERA HELMETS

- True Color Technology
- Shade Control
- Grind Mode
- Sensitivity Delay
- Variable Delay
- View Area 7.1 Sq in
- Light state 4
- Dark state 9-13
- 25amps
- 4 sensors



VISION 911 HELMET

- Shade Control
- Grind Mode

- Light state 4
- Dark state 9-13



- True Color Technology
- Sensitivity Delay
- Variable Delay View Area 6sq in
- 25 amps
- 2 Sensors



VISION HELEMT LARGE

- HD Technology Best-in-class optical clarity&sensitivity X-Tig technology:ideal for low amp Tig welding
- large viewing area
- wide dark state shade range
- Comfagear headgear
- patented cover plate quick
- change system technology
- Shade Control
- Grind Mode Sensitivity Delay Variable Delay
- View Area 17sq in Light state 4
- Dark state 5-13
- X-Tig Mode
- 5 amps 4 Sensors
- Analog







REPLACEMENT FOR CARRERA HELMETS

Polycarbonate filter lenses offer impact resistance far superior

Clear, polycarbonate safety plates (.060" thickness) protect filter

F44949

F44950

F44951

F44952

F44953

Description

Sweatband

Inside Cover Plate

Outside Cover Plate

Control Center Section

Headgear Thumb Screw

lenses from slag, grit, and debris Meets all applicable ANSI standards

REPLACEMENT FOR VISION HELMETS

Description	Part No.
Inside Cover Plate	F44957
SweatBand	F44956

- Polycarbonate filter lenses offer impact resistance far superior to glass
- Clear, polycarbonate safety plates (.060" thickness) protect filter lenses from slag, grit, and debris Meets all applicable ANSI standards


ASTROSPEC WELDING GLASSES F41503

- UVEX "Spatula" style
- Adjustable temples and lens inclination Frame color black
- Lens 5.0 welding tint, hardcoat, replaceable



WELDING/BRAZING GOGGLES F41535

- $2'' \times 4$ -1/4" lift front welding/brazing goggles Vinyl face piece fits naturally to contour of face
- Adjustable elastic strap
- Supplied with replaceable shade 5 polycarbonate filter plate **Note: Do not use shade 5 filter plate for welding.**












FILTER LENSES AND SAFETY PLATES

Description	Part No.
2" x 4-1/4" Filter Lens, Shade 5	F41256
2" x 4-1/4" Filter Lens, Shade 10	F41720
4-1/2" x 5-1/4" Filter Lens, Shade 10	F492
2" x 4-1/4" Safety Lens, Clear	F4594
4-1/2" x 5-1/4" Safety Lens, Clear	F4351
Gold Glass Filter Plate HG10 4.5 X 5.25	F42089

- Polycarbonate filter lenses offer impact resistance far superior to glass
- Clear, polycarbonate safety plates (.060" thickness) protect filter lenses from slag, grit, and debris
- Meets all applicable ANSI standards

SAFETY — DISPOSABLE GLOVES

GLOVEWORKS™ HEAVY DUTY LATEX DISPOSABLE GLOVES





- Powder-free
- Industrial grade
- Extra thick (8 mil) for superior protection

XTREME X3D NITRILE DISPOSIBLE GLOVES POWDER-FREE

Size	Part No.
Small	F42344
Medium	F42346
Large	F42348
X-Large	F42350
XX-Large	F42352



Textured

POWDER-FREE

LIGHTLY POWDERED

Latex Free

Size

Small

Large

Size

Small

Large

Medium

X-Large XX-Large

Latex-free Industrial grade

Textured for a non-slip grip

Packed 100 gloves per box

X-Large

XX-Large

Medium

Packed 200 gloves per box

Part No.

F41380

F4199

F41165

Part No.

F41616

F4383

F4967 F41722

F41507

GLOVEWORKS™ NITRILE DISPOSABLE GLOVES +AMMEX

Color: Blue Comply's with FDA 21CFR, 170-199


GL&VEWORKS.

Available in powdered or powder-free

Thickness: 5mil Palm - 6mil Fingertip

Textured for superior wet or dry grip

GLOVEPLUS™ BLACK NITRILE DISPOSPABLE GLOVES POWDER-FREE





+AMMEX

Packed 100 gloves per box

Color: Natural

Thickness: 8 mil

- Color: Black
- Thickness: 5 mil Palm 6mil Fingertip
- Textured for a non-slip grip Powder-free

Industrial grade

NITRILE EXAM GRADE DISPOSABLE GLOVES

Size	Part No.
Small	F44295
Medium	F44296
Large	F44297
X-Large	F44298



- Medical grade Powder/Latex free
- Micro-roughened grip Superior comfort & strength

GLOVEPLUS™ HEAVY-DUTY NITRILE



Color: Blue

- Extra thick (8 mil) and Extra Long (12")
- Packed 50 gloves per box
- Exam grade

GLOVE WORKS HEAVY DUTY BLACK NITRILE DISPOSABLE GLOVES POWDER-FREE

Size	Part No.	
Medium	F44003	
Large	F44005	
X-Large	F44007	
XX-Large	F44009	
1		



- Latex Free
- Diamond Textured for incredible levels
- Industrial Grade of grip, wet or dry
- Powdered Free
 - Color: Black
 - Thickness: 6mil Palm 7mil Finger tips

XTREME X3™ NITRILE DISPOSABLE GLOVES

Size	Part No.
Small	F4578
Medium	F41302
Large	F4634
VIargo	E4607



- Sets the new standard utilizing thinwall technology for exceptional
- dexterity Powder and latex free
- Packed 100 gloves per box
- Color: Blue
 - Thickness: 3mil (excellent strength)

DISPOSABLE GLOVES POWDER-FREE

Size Part No. Medium F41052

- Textured for a better grip Color: Blue Thickness: 8mil
- **GLOVE WORKS HEAVY DUTY ORANGE NITRILE DISPOSABLE GLOVES** POWDER-FREE

Size	Part No.	
Medium	F43186	
Large	F43188	
X-Large	F43190	
XX-Large	F43192	Т



- Latex Free
- Industrial Grade of grip, wet or dry
- Powder Free
 Diamond Textured for incredible levels
- Color: Orange
- Thickness: 8mil Palm 9mil

HEAVY-DUTY LATEX EXAM GLOVES

POWDER-FREE	
Size	Part No.
Medium	F44800
Large	F44799
X-Large	F44801



- Exam-grade
- Color: Blue
- Powder-free




SAFETY — DISPOSABLE GLOVES (continued)

AMMEX NITRILE EXAM GLOVES

POWDER-FREE		
Size	Part No.	
Small	F44740	
Medium	F44741	
Large	F44743	
X-Large	F44742	
		T .



- Exam-grade Color: Black
- Powder-free
- Textured/micro-roughened
- Thickness: 4 Mil





+AMMEX

- Comfort and dexterity
- Wet and dry grip
- Powder-free Medical grade

GLOVEWORKS HD ROYAL BLUE NITRILE GLOVE

POWDER-FREE

Size	Part No.	
Medium	F44267	
Large	F44269	
X-Large	F44271	
XX-Large	F44273	
 Diamond Textured 		Thi




Thickness: 6mil Palm - 7mil Finger

- Beaded Cuff
- Powder-free
- Ambidextrous

resistance

Color: High Visibility Royal Blue

GLOVE WORKS HEAVY DUTY GREEN NITRILE DISPOSABLE GLOVES





- Industrial Grade of grip, wet or dry
- Powdered Free
- Color: Green
- Thickness: 8mil Palm 9mil
- Finger tips


RAVEN NITRILE GLOVES

MAVEN MITHIEL GLOVES		
Size	Part No.	
Small	F41860	
Medium	F41861	
Large	F41862	
X-Large	F41863	
XX-Large	F41864	



- 6 Mil Nitrile Beaded cuff with textured grip
- Powder Free Ambidextrous Superior puncture & abrasion

LATEX DISPOSABLE GLOVES POWDER-FREE





- Industrial Grade
- Powder Free Textured
- Polymer Coated
- Beaded Cuff
- Non-Sterile/Ambidextrous

THICKSTER™ LATEX DISPOSABLE GLOVES

Size	Part No.		
Medium	F41721		
Large	F41419		
X-Large	F4198		
XX-Large	F41776		
 Heavy duty late 	x construction		50 c

- Maximum strength/tear resistant
- Lightly powdered Textured grip



Thickness: 14 mil

DISPOSABLE GLOVE DISPENSER

F41071 Wall-mountable (comes with hardware) White, powder-coated wire dispenser Holds one box of disposable gloves



HEAVY DUTY DISPOSABLE GLOVE DISPENSER

- $Accommodates \, larger \, box \, of \, diamond \, textured \, gloves$
- Slot holes for vertical or horizontal wall mounting
- Heavy duty white coated-wire holds 1 box 5.67"W X 8/16"h X 3.75"D



Padded palms perfect for use with

SAFETY — GLOVES

Medium

Large

X-Large

PROFLEX HIGRIP GLOVES

Size	Part No.
Medium	F41296
Large	F41303
X-Large	F41240
Toyturad cilicana nalm an	dfingers \Ma

MECHANICS GLOVE BLACK

Excellent dexterity and flexibility Machine washable

Outstanding gripper power

Size

Large

X-Large

Medium

Padded breathable spandex back

Part No.

F42121

F42122

F42123

- Micro-injected closure
- Woven elastic cuff
- Neoprene knuckle pad

Spandex top for great flexibility and ease of movement

Terry cloth thumb brow wipe

PRO HANDLING GLOVE GREY

Size	Part No.	
Medium	F42115	
Large	F42116	
X-Large	F42117	
Machine washahle		 Sili

MECHANICS SAFTEY GLOVE BLACK

Part No.

F42128

F42129

F42130

Machine washable Outstanding protection against

knuckle injury

Greatly reduces skin abrasions and cuts



illicone strips on fingertips and palm for secure grip

pneumatic tools

Unparalleled comfort

MX'S SLIP ON GLOVE YELLOW

Size	Part No.
Medium	F42118
Large	F42119
X-Large	F42120

Part No.

F44100 F44101

F44102 F44103

Case of 48 Pairs

F07089

F07090

Machine washable Excellent dexterity and flexibility

CUT RESISTANT GLOVES

Level 3 cut protection HPPE

Durable latex textured grip Safety orange palm

comfortable machine knit shell

Gray liner helps conceal dirt and

Outstanding gripper power



Size	Part No.	
Small	F4826	
Medium	F4293	
Large	F4545	
X-Large	F41298	
F	1	

- Extensive asphalt reinforcement
- Full finger reinforcement
- Durable nylon fourchettes Internal knuckle protection
- Supportive FlexMesh™Cuff
- Sold by the pair

WATERPROOF WINTER GLOVE



- Waterproof, windproof, breathable membrane
- Insulating micro fleece liner and durable outer shell




- gusset Sold by the pair



NATURAL COTTON CANVAS GLOVES

0	n	e	P	ai	r

Large size



F455

Off-white color

Knit wrist

Size	Part No.
Large	F44427
X-Large	F44427

Size

Large

X-Large

resistance

Size

Large

X-Large

XX-Large

wear

Medium

- Nitrile Sandy Palm Coated TPR padding to protect fingers and

GREEN NITRILE GLOVES

One Pair

F41670

F4330

Abrasive, cut and puncture resistant

· Nitrile provides extensive chemical

Easily identifiable color coded cuff by size

impact protection

TPR bumpers offer back of hand

TPR IMPACT GLOVES

II IN INIII ACT GEOVES	
Size	Part No.
Large	F44427
X-Large	F44427

- Impact glove
- back of hand from impact
- A2 900 grams

Embossed wet/dry grip

13" length, 15 mil thick

ANSI/ISEA 105-2016

PREMIUM LEATHER DRIVER GLOVE

Size	Part No.	
Medium	F42124	
Large	F42125	
X-Large	F42126	
- Top grain pigekin		

- Top grain pigskin
- Straight thumb
- General purpose protection



- Strong & comfortable leather
- Excellent protection for grinding, cutting and dismantling

COTTON JERSEY GLOVES

One Pair Fits All

F4529

- Cotton Jersie provides light duty comfortable hand protection
- Brown color hides the dirt and extends the wear
- Men's size





F41236 12" Gauntlet







SAFETY — DISPOSABLE GLOVES (continued)

LEATHER DRIVERS GLOVES

Size	Part No.
Small	F41777
Medium	F41443
Large	F4500
X-Large	F4799

- Standard grain cowhide
- Straight thumb



- Unlined
- Sold by the pair

COTTON STRING GLOVES

Size	One Pair
Small	F4488
Large	F41091

- with Grip Dots
- Cotton/polyester blend



- Dotted on both sides
- Regular weight

CUT RESISTANT GLOVES

<u></u>	000100	
Size	One Pair	
Large	F44203	
X-Large	F44204	
XX-Large	F44205	
LI: Vie eveen	Matarial	I/wit

4

Hi Vis green Material HPPE/Nitrile Material



Knit wrist closure

Men's size

- Color coated hem for easy size ID
- Cut level 5 for ultimate protection



NITRILE PALM SAFETY GLOVES

One Pair
F4230

- Heavy Duty
- Blue nitrile palm coated
- Jersey lined



NITRILE COAT GLOVES W/CUFF

Size	One Pair
Large	F41725



NYLON SHELL / NITRILE COATED PALM

THE CONTRACTOR OF THE CONTRACT	
Size	Part No.
Medium	F4924
Large	F4769
X-Large	F41552

- Durable Nitrile Coating Provides excellent abrasive resistance and $offers\,protection\,against\,oils\,and$
- Stretch nylon shell feels like your working with your bare hands
- Form fitting and flexible
- Machine Washable

BROWN JERSEY GLOVES

Size	Туре	One Pair
Large	Unlined	F4370
Large	Lined	F4312

- Available lined or unlined
- Unlined gloves have a knit wrist



Lined gloves are slip-on style

STRING KNIT GLOVES

Size One Pair	
Medium	F4842
Large	F4481

- Cotton/Polyester blend
- Seamless and reversable design
- Can also be used as a glove liner for added warmth

COTTON IMPACT GLOVE - GREEN

One Pair

F44415

- Versatile cotton blend glove with TPR
- for multi use
- 100% woven cotton



LEATHER PALM WORK GLOVES

Size	One Pair	Case of 48 Pairs
Large	F41011	F07094
X-Large	F41396	F07095

- **Heavy Duty**
- Rubberized safety cuff
- Full feature deluxe work glove
- Wing thumb
- Large size

LEATHER PALM WORK GLOVES

One Pair	Case of 48 Pair	
F4991	F07093	

- Standard Duty
- Denim cuff
- Washable Reinforced patch palm
- Wing thumb
- Large size

KEVLAR® SHELL / NITRILE COATED PALM

Size	Part No.
Medium	F4251
Large	F41330
X-Large	F41413

Nitrile coating provides excellent abrasive resistance and offers protection against oil and greases

- Kevlar fiber is five times stronger
- than steel and offers exceptional cut
 - Machine Washable

NYLON SHELL / POLYURETHANE COATED PALM

THE CONTRACTOR OF THE CONTRACT	
Size	Part No.
Medium	F41152
Large	F4762
X-Large	F41712

- Polyurethane Palm coating provides unmatched grip and dexterity
 - Stretch nylon shell feels like you are working with your bare hands - keeps hands cool
 - Machine Washable

BAMBOO SHELL / LATEX COATED PALM

Size	Part No.
Medium	F4245
Large	F41650
X-Large	F4540

- Textured latex coating provides great grip and tough abrasion and puncture resistance
- Bamboo fabric is up to 4 times more absorbant than cotton
- Will not hold odor or grow fungus, even if left in moist conditions
- Machine washable (Lay flat to dry) Great for general material handling, tools, gardening, and yard work

SAFETY — GLOVES (continued)

LINEMAN'S GLOVE KIT

F41667 Kit includes:

- 14"L insulating red/black rubber glove
- Goatskin leather protector glove
- 12" protective storage bag
- Compliance:
- Meets or exceeds ASTM D120 Standard
- Meets International Standard 903, IEC-1988





- Keep gloves where you want 'em when you want 'em
- Easy to us, comfortable feel
- Clips to clothing, belts, tool belts and D-Rings
- Breakaway feature
- Dialectric / Non-conductive material

SAFETY — RESPIRATORS

HALF FACEPIECE REUSABLE RESPIRATOR

Part No.	Description
F44348	Small
F44349	Medium
F44360	Large
F44350	P100 Hepa Filter - Pair

- Combines comfort and convenience
- Comfortable soft, lightweight facepiece with easy-toadjust head straps
- NIOSH approved Can be disassembled, cleaned and reused
- Replaceable filters allow reuse of facepiece for cost savings
- Filters Sold Separately

WILLSON® DUST MASK



- Lightweight and disposable For relief from nuisance level dusts & mists (non-oil)
- Not NIOSH-Approved



3M EASI-CARE PAINT SPRAY RESPIRATOR ASSEMBLY

Part No. Description		3M Part No.
F41537	Medium Respirator Assembly	07192
F4228	Large Respirator Assembly	07193
F41349	P95 Filter (10 per Box)	07194
14.1.1		

- Maintenance free
- Recommended for spray painting lacquer, enamel, and pesticides
- NIOSH 42CFR84 approved
- Assembly includes: organic vapor respirator (1 ea.), P95 filter (2 ea.), and filter retainer (2 ea.)
- Replacement P95 filters are available (10 per box)

3M PARTICULATE RESPIRATOR N95

SMITARITEOLATE REST MATOR NOS		
Part No.	3M Part No.	Respirator Per Box
F41267	07185	10
NIOSII 40 SEDO 4		

- 3M recommended for grinding, sanding, and buffing 3M Cool Flow™ exhalation valve improves comfort
- "M" nose clip adjusts to many face shapes NIOSH certified as 95% efficient in removing solid and liquid particles (excluding those containing oils)

RESPIRATOR WIPES ALCOHOL FREE

Part No. **Packaging** F44359 100 per Dispensei

- Alcohol-free hygienic wipes
- Removes body oils and perspiration
- Used for cleaning respirators and other protective equipment



N95 PARTICULATE RESPIRATOR

Part No.	Packaging
F4664	2 Pack

- Inner foam provides a custom seal Dual head strap for optimum fit
- NIOSH-Approved TC-8A-3888



RM10 N95 RESPIRATOR

Part No.	Respirator Per Box
F487 20	
OE0/ officiant recoiratory protection in non-oil areas	

- 95% efficient respiratory protection in non-oil areas
- Maintenance-free construction
 Inside filter for lower breathing resistance
- Latex-free ultrasonic welded head-straps for secure seal
- Adjustable aluminum nose clip with foam strip to reduce the potential for eyewear fogging
- NIOSH approved for protection against particulate aerosols free of oils

3-PLY FACE MASK WITH EAR LOOPS

Part No.	Mask Per Box	
F44614	50	a de la companya de
99.5% bacterial filtra	ation protects from har	mful

- Spun bonded polypropylene; 3-layer, pleated
- Anti-fog sweat band across bridge of nose One size fits all
- Meets FDA requirements as specified in CFR Code 21





SAFETY — HEAD & FACE PROTECTION

HARD HATS

Part No.	Color
F44351	Orange
F44352	White
F44353	Yellow
F44354	Blue
F44355	Hi-Viz Green



- 6-point ratchet nylon suspension
- Light weight polyethylene Adjustable head cradle
- Soft brow band
- Meets ANSI 289.1-2003 Standard Type 1, Class G & E

STANDARD

Curved molded lens 8"x15-1/2" x.06" Thick Clear- **F41601**

FACESHIELDS Economy 8"x15-1/2" x.04" Thick Clear- **F41448**



HARD HATS

Part No.	Color	
F4347	Yellow	
C !		

- 6-point nylon suspension Quick-Slide sizing adjusts suspension from head sizes 6-12-8
- Molded from high density polyethylene for maxium protection
- Meets ANSI Z89.1-2003 standard type
- 1. class C, E & G requirements
- Made in the U.S.A.



DELUX

Aspherical Lens 8"x15-1/2" x.06Thick Clear- **F4597** Tint- F4101

*Use with F41577 Headgear only



OMEGA II FULL BRIM SFTY HELMET

Part No.	Color	
F44356	White	
 6 Point woven nyloi 	suspension	

- Accommodates chin strap
- Moisture wicking brow pad is removable, washable and replaceable
- Adjustment for head size 6.5 8
- SEI Certified



Padded sweat band

*Use with F41448, F41601, F4597, F41577 and F4101

· Non-slip ratchet adjustment Pin lock adjustment for top band

suspension Double cam visor lock



BUMP HAT

Part No.	Color	
F44357	White	
Cuasa cantilation for manifesture air sine dation		

- Cross ventilation for maximum air circulation
- Moisture wicking brow pad is removable, washable and replaceable
- Adjusts from head sizes 6.5 7.75
- Protects head from lacerations, minor bumps and bruises
- For use in areas where certified safety helmets are not required
- Not a hard hat

DELUX HEAD GEAR RATCHET ASSEMBLY

*Use with F41448, F4597



SAFETY — HEARING PROTECTION

BANDED EAR PLUGS

- Light weight and durable band
- Super soft, washable plugs
- NRR: 23



SILENCER EAR MUFFS F41547

- Adjustable, padded headband Soft, foam-padded earcups



REUSABLE CORDED EAR PLUGS F4977

- Super soft, washable plug
- Nylon cord Flip top cas
- NRR: 28



EAR MUFFS

F41285

- Adjustable, padded headband
- Soft, foam-padded earcups
- NRR: 25
- Yellow
- Made in the U.S.A.



4

SAFETY — **HEARING PROTECTION** (continued)

EAR PLUGS Part No.

F44554

F44555

F4262

F4287

NRR: 32 Sold by the box Description

Description

Uncorded

Corded

Tapered shape offers most comfortable fit for ear canal

Corded

No roll-down design for quick/easy fitting

Threads designed to create a stay-put seal

EAR PLUGS — DISPOSABLE FOAM Qty/Box

200 pair

100 pair

Extremely soft foam plug

Nvlon Dielectric cord

Advanced foam formulation

Excellent comfort

NRR: 30 dB

EAR PLUGS — ALLIANCE

Part No.	Qty/Box	Description	
F44666	200 pair	Uncorded	
F44667	100 pair	Corded	
Maica Paduction Patings MDD 22			



- Material: Polyurethane Foam
- Shape: Bullet
- Color: Orange
- Made in the U.S.A.

EAR PLUGS — HONOR

Part No.	Qty/Box	Description	
F44668	200 pair	Uncorded	
F44669	100 pair	Corded	
Maine Deduction Detines NDD 22			



- Material: Polyurethane Foam
- Shape: Wing Color: Yellow & Green
- Made in the U.S.A.



EAR PLUGS — GUARDIAN

Part No.	Qty/Box	Description
F44670	200 pair	Uncorded
F44671	100 pair	Corded

- Noise Reduction Rating: NRR 33
- Material: Polyurethane Foam
- Shape: Bell
- Color: Orange
- Made in the U.S.A.



EAR PLUGS - UNCORDED PAIR

- Smooth, dirt resistant surface Easy to roll down for quick and easy fitting
- Tapered design fits comfortably Soft polyurethane foam is hypoallergenic
- Noise Reduction Rating (NRR) 29 dB, CSA Class AL



EAR PLUG STATION

- Material: Foam
- NPR (max): 33 Usage: Single Use
- 100% PVC-Free
- 250 pair
- Independently tested to ANSI S3.19-1974
- Includes mounting bracket and hardware Made in the U.S.A.



EAR PLUGS — JUSTICE REUSABLE

Part No.	Qty/Box	Description
F44672	100 pair	Corded


- Noise Reduction Rating: NRR 27
- Material: Thermoplastic Rubber
- Shape: Flange Color: Blue
- Made in the U.S.A.



SAFETY — GLASSES

HERO SAFETY GLASSES

Part No.	Lens	
F44673	Clear	
F44674	Smoke	
F44675	Anti-Fog	
F44676	Indoor/Outdoor	



- Polycarbonate temples and single-piece wrap-around lens Scratch-resistant lenses provide 99% protection against harmful UV rays
- Meets or exceeds ANSI Z87.1-2010 standard requirements
- High-impact rated

SCOUT SAFETY GLASSES

Part No.	Lens
F44677	Clear
F44678	Smoke
F44679	Anti-Fog
F44680	Indoor/Outdoor
Polycarhonate	temples and single-piece wrap-arou



- ound lens
- Scratch-resistant lenses provide 99% protection against
- harmful UV rays Soft, non-slip rubber temple tips
- Meets or exceeds ANSI Z87.1-2010 standard requirements


FIDO SAFETY GLASSES

Part No.	Lens	
F44681	Clear	
F44682	Smoke	
F44683	Anti-Fog	
F44684	Indoor/Outdoor	
. Cnort comi fr	ama liahtuwiaht dasian	



- Sport, semi-frame, lightweight design Durable co-injection rubber temples with non-slip nose piece
- Scratch-resistant lenses provide 99% protection against harmful UV rays Meets or exceeds ANSI Z87.1-2015 standard requirements
- Lightweight clear lens with black temple tips

VULTURE SAFETY GLASSES





- Soft, rubber-tipped temples and nosepiece Lightweight design with polycarbonate lens
- Anti-fog coating is water-based and environmentally friendly





SAFETY — **GLASSES** (continued)

COBALT SAFETY GLASSES

Part No.	Lens	
F41033	Clear Lens	
F4311	Smoke Lens	
F4930	Polarized Lens	
 Lightweigh 	t Frame	



Wraparound design

Part No.


RAD-ATAC SAFETY GLASSES

	Part No.	Lens
	F4201	Clear Lens
	F41290	Smoke Lens
Rubber tipped temples		

- Polycarbonate lens
- Lightweight frame

MIRAGE SAFETY GLASSES

MIRAGE SAFETY GLASSES		
Part No.	Lens	
F41321	Clear Lens	
F41197	Smoke Lens	
Dual wraparound optically correct polycarbonate lens		



Sleek lightweight design



F4492 F4401 F41206 F41186 Polarized Lens

REVELATION SAFETY GLASSES

Lens

Clear Lens

Smoke Lens Amber Lens

- Impact resistant polycarbonate lens Adjustable temples fit most face sizes
- Non-slip rubber nose pad

MIRAGE RT SAFETY GLASSES

Part No.	Lens
F41664	Clear Lens
F4915	Smoke Lens
 Dual wraparound optically correct polycarbonate lens 	

- Sleek lightweight design
- Rubber tipped temples

RAD — APOCALYPSE SAFETY GLASSES

Part No.	Lens
F4860	Clear Lens
F41062	Smoke Lens



- Scratch resistant lens
- Includes neck cord

3M SECUREFIT SAFETY GLASSES



- Polycarbonate lense
- Absorbs 99.9% UVA and UVB
- Padded temple for added comfort
- Soft, adjustable nose pads

SHARK SAFETY GLASSES

CHIEF VISITOR GLASSES

Lens

Can be worn over prescription glasses

Clear Lens

Smoke Lens Integrally molded brow guard Reinforced sideshields

Part No.	Lens
F4182	Clear Lens
F41311	Smoke Lens
0	1 .

- One piece lens design
- Adjustable temples
- Frame color blue

Part No.

F41584


F4305

RAD — SEQUAL SAFETY GLASSES

Part No.	Lens
F4954	Clear Lens
F41580	Smoke Lens
Soft rubber	noseniece and temples

- Polycarbonate lens
- Lightweight design

CHEATERS SAFETY GLASSES		
Part No.	Lens Color	
F4357	Clear 1.0	
F41620	Clear 1.5	
F4110	Clear 2.0	
F41031	Clear 2.5	
F4619	Clear 3.0	
F41399	Smoke 1.5	
F4342	Smoke 2.0	



- Vented rubber no sepiece
- Magnification diopter molded into the lens

UVEX XC	SAFETY GLASSES
Part No.	Lens
F4755	Clear



- Made in the U.S.A.
 Passes ANSI Z87+ and MIL-PRF 31013
- HydroShield™ coating guarantees fog free lenses
- 99.9% UV protection
- Anti-Scratch lenses



TOUR-GUARD III SAFETY GLASSES W/DISPENSER

Part No.	Lens
F41592	Clear

- Dispenser contains 20 pair of Tour-Guard III Safety Glasses ANSI Z87.1-2003 High Impact Compliant
- Made in the U.S.A.





Part No.	Frame/Lens
F4190	Black/Clear
F41136	Black/Smoke
F41326	White/Clear
F4859	White/Smoke

- Sleek, lightweight design with wraparound temples Impact resistant polycarbonate lens
- Adjustable rubber nosepiece
- Meets ANSI 7871+
- Anti-fog lens coating

CLEAR SIDESHIELDS

F44278

- Fits easily over your prescription eyewear temples 2" wide x 1" high
- Does NOT meet ANSI Z87.1 + standards





4

SAFETY — EYE PROTECTION

PERFORATED GOGGLES

Clear anti-fog lens - F4818

- Perforated sideshields
- Elastic strap
- Fits over most prescription glasses



CHEMICAL GOGGLES

- Clear anti-fog lens F4336
 Indirect vents provides protection against chemical splashes
- NeoPrene strap

Color

red

Fits over most prescription glasses



ANTI-SPLASH/FOG GOGGLE

F41117

- Tough Duralite Polcarbonate Lens Anti-Fog Resistant Coating Large Lens Opening Fits Over

- & Saftey Glasses Wide Nasal Flare Fits Over Most Half-Mask Respirators
- Meets ANSI Z87.1 and Z94.3 Standards
- Made in the U.S.A.



EYE WASH STATIONS

Part No.	Description	
F4200	Eye Wash Station Refill 16 oz.	
F41193	Dual Eye Wash Station 2/16 oz.	

- Wall mountable
- For use wherever immediate eye and body flushing
- Once bottle is opened, discard and replace with refill



SAFETY NECK CORDS Part No. F4284

- black F41462
- Provides convenient access to safety eyeware Universal cords fit all safety glasses



LENS CLEANING TOWELETTES F4993

- Handy pocket size pre-moistened towelettes
- 100 towelettes per box Box serves as dispenser
- Cleans greasy & oily glasses while providing an antifog/anti-static coating

LARGE LENS CLEANING STATION F41324

- 1603 spray cleaning solution
- 1200 tissues

SAFETY — MISCELLANEOUS PROTECTION

3 PIECE RAIN SUIT

Size		Part No.	
Large		F4891	
X-Large		F4562	
XX-Large		F41049	
XXX-Large		F41276	
2.0:		 1.4	

- 3 Piece rain suit includes bib overall suspender and jacket with detachable hood
- .35mm PVC/Polyester
- Corduroy Collar
- Color: Yellow



KNEELING PAD

Size	Part No.
15-1/2×7	F41859
Challetin and allet Common and allering	

- Lightwaight foam rubber
- Comfortable and easy to use



PROFLEX STANDARD BACK SUPPORT

Size	Part No.
Medium	F41437
Large	F41112
X-Large	F41341
XX-Large	F41680
Patented non-co	anductive Sticky Finger * ctays

- Adjustable detachable suspenders Patented Power Panel *postitioners
- $\hbox{Durable spandex body material}$
- Strechable bias binding with zig-zag stitching



DELUXE KNEE PAD F41856 Plastic cap over tough nylon fabric soft

- foam rubber core Water and abrasive resistant
- Velcro closures
- Easy to use



NITROFOAM™ ALL TERRAIN KNEEPADS

- Durable all terrain cap Extremely comfortable to wear
- Model 507 is a compact style that offers complete protection
- Model 707 offers ultimate protection Double strap for comfort and flexibility
- Sold by the pair



Model 707

PROFLEX ECONOMY BACK SUPPORT

Size	Part No.	
Medium	F4522	
Large	F4948	
X-Large	F41338	
XX-Large	F41207	

- Economical spandex back
- Adjustable detachable suspenders
- Non-conductive polyproplene stays
- Strechable bias binding with zig-zag stitching
- Rubber track webbing



SAFETY — FALL PROTECTION

FALL PROTECTION - FALL TECH

At FallTech, we design and build products of the highest quality and offer them at reasonable prices. Our Personal Fall Arrest Systems meet or exceed the highest industry standards, including ANSI Z359.

FALL TECH - LANYARDS

Part No.	Description
F41865	Self Retracting Lanyard 10'
F41868	6' Shock Absorbing Lanyard

• FallTech also has a variety of positioning and restraint lanyards designed to prevent you from falling from your work position, giving you the ability to work hands free with complete security. All of our lanyards are designed to meet or exceed applicable OSHA and ANSI standards.



FALL TECH - HARNESS

Part No.	Description		
F41867	Full Body Harness Unifit w/pad		
F41866	Full Body Harness Unifit 3D		

All of our harnesses are proudly made by hand right here in the USA, and are truly a cut above. We start with the highest $quality\,polyester\,and\,aramid\,webbings\,and\,finish\,them\,off$ with our own proprietary hardware and accessory parts. Even our most basic harness webbing exceeds OSHA and ANSI requirements for tensile strength by more than 1,300 lbs



FALL TECH - FALL KIT

Part No.	Description
F41869	End User Fall Kits

All FallTech Combination Sets meet or exceed OSHA and ANSI standards



SAFETY — FIRST AID

10 PERSON FIRST AID KIT

Part No.	Description	Box Qty
F41128	Plastic Bandage	16 ct
F41708	Trauma Pad, 5" x 9"	1 ea.
F4759	Triangular Bandage, 40" x 40" x 56"	1 ea.
F41354	Sterile Gauze Pads, 3" x 3"	4ct
F41686	Antiseptic Wipes	10 ct
F4906	Burn Relief	6ct

^{*}This kit does not meet the ANSI 2015 Safety Standards

Part No.	Description	Box Qty
F41655	Cold Pack 4" x 5"	1 ea.
F41009	Cloth Tape, 1/2"x2.5 yds	1
F41625	Nitrile Exam Gloves	10 pr



- Treats 10 or more people
- 71 pieces
- Ideal for home, car, or small office

25 PERSON 16 UNIT FIRST AID KIT

F44335

Part No.	Description	Box Qty
F44330	CPR Mask, Scissors, Tape Roll	1
F44326	First Aid Guide	1
F43604	Hand Sanitizer Packets, 0.9g	10
F4389	Adhesive Fabric Bandages, 1"x3"	16
F4413	Triple antibiotic Ointment Packets, 0.5g	12
F44331	BZK Antiseptic Towlettes	10
F43603	First Aid/Burn Cream Packets, 0.9g	12
F43602	Burn Dressing, 4"x4"	1

Part No.	Description	Box Qty
F44325	Cold Pack, 4"x5"	1
F44332	Nitrile Exam Gloves	4
F44343	Sterile Gauze Pads, 3'x3"	4
F44324	Triangular Bandage, 40"x40"x56"	1
F4392	1 Eyewash, 1ozw/2 Eye Pads and Strips	1
F41708	Trauma Pad, 5"x9"	2
F41262	Conforming Gauze Rolls, 2"	2



- ANSI 2015 Compliant Carry handle or wall mountable
- Treats 25 people
- 84 pieces Single use packaging

SAFETY — **FIRST AID** (continued)

3 SHELF FIRST AID CABINET F44333

Part No.	Description	Box Qty
F4764	Extra-Strength Non-Aspirin	100
F4913	Antacid Tablets	100
F44326	First Aid Guide	1
F41625	Nitrile Exam Gloves	10
F43604	Hand Sanitizer Packets, 0.9g	10
F43603	First Aid/Burn Cream Packets, 0.9g	12
F41675	Burn Spray, 4 oz	1
F44341	Scissors	1
F44342	Tweezers	1
F44323	Hema-flex 5/9 Trauma Pad, 4"x4yd gauze, 2 Nitrile Gloves	1

100

10

10

Part No.	Description	Box Qty	
F44329	Sterile Gauze Pads, 4'x4"	10	
F43611	Elastic Bandage Wrap, 4"x5yd	1	
F43619	Sterile Eye Pads and Strips	4	
F44321	Eyewash, 4oz	1	
F43620	Heavy Woven Fabric Bandages, 2"x3"	10	
F41708	Trauma Pad, 5"x9"	1	
F41262	Conforming Gauze Rolls, 2"	2	
F41527	Adhesive Fabric Bandages, 1'x3"	100	
F4966	Fingertip and Knucle Fabric Bandages	50	
F4395	Triple Antifiotic Ointment Packets, 0.5g	25	
F41657	Alcohol Wipes	100	
F41551	Cold Pack, 6"x9"	1	
F44344	Waterproof Ta[pe, 1/2"x5yd	1	
F44324	Traiangular Bandage, 40"x40"x5"	2	



- ANSI 2015 Compliant Steel case with a handle and wall mount option Treats 100 150 people 657 pieces

5 SHELF FIRST AID CABINET F44334

CPR Face Shield

Cotton Tipped Applicators

Sterile Gauze Pads, 2"x2"

Sterile Gauze Pads, 3"x3"

F43615

F44320

F44327

F44343

Part No.	Description	Box Qty
F44336	Extra-Strength Pain Reliever	250
F44337	Conforming Gauze Rolls, 4"	1
F4255	Aspirin Tablets	100
F33334	Electrolyte Tablets	250
F44358	Allergy Tablets	50
F44338	Ibuprofen Tablets	250
F44319	Antacid Tablets	250
F44339	Cough & Sore Throat Lozenges	50
F4412	Triple Cut Adhesive Tape Roll, 2"	1
F43606	Hand Sanitizer, 4 oz	1
F43609	Padded Flexible Splint, 4.25" x 24"	1
F44326	First Aid Guide	1
F44340	Butterfly Closures	16
F41675	Burn Spray, 4 oz	1
F41022	Antiseptic Spray, 4 oz	1
F44341	Scissors	1
F43610	Rubber Tourniquet, 1" x 18"	1
F44342	Tweezers	1
F41628	Hema-Seal 8" x 10" Trauma Pad in 4" x 4 yd Gauze, 2 Nitrile Exam Gloves	1
F43615	CPR Face Shield	1
F41625	Nitrile Exam Gloves	10
F41626	Eyewash, 8 oz	1
F44320	Cotton Tipped Applicators	100
F43611	Elastic Bandage Wrap, 4" x 5 yd	1
F43619	Sterile Eye Pads and Strips	4
F44321	Eyewash, 4 oz	1

Part No.	Description	Box Qty
F41729	Ammonia Inhalants	10
F41527	Adhesive Fabric Bandages, 1" x 3"	100
F41482	Knuckle Fabric Bandages	40
F41385	Fingertip Fabric Bandages	40
F41602	Heavy Woven Fingertip Fabric Bandages	25
F41689	Adhesive Plastic Bandages, 3/4" x 3"	100
F4934	Providone-lodine Infection Control Wipes	50
F4395	Triple Antiobiotic Ointment Packets, 0.5g	25
F4793	Burn Gel Packets, 1/8 oz	25
F41347	Hydrocortisone Cream Packets, 0.9g	25
F4533	Adhesive Fabric Bandages, 2" x 4"	25
F41657	Alcohol Wipes	100
F4275	BZK Antiseptic Towelettes	50
F41039	Sterile Gauze Pads, 2"x 2" and 3" x 3"	48
F43612	Non Stick Pads, 3" x 4"	50
F4846	Spray-on Bandage, 3 oz	1
F43602	Burn Dressing, 4" x 4"	2
F44323	Hema-Flex 5x9 Trauma Pad in 4" x 4yd Gauze, 2 Nitrile Exam Gloves	2
F44325	Cold Pack, 4" x 5"	2
F44324	Triangular Bandage, 40" x 50" x 56"	2
F41708	Trauma Pad, 5" x 9"	2
F41262	Conforming Gauze Rolls, 2"	2



- ANSI 2015 Compliant Steel case with a handle and wall mount option Treats over 200 people 2133 pieces

SAFETY — **FIRST AID** (continued)

SMART COMPLIANCE FIRST AID KIT

- ANSI Standards CompliantSmartTab ezREfill System

- Eliminates disorganized supplies Clearly labeled compartments

- Easily accessible contents SAFETY HUB APP for maintaining inventory

25 PERSON KIT

Part No.	Description Box Qty	
F44462	Hand Sanitizer Packets	10 ct
F44445	Fabric Bandages 1" x 3"	25 ct
F44460	Bzk Antispetic Wipes	10 ct
F44529	Sterile Gauze Pad, 3" x 3"	10 ct
F44468	Tape, 1/2" x 5yd & 2 Conf Gauze	1 ea.
F44469	Scissors, Wire Handle, 4.5"	1 ea.
F44472	Cold Pack 4" x 5",	1 ea.
F44535	First Aid Guide Pack	1 ea.

Part No.	Description Box Qty	
F44475	Nitirle Gloves	4ct
F44476	Stainless Steel Tweezers, 3"	1 ea.
F44477	Eyewash, 1 oz Bot, 2 Pads	1 set
F44533	Burn Cream, 10/bag	10 bag
F44530	Burn Dressing, 4" x 4"	1 ea.
F44490	Antibiotic Ointment	10 bx
F44492	Cpr Mask and Triangular Bandage	1 set



50 PERSON KIT F44414

Part No.	Description	Box Qty
F44462	Hand Sanitizer Packets	10/bx
F44444	Plastic Band 1.5" x 1.5"	10/bx
F44445	Fabric Bandages 1" x 3"	25/bx
F44449	Fabric Fingertip Band	1/bx
F44528	Adhes Plast Band, 3/4" x 3"	50
F44459	Alcohol Wipes	20/bx
F44460	Bzk Antispetic Wipes	10/bx
F44531	2" x 2" Sterile Gauze Pad	10 ct
F44534	5" x 9" Trauma Pad	1/bag
F44529	Sterile Gauze Pad, 3" x 3"	10ct
F44468	Tape, 1/2" x 5yd & 2 Conf Gauze	1 set
F44469	Scissors, Wire Handle, 4.5"	1 ea.

Part No.	Description Box Qty	
F44470	Triangular Band 40' x 40" x 56"	1 set
F44472	Cold Pack 4" x 5"	1/bx
F44474	Cpr Mask, 2 Gloves Per/box	1 set
F44535	First Aid Guide Pack	1 ea.
F44475	Nitirle Gloves	4/bx
F44476	Stainless Steel Tweezers, 3"	1 ea.
F44478	1 oz Eyewash, 2 Pads, 5yd Tape	1 set
F44483	Aspirin, 10 x 2/bx	10/bx
F44485	Ext Strgth Non-aspirin, 10 x 2/bx	10/bx
F44486	First Aid Burn Cream	10/bx
F44488	Ibuprofen, 10 x 2/bx	10/bx
F44490	Antibiotic Ointment	10/bx



150 PERSON KIT F44413

Part No.	Description Box Qty	
F44462	Hand Sanitizer Packets,	10/bx
F44493	Conforming Gauze, 2" x 5 Yd	1 ea.
F44494	Burn Spray	4 oz
F44495	Antiseptic Spray	4 oz
F44552	Splinter Out	10 ct
F44553	Cotton Tipped Applicators	100 ct
F44444	Plastic Band 1.5" x 1.5"	10/bx
F44445	Fabric Bandages 1" x 3"	25/bx
F44446	Plastic Bandages 1" x 3"	25/bx
F44500	Conform Gauze Roll, 4" x 5 Yd 1 ea.	
F44551	Padded Flexible Splint, 4.25" x 24" 1 ea.	
F44459	Alcohol Wipes	20/bx
F44460	Bzk Antispetic Wipes	10/bx
F44531	2" x 2" Sterile Gauze Pad	10/ct
F44534	5" x 9" Trauma Pad,	1/bag
F44529	Sterile Gauze Pad, 3" x 3"	10/ct
F44507	Triangular Band	2/bx
F44469	Scissors, Wire Handle, 4.5"	1 ea.
F44472	Cold Pack 4" x 5"	1/bx
F44535	First Aid Guide Pack 1 ea.	
F44476	Stainless Steel Tweezers, 3"	1 ea.
F44478	1 oz Eyewash, 2 Pads, 5yd Tape	1 set

Part No.	Description Box Qty	
F44514	Cpr Mask, 4 Nitrile Gloves	1 set
F44515	Fabric Fingertip Band	20/bx
F44516	Nitrile Gloves	8/bx
F44517	1/2" x 5yd First Aid Tape	2/bx
F44518	2" x 5yd Elastic Band	1/bx
F44537	2" x 4" Fab Band(6),b'fly Band10	1 set
F44520	Fabric Knuckle Band	20/box
F44530	Burn Dressing, 4" x 4"	1 ea.
F44521	Eyewash, 4 oz	1 ea.
F44522	Tourniquet	1 ea.
F44524	Burn Cream	20/bx
F44525	Antibiotic Ointment	20/bx
F44526	Sting Wipes, 20, & Hydro Cr	1 set
F44544	Aspirin Tablets	100 ct
F44545	lbuprofen Tablets	100 ct
F44546	Extra-strength Non-aspirin Tables	100 ct
F44547	Antacid Tablets	100 ct
F44548	Woundseal Powder Packs	2 ct
F44549	Liquid Skin	4ct
F44550	Elovate 15 Glucose Slimpak	2 ct
F44527	2" Triple Cut Adhesive Roll	1 ea.




SAFETY — PERSONAL PROTECTION

BLOODBORNE PATHOGEN BODILY FLUID SPILL KIT

Kit Contents

Ricontents	
Qty.	Description
1	Plastic case 9"x 8-3/8"x 2-1/2"
1	Disposable gown w/full sleeves
2	Disposable shoe covers
1	Eye shield w/ear loop mask
2	Exam quality vinyl gloves, 1 pair
1	Red Z fluid solidifier, 21 gram
1	Biohazard Scoop with scraper
2	15"x 24" Biohazard Bags, 5 gal. capacity
2	Clear bags w/twist ties
3	Disposable clean-up towels
3	Antiseptic cleansing wipes (sting free)
2	5"x8" Germicidal (kills germs) wipe, covers 7.5 sq. ft.
1	Bodily Fluid Pick-Up Guide



Kit meets federal OSHA recommendations

Reusable plastic case can be easily carried or mounted on a wall



SWEATBANDS F41182

(bag of 25)



Deluxe full size (8-5/8" long)

ARTIC RADWEAR COOLING WRAP

> unwanted smells Heat stress safety management

Secure around neck by pulling through slot opening Reusable packaging design Safe and reusable, jobsite proven

Anti-microbial treated to help prevent mold build-up and

Lasts up to 5 hours, depending on humidity levels Dimensions: 26" x 8.25"

- Individually wrapped in plastic sleeves
- Color: blue

F44279



KLEENGUARD A40 COVERALLS

	Size	Case Count	Part No.	Part No. w/Hood
Ī	L	25	F41247	
	XL	25	F4647	F41768
Ī	XXL	25	F4798	F41063
	XXXL	25	F4848	

- Breathable, microporus film laminate material
- Passes NFPA 99 for antistatic materials Meets ANSI/ ISEA 101-1996 sizing standards

TYVEK COVERALLS

Size	Part No.
L	F44366
XL	F44368
XXL	F4774
XXXL	F4953
144.4	

- White coveralls
- Tyvek material
- Disposable
- Elastic border at wrists and ankles
- Zippered front
- Greater range of movement while stretching and bending



NECK SHADE F44380

- Contrasting Trim Detail
- Materials: Self Extinguishing Treated 100% Polyester Mesh
- Fits both cap-style and full brim hard hats

HOTHANDS HAND WARMER

Up to eight hours or more of long



lasting heat Ready-to-use Air-activated

Safe, natural heat Single-use, heat packs provide additional warmth.

2 warmers per pack Made in USA



HOTHANDS

PVC RUBBER BOOT 16"

Size	Part No.
8	F43600
9	F43517
10	F43518
11	F43516
12	F43519
13	F43515

- 16" Length One piece injection mold
- Black high molecular pvc compound Bar cleat outsole
- Over the sock style
- Plain toe
- Non-skid
- ANSI standard Z91 PT91



SHOF COVERS	
Color	Part No. 100/Pack
White	F41304
 100% spun bond po 	

- Skid-free sole sleeves
- One size fits most



HOTHANDS TOE WARMER

- Up to eight hours or more of long lasting heat
- Ready-to-use
- Air-activated
- Safe, natural heat
- Single-use, heat packs provide additional warmth
 - 2 per pack
- Made in USA





SAFETY — **PERSONAL PROTECTION** (continued)

SAFETY T-SHIRT LIME

Size	Part No.
Medium	F44361
Large	F44363
X-Large	F44364

- Hi-Viz Lime 100% polyester birdseye mesh Moisture wicking
- Left chest pocket ANSI Class 2
- Conforms to ANSI/ISEA 107-2015



SAFETY VEST - ECONOMY CLASS 2

Size	Part No.
Large	F41660
X-Large	F41261
XX-Large	F41633
XXX-Large	F41378

- **Closure:** Hook & Loop 2" Silver tape reflective material, 1 Horizontal stripe Color: Hi-viz green
- Material: 100% polyestermesh
- Meet requirenebts of ansi/Isea 107-2004



SAFETY VEST - BREAK-AWAY CLASS 2

Size	Part No.	
SM/XLG	F43713	
2XL/5XL	F43714	

- 5 Point Break-Away Front Zipper Closure
- 2 nylon microphone tabs
- 5 pockets
- Meets ANSI/ISEA 1-7 Class II & 207-2006 Standards



SAFETY VEST - STANDARD

CL	_A	S	S	3

4

Size	Color	Part No.
Medium	Hi-Viz Green	F41272
Large	Hi-Viz Green	F4740
X-Large	Hi-Viz Green	F4551
XX-Large	Hi-Viz Green	F41131
XXX-Large	Hi-Viz Green	F41726
Medium	Hi-Viz Orange	F4489
Large	Hi-Viz Orange	F4927
X-Large	Hi-Viz Orange	F4337
XX-Large	Hi-Viz Orange	F41361
XXX-Large	Hi-Viz Orange	F41562

- Closure: Zipper
- 2" Silver tape reflective material, 2 Horizontal stripe

 Material: 100% polyestermesh

 Pockets: 2 each upper outside, 2 ea lower inside

- Meet requirements of ansi/Isea 107-2004



STAKE FLAGS

Flag Size	Stem Length	Color	Part No.
2-12" x 3-1/2"	21	Yellow	F41656
2-12" x 3-1/2"	21	Blue	F4663
2-12" x 3-1/2"	21	Orange	F4422
2-12" x 3-1/2"	21	Red	F41479

- For marking gas, water, or electric lines on construction sites
- Each flag is glued to its metal stem and will not slip or slide



WET FLOOR SIGN - YELLOW

- Professional quality, two-sided sign
- Specially contoured feet to minimize contact with floor to floor finishes
- Durable Polypropylene; 25" tall x 11" wide
- BPA free



SAFETY CONES

Size	Part No.	
12"	F41220	
18"	F4344	
28"	F4355	

- Brillant Red-Orange with UV inhibitor 100% PVC Injected Molded cone
- Environmentally Friendly-100% Recyclable

