

Carnivore Super Powder

With Enzymes

TECHNICAL DATA SHEET



Extra High Potency Bacterial Digestant

DIRECTIONS: Aerobic and Anaerobic Digesters: Use 11/2 pounds per week for every 1000 cubic feet (7,500 gallons) of capacity. When a heavy scum blanket or grease layer is present, double the treatment amount. Wet Wells, Lift Stations, Sewer Mains and Laterals: Add 1 to 2 pounds per 500 cubic feet (3,750 gallons) directly into the wet well or lift station . Treat laterals during periods of low flow . For every 500 feet of length, use 1 pound per 8 inches of pipe diameter. Lagoons: To reduce odors, sludge build -up, and improve clarification, use 1 to 4 pounds weekly per 50,000 gallons of lagoon capacity. Trickling Filters: Use an initial treatment of 6 to 12 pounds per million gallons of daily flow. Repeat this treatment after 48 hours. For maintenance, use 3 to 6 pounds weekly per million gallons of daily flow . Septic Systems : Use 1 pound for every 1000 gallons of system capacity (or 1 pound for every 5 people using the system) as an initial treatment, ideally added directly to the septic tank. For maintenance, flush into the toilet 1 pound per week . NOTE: To keep drain fields and leech beds operating properly, add 1 pound directly into the distribution box. Repeat this treatment weekly until flow is improved . Pit Toilets: To reduce odors, increase capacity and liquefy solids in pit toilets, use 1 pound per 1000 gallons of capacity per week. NOTE: Discontinue the use of formaldehyde preservatives or disinfectants in these toilets.

<u>Ingredients</u>	<u>C.A.S. #</u>
Sodium Chloride	
Yeast Culture	No CAS Number
Genes Bacillus	68038-68-6
Sodium Bicarbonate	144-55-8
Enzyme Blend	No CAS Number

HMIS	
Enzyme Blend	No CAS Number
Sodium Bicarbonate	144-55-8
Genes Bacillus	68038-68-6
Yeast Culture	No CAS Number
Sodium Chloride	

U	5	d	y	е	•
					,

- Lagoons
- Septic Tanks
- Grease Traps
- Sewage Treatment Plants
- Dairy Product Plants
- Meat & Poultry Plants
- Rendering Plants

Form: Powder Color: Tan Odor: Yeast-like

pH: N/A

Solubility (in water): Soluble (in mineral spirits): Insoluble VOC Content (% by weight): N/A Flash Point (ASTM D-7821): N/A

Specific Gravity: N/A

Density: N/A

Storage Stability (at 70 F): 3-5 years

HMIS				NFPA
	Severe	4	Extreme	
Health0	Serious	3	High	Health0
Flammability0	Moderate	2	Moderate	Flammability0
Reactivity0	Slight	1	Slight	Reactivity0
Personal Protection None	Minimal	0	Insignificant	Special PrecautionsNone



